

Left Side
Connector(s): LC-Duplex Secure
Mode: MM
Housing Color: Rose
Geom. Spec: N/A

A - _____ - B
B - _____ - A

Connector(s): LC-Duplex
Mode: MM
Housing Color: Beige
Geom. Spec: N/A

- 1 Product and Processing must meet requirements of Tyco Electronics Standard 230-702
- 2 Includes dust caps (not shown on print).
- 3 IL tested at 1300nm.
- 4 Label 2 will not be present on any cable assembly less than 5 meters long.

A		Rev Per EC# RELEASE	12/7/2007	-	J
P	LTR	REVISION RECORD	DATE	DIN	A

DIMENSIONS:
meters



TOLERANCES UNLESS OTHERWISE SPECIFIED		
0 PLC	$\pm$	-
1 PLC	$\pm$	-
2 PLC	$\pm$	-
3 PLC	$\pm$	-
4 PLC	$\pm$	-

Restricted To:

DIN Cable Assy Configurator		MATERIAL	HEAT TREAT	
GSK Jeremy Duncan		-		
APVD Jeremy Duncan		 Tyco Electronics, Inc. Harrisburg, PA 17105-3608		
NAME FO C/A - 2 fiber, XG - 50/125, OFNR (Riser) jacket, LC-Duplex Secure to LC-Duplex				
SCALE NTS	SIZE A2	DRAWING NO C- 1906095	SHEET 1 of 4	REV A

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION. IT IS NOT TO BE DISCLOSED TO ANY OTHERS WITHOUT THE WRITTEN AUTHORIZATION OF TYCO ELECTRONICS CORPORATION, HARRISBURG, PENNSYLVANIA.

THIS DRAWING IS A CONTROLLED DOCUMENT.
PAGE NO

LOC
CE
DIST
16

CAC Customer Layout Rev: D

Part #	L (meters)	L (feet)	LC-Duplex Secure, Rose			LC-Duplex, Beige		
			IL	(dB)	RL (dB)	IL	(dB)	RL (dB)
0-1906095-1	0.950 - 1.050	3.11 - 3.44	0.5	-	-	0.5	-	-
0-1906095-2	1.950 - 2.050	6.39 - 6.72	0.5	-	-	0.5	-	-
0-1906095-3	2.950 - 3.050	9.67 - 10.00	0.5	-	-	0.5	-	-
0-1906095-4	3.920 - 4.080	12.86 - 13.38	0.51	-	-	0.51	-	-
0-1906095-5	4.920 - 5.080	16.14 - 16.66	0.51	-	-	0.51	-	-
0-1906095-6	5.920 - 6.080	19.42 - 19.94	0.51	-	-	0.51	-	-
0-1906095-7	6.920 - 7.080	22.70 - 23.22	0.51	-	-	0.51	-	-
0-1906095-8	7.920 - 8.080	25.98 - 26.50	0.51	-	-	0.51	-	-
0-1906095-9	8.850 - 9.150	29.03 - 30.01	0.51	-	-	0.51	-	-
1-1906095-0	9.850 - 10.150	32.31 - 33.30	0.52	-	-	0.52	-	-
1-1906095-1	10.850 - 11.150	35.59 - 36.58	0.52	-	-	0.52	-	-
1-1906095-2	11.850 - 12.150	38.87 - 39.86	0.52	-	-	0.52	-	-
1-1906095-3	12.850 - 13.150	42.15 - 43.14	0.52	-	-	0.52	-	-
1-1906095-4	13.850 - 14.150	45.43 - 46.42	0.52	-	-	0.52	-	-
1-1906095-5	14.850 - 15.150	48.72 - 49.70	0.52	-	-	0.52	-	-
1-1906095-6	15.840 - 16.160	51.96 - 53.01	0.52	-	-	0.52	-	-
1-1906095-7	16.830 - 17.170	55.21 - 56.33	0.53	-	-	0.53	-	-
1-1906095-8	17.820 - 18.180	58.46 - 59.64	0.53	-	-	0.53	-	-
1-1906095-9	18.810 - 19.190	61.71 - 62.95	0.53	-	-	0.53	-	-
2-1906095-0	19.800 - 20.200	64.96 - 66.27	0.53	-	-	0.53	-	-
2-1906095-1	20.790 - 21.210	68.20 - 69.58	0.53	-	-	0.53	-	-
2-1906095-2	21.780 - 22.220	71.45 - 72.90	0.53	-	-	0.53	-	-
2-1906095-3	22.770 - 23.230	74.70 - 76.21	0.53	-	-	0.53	-	-
2-1906095-4	23.760 - 24.240	77.95 - 79.52	0.54	-	-	0.54	-	-
2-1906095-5	24.750 - 25.250	81.20 - 82.84	0.54	-	-	0.54	-	-
2-1906095-6	25.740 - 26.260	84.44 - 86.15	0.54	-	-	0.54	-	-
2-1906095-7	26.730 - 27.270	87.69 - 89.46	0.54	-	-	0.54	-	-
2-1906095-8	27.720 - 28.280	90.94 - 92.78	0.54	-	-	0.54	-	-
2-1906095-9	28.710 - 29.290	94.19 - 96.09	0.54	-	-	0.54	-	-
3-1906095-0	29.700 - 30.300	97.44 - 99.40	0.55	-	-	0.55	-	-
3-1906095-1	30.690 - 31.310	100.68 - 102.72	0.55	-	-	0.55	-	-
3-1906095-2	31.680 - 32.320	103.93 - 106.03	0.55	-	-	0.55	-	-
3-1906095-3	32.670 - 33.330	107.18 - 109.35	0.55	-	-	0.55	-	-
3-1906095-4	33.660 - 34.340	110.43 - 112.66	0.55	-	-	0.55	-	-
3-1906095-5	34.650 - 35.350	113.68 - 115.97	0.55	-	-	0.55	-	-
3-1906095-6	35.640 - 36.360	116.92 - 119.29	0.55	-	-	0.55	-	-
3-1906095-7	36.630 - 37.370	120.17 - 122.60	0.56	-	-	0.56	-	-
3-1906095-8	37.620 - 38.380	123.42 - 125.91	0.56	-	-	0.56	-	-
3-1906095-9	38.610 - 39.390	126.67 - 129.23	0.56	-	-	0.56	-	-
4-1906095-0	39.600 - 40.400	129.92 - 132.54	0.56	-	-	0.56	-	-
4-1906095-1	40.590 - 41.410	133.16 - 135.85	0.56	-	-	0.56	-	-
4-1906095-2	41.580 - 42.420	136.41 - 139.17	0.56	-	-	0.56	-	-

Qty	U of M	Description	Item No.
2	piece	Trace Label	7
4	piece	Eyelet/Shrink tube assembly - White	6
AR	meter	2 Fiber, XG-50/125, 2.0mm, Twinzip, Aqua, OFNR (Riser)	5
2	piece	LC Connector Assy, 1.6mm-2.0mm, MM	4
2	piece	LC Connector Assy, MM	3
2	piece	LC Duplex clip, black	2
4	piece	LC, SC, FC Straight Boot, Beige	1

DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:	
meters		0 P.L.C.	± .
		1 P.L.C.	± .
		2 P.L.C.	± .
		3 P.L.C.	± .
		4 P.L.C.	± .

Restricted To:

DIN Cable Assy Configurator		MATERIAL -	HEAT TREAT -	
CHK Jeremy Duncan	AMP Tyco Electronics, Inc. Harrisburg, PA 17105-3608			
APVD Jeremy Duncan				
NAME FO C/A - 2 fiber, XG - 50/125, OFNR (Riser) jacket, LC-Duplex Secure to LC-Duplex				
SCALE NTS	SIZE A2	DRAWING NO C- 1906095	SHEET 2 of 4	REV A

8 7 6 5 4 3 2 1

THIS DRAWING IS A CONTROLLED DOCUMENT.

LOC
CE
DIST
16

CAC Customer Layout Rev: D

	A	Rev Per EC#	RELEASE	12/7/2007	- JG
P	LTR	REVISION RECORD		DATE	DIN AP

DIMENSIONS; meters		TOLERANCES UNLESS OTHERWISE SPECIFIED	
	0 PLC	±	-
	1 PLC	±	-
	2 PLC	±	-
	3 PLC	±	-
	PLC	±	-

	C
	C
	E
	A

LOC
CE
DIST
16

CAC Customer Layout Rev: D

8

7

6

5

4

3

2

1

Label 1

Per specification 107-1645-1



-Trace # - Bar Code

-Trace # - Human Readable

Logo

Made in XXXX

X-XXXXXXXX-X

-Part Number

Country of Origin

This label is used on all lengths on this drawing.

Label 2

Per specification 107-1645-1



—Trace # - Bar Code

—Trace # - Human Readable

Logo

Made in XXXX

X-XXXXXXXX-X

—Part Number

—Country of Origin

This label is used on all lengths on this drawing.

	A	Rev Per EC#	RELEASE	12/7/2007	-	JC	
P	LTR	REVISION RECORD			DATE	DIN	AP

DIMENSIONS;
meters

TOLERANCES UNLESS OTHERWISE SPECIFIED		
0 PLC	$\pm$	-
1 PLC	$\pm$	-
2 PLC	$\pm$	-
3 PLC	$\pm$	-
4 PLC	$\pm$	-

Restricted To:

DN Cable Assy Configurator		MATERIAL -		HEAT TREAT -	
CHK Jeremy Duncan					
APVD Jeremy Duncan					
NAME FO C/A - 2 fiber, XG - 50/125, OFNR (Riser) jacket, LC-Duplex					
Secure to LC-Duplex					
SCALE NTS	SIZE A2	DRAWING NO C- 1906095	SHEET 4 of 4	REV A	

D

C

B

A