

RELAYS, CONTACTORS & SWITCHES

## **TACTILE SWITCHES**





✓ Active

<u>+</u>

PRODUCT DRAWING



3D PDF

TE CONNECTIVITY (TE)

FSM4LPATR=TACT SWITCH,SMT,T&R

Alcoswitch | FSM4LP

4-1437565-3

TE Internal Number: 4-1437565-3

Alias ID: FSM4LPA

Always EU RoHS/ELV Compliant

Actuator Style Round

Operating Function No

Contact Base Material Phosphor Bronze

Contact Plating Silver

Dust Proof No

**Product Drawings** 

TACTILE SWITCH 6X6mm LOW PROFILE, SURFACE MOUNT

PDF **English** 

**CAD Files** 

Customer View Model

2D\_DXF.ZIP English

3D PDF

PDF **3D** 

Customer View Model

3D\_IGS.ZIP English

**Customer View Model** 

3D\_STP.ZIP English

Catalog Pages/Data Sheets

SWITCHES\_CORE\_PROGRAM\_CATALOG

PDF **English** 

Product Environmental Compliance

TE Material Declaration

MD\_4-1437565-3\_012020132210\_dmtec

PDF **English** 

Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

**Product Type Features** 

Actuator Style

Round

Dust Proof

No

Illuminatad

NI\_

	шитшаеч	IAO
	Leg Style	Standard
	Product Type	Switch
Configuration Features	Operating Function	No
	Support Bracket	Without
	Configuration (Pole-Throw)	Single Pole - Single Throw
	Number of Actuators	1
	Ganged	With
	ESD Grounding Terminal	Without
	Tactile	Yes
	Snap Action	Without
	Tactile Feel	With
Body Features	Actuator Color	Red
Body Features	Bushing Style	Unthreaded
	Actuator Material	Nylon
	Actuator Force	260 g [ 9.178 oz ]
	Cover Material	Steel
	Actuator Profile	Extended
	Case Material	PPS
	Case Color	Black
Contact Features	Contact Base Material	Phosphor Bronze
	Contact Plating	Silver
	Contact Current Rating (mA)	50
Termination Features	Termination Type	Printed Circuit Board
Mechanical Attachment	Mounting Type	Surface Mount
	Mounting Angle	Vertical
Housing Features	Low Profile	With
	Process Sealed	No
Dimonsions	Agticator Longith	17mm [ 047 in ]

Actuator Length

Switch Height (in)

1.7 mm [ .067 in ]

.169

Dimensions

Button Width	2.3 mm [ .118 in ]	ı
--------------	--------------------	---

Usage Conditions	Temperature Rating (°C)	Standard
Packaging Features	Packaging Method	Tape & Reel
Other	Comment	(On) indicates momentary position.
Product Compliance	Statement of Compliance	

VIEW ALL PRODUCT COMPLIANCE