

CONNECTOR HOUSINGS

















TE Internal Number: 776164-1

Connector Style Housing for female terminals

35 POS AMP SEAL PLUG ASSY BLK

Mating Pin Diameter 1.3 mm [.051 in]

Number of Positions 35

TE CONNECTIVITY (TE)

AMP | AMPSEAL

776164-1

Pitch 4 mm [.157 in]

Sealed **Yes**



PRODUCT DRAWING



3D PDF

Product Drawings

PLUG ASSEMBLY, AMPSEAL FAMILY DRAWING

PDF **English**

CAD Files

Customer View Model

2D_DXF.ZIP English

3D PDF

PDF **3D**

Customer View Model

3D_IGS.ZIP English

Customer View Model

3D STP.ZIP English

Product Specifications

Application Specification AMPSEAL Automotive Plug Connector And Header Assembly

PDF **English**

Instruction Sheets

Instruction Sheet (U.S.) AMPSEAL Automotive Plug Assemblies 776268-[], 776273-[], 770680-[], And

776164-[]

PDF **English**

Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

	Sealed	Yes
	Hybrid Connector	No
	Primary Locking Feature	Integrated in Housing
	Connector System	Wire-to-Board/Device
	Row-to-Row Spacing	.157 mm [4 in]
	Strain Relief	Add By Accessory
Configuration Features	Number of Positions	35
	Number of Rows	3
Electrical Characteristics	Nominal Voltage Architecture (V)	12, 24, 42, 48, 80, 90, 125, 240
	Operating Voltage (VAC)	250
Body Features	Cable Exit Angle	180°
	Body Material	Other
	Color	Black
Contact Features	Mating Pin Diameter	1.3 mm [.051 in]
Mechanical Attachment	Terminal Position Assurance	Yes
	Mounting Feature	No
	Polarized	Yes
Housing Features	Pitch	4 mm [.157 in]
Dimensions	Width	33.6 mm [1.323 in]
	Height	34.6 mm [1.362 in]
	Length	63.4 mm [2.496 in]
Usage Conditions		
	Operating Temperature Range	-40 – 125 °C [-40 – 257 °F]
Industry Standards	Operating Temperature Range Degree of Protection	-40 - 125 °C [-40 - 257 °F]
Industry Standards		
	Degree of Protection UL Flammability Rating	IP6K9K UL 94V-0
Industry Standards Packaging Features	Degree of Protection UL Flammability Rating Packaging Method	IP6K9K UL 94V-0 Package
	Degree of Protection UL Flammability Rating	IP6K9K UL 94V-0

No

Yes


Serviceable

Product Compliance


Statement of Compliance

VIEW ALL PRODUCT COMPLIANCE

CUSTOMERS ALSO BOUGHT







RELATIONSHIP

Cavity Plugs
Cavity Plugs

See All Cavity Plugs



Connectors - Seals & Cavity Plugs AMP I AMPSEAL

SEAL PLUG, AMPSEAL - 770678-1 TE INTERNAL NUMBER: 770678-1 ALIAS ID: AMP-0-0770678-1, EG9736-000

Always EU RoHS/ELV Compliant

Seal Type Cavity Blanking Plug


Color Natural

RELATIONSHIP

Mating Products

Used to identify Mating Parts

See All Mating Products



PRODUCT - MATING PRODUCTS

Connectors - Automotive, Truck, Bus, & Off-Road Headers AMP I AMPSEAL

HEADER ASSY, 35 POS VERTICAL - 1-776230-1
TE INTERNAL NUMBER: 1-776230-1

✓ Active

Always EU RoHS/ELV Compliant

Pin Diameter 1.3 mm

Pitch 4 mm

Number of Circuits 35

Sealed Yes

Mounting Orientation Vertical/180°

