



SPEED (SECONDS)	MODEL NUMBER
15	15M5011E-6Y
30	30M5011E-6Y
60	60M5011E-6Y

SPECIFICATIONS								
WIRING	INPUT		OUTPUT			SHAFT ROTATION FOR VOLTAGE INCREASE	TERMINAL CONNECTIONS FOR INCREASING VOLTAGE AS VIEWED FROM TOP	
	VOLTS	HERTZ	VOLTS	MAX. AMPS	MAX. KVA		INPUT	OUTPUT
THREE PHASE WYE	240	60	0-280	100	48.5	CW	2-2-2	B-B-B
UNLESS OTHERWISE SPECIFIED, TOLERANCE IS ± DECIMALS .XX, HOLES .12, ANGLES DRAFT 1°, UNITS IN [mm]			TITLE: SPECIFICATION CONTROL DRAWING MOTORIZED VARIABLE TRANSFORMER 15, 30 & 60M5011E-6Y			STACO ENERGY PRODUCTS CO. DAYTON, OHIO U.S.A.		
MATERIAL: ALL DIMENSIONS APPLY AFTER PLATING			DRAWN BY TIM RAU	DATE 12/14/95	FIRST USED ON	DO NOT SCALE DWG.	CUSTOMER APPROVAL	DATE
The information and design disclosed herein was originated by and is the property of STACO ENERGY PRODUCTS CO., which reserves all patent, proprietary, design, manufacturing, reproduction, use and sale rights thereto, and to any article disclosed therein except to the extent rights are expressly granted to others. The foregoing does not apply to vendor proprietary parts.			CHECKER	DATE	WEIGHT APPROX.	CODE IDENT. NO. 83008	DWG. SIZE D	DWG. NO. 031-6961
			ENGINEER	DATE	SCALE .2=1	SHEET 1 OF 1		

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Staco:

M5011E-6Y