

EVALUATION KIT  
AVAILABLE

## Dual 1.5/3.0/6.0Gbps SAS/SATA Redriver

### General Description

The MAX4952B dual-channel redriver is designed to re-drive one full lane of SAS or SATA signals up to 6.0Gbps and operates from a single +3.3V supply. The MAX4952B is designed for commercial SAS or SAS/SATA applications, such as servers.

The MAX4952B features independent output boost and enhances signal integrity at the receiver by re-establishing full output levels. SAS/SATA out-of-band (OOB) signaling is supported using high-speed amplitude detection on the inputs and squelch on the corresponding outputs.

Inputs and outputs are all terminated in  $50\Omega$  internally and exhibit excellent return loss.

The MAX4952B is available in a small, 20-pin, 4.0mm x 4.0mm TQFN package with flow-through traces for ease of layout. This device is specified over the 0°C to +70°C operating temperature range.

### Applications

Servers

Data Storage

### Features

- ◆ Single +3.3V Supply Operation
- ◆ Low Power-Down Current (350 $\mu$ A typ) for Power-Sensitive Applications
- ◆ Supports SAS I/II/III  $\leq$  6.0Gbps
- ◆ Excellent Return Loss  
Exceeds SAS/SATA Return Loss Mask (Better Than 8dB Up to 3GHz)
- ◆ Supports SAS/SATA OOB-Level Signaling  
Very Fast Entry and Exit Time of 5ns (Max)  
Programmable SAS/SATA Threshold
- ◆ Independent Output-Boost Selection  
Two Levels: 0dB, 6dB
- ◆ On-Chip 50 $\Omega$  Input/Output Terminations
- ◆ In-Line Signal Traces for Flow-Through Layout
- ◆ Space-Saving, 4.0mm x 4.0mm TQFN Package
- ◆ ESD Protection on All Pins:  $\pm 5.5$ kV (Human Body Model)

### Ordering Information

PART	TEMP RANGE	PIN-PACKAGE
MAX4952BCTP+	0°C to +70°C	20 TQFN-EP*

+Denotes a lead(Pb)-free/RoHS-compliant package.

\*EP = Exposed Pad.

MAX4952B

# Dual 1.5/3.0/6.0Gbps SAS/SATA Redriver

## ABSOLUTE MAXIMUM RATINGS

(All voltages referenced to GND.)

V <sub>CC</sub> .....	-0.3V to +4.0V
All Other Pins (Note 1) .....	-0.3V to (V <sub>CC</sub> + 0.3V)
Short-Circuit Output Current DAP, DAM, HBM, HBP.....	90mA
Continuous Power Dissipation (T <sub>A</sub> = +70°C)	
20-Pin TQFN (derate 25.6mW/°C above +70°C).....	2051mW
Junction-to-Case Thermal Resistance (θ <sub>JC</sub> ) (Note 2)	
20-Pin TQFN.....	6°C/W

**Note 1:** All I/O pins are clamped by internal diodes.

**Note 2:** Package thermal resistances were obtained using the method described in JEDEC specification JESD51-7, using a four-layer board. For detailed information on package thermal considerations, refer to [www.maxim-ic.com/thermal-tutorial](http://www.maxim-ic.com/thermal-tutorial).

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

## ELECTRICAL CHARACTERISTICS

(V<sub>CC</sub> = +3.0V to +3.6V, C<sub>CL</sub> = 10nF coupling capacitor on each output, R<sub>L</sub> = 50Ω on each output, T<sub>A</sub> = 0°C to +70°C, unless otherwise noted. Typical values are at V<sub>CC</sub> = +3.3V and T<sub>A</sub> = +25°C.) (Note 3)

PARAMETER	SYMBOL	CONDITIONS		MIN	TYP	MAX	UNITS
<b>DC PERFORMANCE</b>							
Power-Supply Range	V <sub>CC</sub>			3.0	3.6		V
Power-Down Current	I <sub>PWRDN</sub>	EN = GND		0.35	2		mA
Supply Current	I <sub>CC</sub>	EN = V <sub>CC</sub>	BA = BB = V <sub>CC</sub>	100	130		mA
			BA = BB = GND	85	100		
Input Impedance, Differential	Z <sub>RX-DIFF-DC</sub>	DC		85	100	115	Ω
Output Impedance, Differential	Z <sub>TX-DIFF-DC</sub>	DC		85	100	115	Ω
<b>AC PERFORMANCE</b>							
Input Return Loss, Differential (Note 4)	RLRX-DIFF	0.1GHz < f ≤ 0.3GHz		-18			dB
		0.3GHz < f ≤ 0.6GHz		-14			
		0.6GHz < f ≤ 1.2GHz		-10			
		1.2GHz < f ≤ 2.4GHz		-8			
		2.4GHz < f ≤ 3.0GHz		-8			
		3.0GHz < f ≤ 6.0GHz		-1			
Input Return Loss, Common Mode (Note 4)	RLRX-CM	0.1GHz < f ≤ 0.3GHz		-6			dB
		0.3GHz < f ≤ 0.6GHz		-5			
		0.6GHz < f ≤ 1.2GHz		-5			
		1.2GHz < f ≤ 2.4GHz		-5			
		2.4GHz < f ≤ 3.0GHz		-5			
		3.0GHz < f ≤ 6.0GHz		-1			

# Dual 1.5/3.0/6.0Gbps SAS/SATA Redriver

MAX4952B

## ELECTRICAL CHARACTERISTICS (continued)

( $V_{CC} = +3.0V$  to  $+3.6V$ ,  $C_{CL} = 10nF$  coupling capacitor on each output,  $R_L = 50\Omega$  on each output,  $T_A = 0^\circ C$  to  $+70^\circ C$ , unless otherwise noted. Typical values are at  $V_{CC} = +3.3V$  and  $T_A = +25^\circ C$ .) (Note 3)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Output Return Loss, Differential (Note 4)	RLTX-DIFF	0.1GHz < $f \leq 0.3GHz$			-14	dB
		0.3GHz < $f \leq 0.6GHz$			-8	
		0.6GHz < $f \leq 1.2GHz$			-8	
		1.2GHz < $f \leq 2.4GHz$			-8	
		2.4GHz < $f \leq 3.0GHz$			-8	
		3.0GHz < $f \leq 6.0GHz$			-1	
Output Return Loss, Common Mode (Note 4)	RLTX-CM	0.1GHz < $f \leq 0.3GHz$			-8	dB
		0.3GHz < $f \leq 0.6GHz$			-5	
		0.6GHz < $f \leq 1.2GHz$			-5	
		1.2GHz < $f \leq 2.4GHz$			-5	
		2.4GHz < $f \leq 3.0GHz$			-5	
		3.0GHz < $f \leq 6.0GHz$			-1	
Differential Input Signal Range	VRX-DFF-PP	SATA 1.5Gbps, 3Gbps, 6Gbps, $M = GND$	225	1600		mVp-P
		SAS 1.5Gbps, 3Gbps, $M = V_{CC}$	275	1600		
		SAS 6.0Gbps, $M = V_{CC}$	300	1600		
OOB Squelch Threshold	VSQ-DIFF	SATA OOB, $M = GND$	50	150		mVp-P
		SAS OOB, $M = V_{CC}$	120	220		
Differential Output-Voltage Swing	VTX-DIFF-PP	$f = 750MHz, 1.5GHz$	BA = BB = GND	450	650	mVp-P
			BA = BB = V <sub>CC</sub>	900	1300	
Propagation Delay	TPD			300		ps
Output Rise/Fall Time	t <sub>TX-RISE-FALL</sub>	Figure 1 (Notes 4, 5)	40	40		ps
Deterministic Jitter	t <sub>TX-DJ-DD</sub>	Up to 6.0Gbps (Notes 4, 6)		15		psp-P
Random Jitter	t <sub>TX-RJ-DD</sub>	Up to 6.0Gbps (Notes 4, 6)		1.4		psRMS
OOB Output Startup/Shutdown Time	TOOB	(Note 7)	3	5		ns
Differential Offset Delta	$\Delta V_{OOB,DIFF}$	Difference between OOB and active-mode output offset	-80	+80		mV
Common-Mode Delta	$\Delta V_{OOB,CM}$	Difference between OOB and active-mode output $V_{CM}$	-50	+50		mV
<b>CONTROL LOGIC</b>						
Input Logic-Level Low	V <sub>IL</sub>				0.6	V
Input Logic-Level High	V <sub>IH</sub>			1.4		V
Input Logic Hysteresis	V <sub>HYST</sub>			100		mV
Input Pulldown Resistor	R <sub>DOWN</sub>			70		k $\Omega$
<b>ESD PROTECTION</b>						
All Pins		Human Body Model		$\pm 5.5$		kV

**Note 3:** This device is 100% production tested at  $T_A = +70^\circ C$ . Specifications for all temperature limits are guaranteed by design.

**Note 4:** Guaranteed by design.

**Note 5:** Rise and fall times are measured using 20% and 80% levels.










**Note 6:** DJ measured using K28.5 pattern; RJ measured using D10.2 pattern.

**Note 7:** Total time for OOB detection circuit to enable/squelch the output.

# Dual 1.5/3.0/6.0Gbps SAS/SATA Redriver

## Typical Operating Characteristics

(V<sub>CC</sub> = +3.3V, M = GND, T<sub>A</sub> = +25°C; all eye diagrams measured using K28.5 pattern, unless otherwise noted.)








# Dual 1.5/3.0/6.0Gbps SAS/SATA Redriver

## Typical Operating Characteristics (continued)


( $V_{CC} = +3.3V$ ,  $M = GND$ ,  $T_A = +25^\circ C$ ; all eye diagrams measured using K28.5 pattern, unless otherwise noted.)

MAX4952B



# Dual 1.5/3.0/6.0Gbps SAS/SATA Redriver

## Pin Configuration



## Pin Description

PIN	NAME	FUNCTION
1	HAP	Noninverting Input from Host Channel A. HAP must be capacitively coupled (see note).
2	HAM	Inverting Input from Host Channel A. HAM must be capacitively coupled (see note).
3, 13, 17, 18	GND	Ground
4	HBM	Inverting Output to Host Channel B. HBM must be capacitively coupled (see note).
5	HBP	Noninverting Output to Host Channel B. HBP must be capacitively coupled (see note).
6, 10, 16, 20	VCC	Power-Supply Input. Bypass VCC to GND with low-ESR 0.01µF and 4.7µF capacitors in parallel as close to the device as possible; recommended for each VCC pin.
7	EN	Enable Input. Drive EN low for low-power standby mode. Drive EN high for normal operation. EN is internally pulled down by a 70kΩ (typ) resistor.
8	BB	Channel B Boost-Enable Input. Drive BB high to enable channel B +6dB output boost. Drive BB low for standard SAS/SATA output level. BB is internally pulled down by a 70kΩ (typ) resistor.
9	BA	Channel A Boost-Enable Input. Drive BA high to enable channel A +6dB output boost. Drive BA low for standard SAS/SATA output level. BA is internally pulled down by a 70kΩ (typ) resistor.
11	DBP	Noninverting Input from Device Channel B. DBP must be capacitively coupled (see note).
12	DBM	Inverting Input from Device Channel B. DBM must be capacitively coupled (see note).
14	DAM	Inverting Output to Device Channel A. DAM must be capacitively coupled (see note).
15	DAP	Noninverting Output to Device Channel A. DAP must be capacitively coupled (see note).
19	M	OOB-Mode Logic Input. M is internally pulled down by a 70kΩ (typ) resistor. Drive M low or leave unconnected for SATA OOB threshold. Drive M high for SAS OOB threshold.
—	EP	Exposed Pad. Internally connected to GND. Connect to a large ground plane for proper thermal and electrical operation. Not intended as an electrical connection point.

**Note:** For proper operation, Maxim recommends the use of low-ESR, X7R, 10nF, 0402-sized capacitors for all redriver inputs and outputs.

## Dual 1.5/3.0/6.0Gbps SAS/SATA Redriver





Figure 1. Circuit for Measuring  $t_{R/F}$  for MAX4952B (refer to the SATA specifications for compliance measurement)

### Functional Diagram/Truth Table



EN	BA	BB	CHANNEL A OUTPUT LEVEL	CHANNEL B OUTPUT LEVEL
0	X	X	Power-Down	Power-Down
1	0	0	No Boost	No Boost
1	0	1	No Boost	Boost
1	1	0	Boost	No Boost
1	1	1	Boost	Boost

X = Don't care.

M	OOB THRESHOLD
0	SATA
1	SAS

## **Dual 1.5/3.0/6.0Gbps SAS/SATA Redriver**




Figure 2. Typical Application Circuit




Figure 3. MAX4952B Driving a SAS Cable

# Dual 1.5/3.0/6.0Gbps SAS/SATA Redriver

## Detailed Description

The MAX4952B dual-channel redriver is designed to redrive one full lane of SAS/SATA signals up to 6.0Gbps while operating from a single +3.3V supply.

The MAX4952B features independent output boost and enhances signal integrity at the receiver by re-establishing full output levels. SAS/SATA OOB signaling is supported using high-speed amplitude detection on the inputs and squelch on the corresponding outputs.

### Input/Output Terminations

Inputs and outputs are internally  $50\Omega$  terminated to VCC (see the *Functional Diagram/Truth Table*) and must be AC-coupled using low-ESR, X7R, 10nF capacitors to the SAS/SATA controller IC and SAS/SATA device for proper operation.

### Enable Input (EN)/Power-Down Mode

The MAX4952B features an active-high enable input, EN, which has an internal pulldown resistor of  $70\text{k}\Omega$  (typ). When EN is driven low or left unconnected, the MAX4952B enters power-down mode and squelches the output. Drive EN high for normal operation.

### SAS/SATA Mode Input (M)

The MAX4952B supports both SAS and SATA OOB levels. When in SAS mode, the OOB threshold is 120mVP-P (min), and when in SATA mode, the OOB threshold is 50mVP-P (min). Signals below the OOB threshold are squelched to prevent unwanted noise from being redriven at the output. Drive M low or leave unconnected to set SATA OOB levels. Drive M high to set SAS OOB levels. See the *Functional Diagram/Truth Table*. M has an internal pulldown resistor of  $70\text{k}\Omega$  (typ).

### Output Boost-Selection Inputs (BA, BB)

The MAX4952B has two digital control logic inputs, BA and BB. BA and BB have internal pulldown resistors of  $70\text{k}\Omega$  (typ). BA and BB control the boost level of their corresponding redrivers (see the *Functional Diagram/Truth Table*). Drive BA or BB low or leave unconnected for standard SAS/SATA output levels. Drive BA or BB high to boost the output.

## Applications Information

### Layout

Circuit board layout and design can significantly affect the performance of the MAX4952B. Use good, high-fre-

quency design techniques, including minimizing ground inductance and using controlled-impedance transmission lines on data signals. Place low-ESR 0.01 $\mu\text{F}$  and 4.7 $\mu\text{F}$  power-supply bypass capacitors in parallel as close to VCC as possible, or, as recommended, on each VCC pin. Always connect VCC to a power plane. The MAX4952B requires coupling capacitors for all redriver inputs and outputs. Maxim recommends high-quality, low-ESR, X7R, 10nF, 0402-sized capacitors.

### Exposed-Pad Package

The exposed-pad, 20-pin TQFN package incorporates features that provide a very low-thermal resistance path for heat removal from the IC. The exposed pad on the MAX4952B must be soldered to the circuit board ground plane for proper thermal and electrical performance. For more information on exposed-pad packages, refer to Application Note 862: *HFAN-08.1: Thermal Considerations of QFN and Other Exposed-Paddle Packages*.

### ESD Protection

As with all Maxim devices, ESD protection structures are incorporated on all pins to protect against electrostatic discharges encountered during handling and assembly. The MAX4952B is protected against ESD up to  $\pm 5.5\text{kV}$  (Human Body Model) without damage. The ESD structures withstand  $\pm 5.5\text{kV}$  in all states (normal operation and powered down). After an ESD event, the MAX4952B continues to function without latchup.

### Human Body Model

The MAX4952B is characterized for  $\pm 5.5\text{kV}$  ESD protection using the Human Body Model (MIL-STD-883, Method 3015). Figure 4 shows the Human Body Model and Figure 5 shows the current waveform it generates when discharged into low impedance. This model consists of a 100pF capacitor charged to the ESD voltage of interest that is then discharged into the device through a  $1.5\text{k}\Omega$  resistor.

### Power-Supply Sequencing

**Caution: Do not exceed the absolute maximum ratings because stresses beyond the listed ratings can cause permanent damage to the device.**

Proper power-supply sequencing is recommended for all devices. Always apply GND then VCC before applying signals, especially if the signal is not current limited.

**MAX4952B**

# Dual 1.5/3.0/6.0Gbps SAS/SATA Redriver




Figure 4. Human Body ESD Test Model




Figure 5. Human Body Current Waveform

## Chip Information

PROCESS: BiCMOS

## Package Information

For the latest package outline information and land patterns, go to [www.maxim-ic.com/packages](http://www.maxim-ic.com/packages). Note that a "+", "#", or "-" in the package code indicates RoHS status only. Package drawings may show a different suffix character, but the drawing pertains to the package regardless of RoHS status.

PACKAGE TYPE	PACKAGE CODE	DOCUMENT NO.
20 TQFN-EP	T2044+2	<a href="#">21-0139</a>

*Maxim cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim product. No circuit patent licenses are implied. Maxim reserves the right to change the circuitry and specifications without notice at any time.*

10 **Maxim Integrated Products, 120 San Gabriel Drive, Sunnyvale, CA 94086 408-737-7600**

© 2010 Maxim Integrated Products

Maxim is a registered trademark of Maxim Integrated Products, Inc.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Maxim Integrated:](#)

[MAX4952BCTP+](#) [MAX4952BCTP+T](#)