



---

The following document contains information on Cypress products. Although the document is marked with the name "Spansion", the company that originally developed the specification, Cypress will continue to offer these products to new and existing customers.

#### **Continuity of Specifications**

There is no change to this document as a result of offering the device as a Cypress product. Any changes that have been made are the result of normal document improvements and are noted in the document history page, where supported. Future revisions will occur when appropriate, and changes will be noted in a document history page.

#### **Continuity of Ordering Part Numbers**

Cypress continues to support existing part numbers. To order these products, please use only the Ordering Part Numbers listed in this document.

#### **For More Information**

Please contact your local sales office for additional information about Cypress products and solutions.

#### **About Cypress**

Cypress (NASDAQ: CY) delivers high-performance, high-quality solutions at the heart of today's most advanced embedded systems, from automotive, industrial and networking platforms to highly interactive consumer and mobile devices. With a broad, differentiated product portfolio that includes NOR flash memories, F-RAM™ and SRAM, Traveo™ microcontrollers, the industry's only PSoC® programmable system-on-chip solutions, analog and PMIC Power Management ICs, CapSense® capacitive touch-sensing controllers, and Wireless BLE Bluetooth® Low-Energy and USB connectivity solutions, Cypress is committed to providing its customers worldwide with consistent innovation, best-in-class support and exceptional system value.

# MB3793-42

**POWER-VOLTAGE MONITORING IC WITH WATCHDOG**

**TIMER**

**BIPOLAR**

**ASSP**

***Data Sheet (Full Production)***

---



**Notice to Readers:** This document states the current technical specifications regarding the Spansion product(s) described herein. Spansion Inc. deems the products to have been in sufficient production volume such that subsequent versions of this document are not expected to change. However, typographical or specification corrections, or modifications to the valid combinations offered may occur.

## Notice On Data Sheet Designations

Spansion Inc. issues data sheets with Advance Information or Preliminary designations to advise readers of product information or intended specifications throughout the product life cycle, including development, qualification, initial production, and full production. In all cases, however, readers are encouraged to verify that they have the latest information before finalizing their design. The following descriptions of Spansion data sheet designations are presented here to highlight their presence and definitions.

### Advance Information

The Advance Information designation indicates that Spansion Inc. is developing one or more specific products, but has not committed any design to production. Information presented in a document with this designation is likely to change, and in some cases, development on the product may discontinue. Spansion Inc. therefore places the following conditions upon Advance Information content:

"This document contains information on one or more products under development at Spansion Inc. The information is intended to help you evaluate this product. Do not design in this product without contacting the factory. Spansion Inc. reserves the right to change or discontinue work on this proposed product without notice."

### Preliminary

The Preliminary designation indicates that the product development has progressed such that a commitment to production has taken place. This designation covers several aspects of the product life cycle, including product qualification, initial production, and the subsequent phases in the manufacturing process that occur before full production is achieved. Changes to the technical specifications presented in a Preliminary document should be expected while keeping these aspects of production under consideration. Spansion places the following conditions upon Preliminary content:

"This document states the current technical specifications regarding the Spansion product(s) described herein. The Preliminary status of this document indicates that product qualification has been completed, and that initial production has begun. Due to the phases of the manufacturing process that require maintaining efficiency and quality, this document may be revised by subsequent versions or modifications due to changes in technical specifications."

### Combination

Some data sheets contain a combination of products with different designations (Advance Information, Preliminary, or Full Production). This type of document distinguishes these products and their designations wherever necessary, typically on the first page, the ordering information page, and pages with the DC Characteristics table and the AC Erase and Program table (in the table notes). The disclaimer on the first page refers the reader to the notice on this page.

### Full Production (No Designation on Document)

When a product has been in production for a period of time such that no changes or only nominal changes are expected, the Preliminary designation is removed from the data sheet. Nominal changes may include those affecting the number of ordering part numbers available, such as the addition or deletion of a speed option, temperature range, package type, or VIO range. Changes may also include those needed to clarify a description or to correct a typographical error or incorrect specification. Spansion Inc. applies the following conditions to documents in this category:

"This document states the current technical specifications regarding the Spansion product(s) described herein. Spansion Inc. deems the products to have been in sufficient production volume such that subsequent versions of this document are not expected to change. However, typographical or specification corrections, or modifications to the valid combinations offered may occur."

Questions regarding these document designations may be directed to your local sales office.

**MB3793-42**

# POWER-VOLTAGE MONITORING IC WITH WATCHDOG TIMER BIPOLAR ASSP

### ***Data Sheet (Full Production)***

## ■ DESCRIPTION

The MB3793 is an integrated circuit to monitor power voltage; it incorporates a watchdog timer.

A reset signal is output when the power is cut or falls abruptly. When the power recovers normally after resetting, a power-on reset signal is output to microprocessor units (MPUs). An internal watchdog timer with two inputs for system operation diagnosis can provide a fail-safe function for various application systems.

The model number and package code are as shown below.


Model No.	Marking Code	Detection voltage
MB3793-42	3793-A	4.2 V

## ■ FEATURES

- Precise detection of power voltage fall:  $\pm 2.5\%$
- Detection voltage with hysteresis
- Low power dispersion:  $I_{CC} = 27 \mu A$  (reference)
- Internal dual-input watchdog timer
- Watchdog timer halt function (by inhibition terminal)
- Independently-set watchdog and reset times
- Mask option for detection voltage (4.9 to 2.4 V, 0.1-V steps)
- Two types of packages (SOP-8pin : 2 types)


## ■ APPLICATION

- Arcade Amusement etc.

**■ PIN ASSIGNMENT****■ PIN DESCRIPTION**

Pin No.	Symbol	Description	Pin No.	Symbol	Description
1	$\overline{\text{RESET}}$	Outputs reset	5	Vcc	Power supply
2	CTW	Sets monitoring time	6	INH	Inhibits watchdog timer function
3	CTP	Sets power-on reset hold time	7	CK2	Inputs clock 2
4	GND	Ground	8	CK1	Inputs clock 1

## ■ BLOCK DIAGRAM



## ■ BLOCK FUNCTIONS

### 1. Comp. S

Comp. S is a comparator with hysteresis to compare the reference voltage with a voltage ( $V_S$ ) that is the result of dividing the power voltage ( $V_{CC}$ ) by resistors  $R_1$  and  $R_2$ . When  $V_S$  falls below 1.24 V, a reset signal is output. This function enables the MB3793 to detect an abnormality within 1  $\mu$ s when the power is cut or falls abruptly.

### 2. Comp. O

Comp. O is a comparator to control the reset signal ( $\overline{RESET}$ ) output and compares the threshold voltage with the voltage at the CTP terminal for setting the power-on reset hold time. When the voltage at the CTP terminal exceeds the threshold voltage, resetting is canceled.

### 3. Reset output buffer

Since the reset ( $\overline{RESET}$ ) output buffer has CMOS organization, no pull-up resistor is needed.

### 4. Pulse generator

The pulse generator generates pulses when the voltage at the CK1 and CK2 input clock terminals changes to High from Low level (positive-edge trigger) and exceeds the threshold voltage; it sends the clock signal to the watchdog timer.

### 5. Watchdog timer

The watchdog timer can monitor two clock pulses. Short-circuit the CK1 and CK2 clock terminals to monitor a single clock pulse.

### 6. Inhibition terminal

The inhibition (INH) terminal forces the watchdog timer on/off. When this terminal is High level, the watchdog timer is stopped.

### 7. Flip-flop circuit

The flip-flop circuit RSFF1 controls charging and discharging of the power-on reset hold time setting capacity ( $C_{TP}$ ). The flip-flop circuit RSFF2 switches the charging accelerator for charging  $C_{TP}$  during resetting on/off. This circuit only functions during resetting and does not function at power-on reset.

## ■ ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Rating		Unit
		Min	Max	
Power voltage*	V <sub>CC</sub>	-0.3	+7	V
Input voltage*	CK1	-0.3	+7	V
	CK2			
	INH			
Reset output voltage (direct current)	RESET	I <sub>OL</sub> I <sub>OH</sub>	-10 +10	mA
Power dissipation (Ta ≤ +85°C)	P <sub>D</sub>	—	200	mW
Storage temperature	T <sub>STG</sub>	-55	+125	°C

\*: The power voltage is based on the ground voltage (0 V).

### WARNING:

1. Semiconductor devices may be permanently damaged by application of stress (including, without limitation, voltage, current or temperature) in excess of absolute maximum ratings. Do not exceed any of these ratings.

## ■ RECOMMENDED OPERATING CONDITIONS

Parameter	Symbol	Value			Unit
		Min	Typ	Max	
Power supply voltage	V <sub>CC</sub>	1.2	5.0	6.0	V
Reset (RESET) output current	I <sub>OL</sub> I <sub>OH</sub>	-5	—	+5	mA
Power-on reset hold time setting capacity	C <sub>TP</sub>	0.001	0.1	10	μF
Watchdog timer monitoring time setting capacity	C <sub>TW</sub>	0.001	0.1	1	μF
Watchdog timer monitoring time	t <sub>WD</sub>	0.1	—	1500	ms
Operating ambient temperature	T <sub>A</sub>	-40	+25	+85	°C

### WARNING:

1. The recommended operating conditions are required in order to ensure the normal operation of the semiconductor device. All of the device's electrical characteristics are warranted when the device is operated under these conditions.
2. Any use of semiconductor devices will be under their recommended operating condition.
3. Operation under any conditions other than these conditions may adversely affect reliability of device and could result in device failure.
4. No warranty is made with respect to any use, operating conditions or combinations not represented on this data sheet. If you are considering application under any conditions other than listed herein, please contact sales representatives beforehand.

## ■ ELECTRICAL CHARACTERISTICS

## 1. DC Characteristics

(V<sub>CC</sub> = +5 V, Ta = +25°C)

Parameter	Symbol	Conditions	Value			Unit	
			Min	Typ	Max		
Power current	I <sub>CC1</sub>	Watchdog timer operation* <sup>1</sup>	—	27	50	µA	
	I <sub>CC2</sub>	Watchdog timer halt* <sup>2</sup>	—	25	45		
Detection voltage	V <sub>SL</sub>	V <sub>CC</sub> falling	Ta = +25°C	4.10	4.20	4.30	V
			Ta = -40 to +85°C	4.05	4.20	4.35	
	V <sub>SH</sub>	V <sub>CC</sub> rising	Ta = +25°C	4.20	4.30	4.40	V
			Ta = -40 to +85°C	4.15	4.30	4.45	
Detection voltage hysteresis difference	V <sub>SHYS</sub>	V <sub>SH</sub> - V <sub>SL</sub>	50	100	150	mV	
CK input threshold voltage	V <sub>CIH</sub>	—	(1.4)	1.9	(2.5)	V	
	V <sub>CIL</sub>	—	(0.8)	1.3	(1.8)	V	
CK input hysteresis	V <sub>CHYS</sub>	—	(0.4)	0.6	(0.8)	V	
INH input voltage	V <sub>IIL</sub>	—	3.5	—	V <sub>CC</sub>	V	
	V <sub>IIL</sub>	—	0	0	0.8	V	
Input current (CK1,CK2,INH)	I <sub>IIH</sub>	V <sub>CK</sub> = V <sub>CC</sub>	—	0	1.0	µA	
	I <sub>IIL</sub>	V <sub>CK</sub> = 0 V	-1.0	0	—	µA	
Reset output voltage	V <sub>OH</sub>	I <sub>RESET</sub> = -5 mA	4.5	4.75	—	V	
	V <sub>OL</sub>	I <sub>RESET</sub> = +5 mA	—	0.12	0.4	V	
Reset-output minimum power voltage	V <sub>CCL</sub>	I <sub>RESET</sub> = +50 µA	—	0.8	1.2	V	

\*1: At clock input terminals CK1 and CK2, the pulse input frequency is 1 kHz and the pulse amplitude is 0 V to V<sub>CC</sub>.

\*2: Inhibition input is at High level.

## 2. AC Characteristics


( $V_{CC} = +5$  V,  $T_a = +25^\circ\text{C}$ )

Parameter	Symbol	Conditions	Value			Unit
			Min	Typ	Max	
Power-on reset hold time	$t_{PR}$	$C_{TP} = 0.1 \mu\text{F}$	80	130	180	ms
Watchdog timer monitoring time	$t_{WD}$	$C_{TW} = 0.01 \mu\text{F}$ $C_{TP} = 0.1 \mu\text{F}$	7.5	15	22.5	ms
Watchdog timer reset time	$t_{WR}$	$C_{TP} = 0.1 \mu\text{F}$	5	10	15	ms
CK input pulse duration	$t_{CKW}$	—	500	—	—	ns
CK input pulse cycle	$t_{CKT}$	—	20	—	—	$\mu\text{s}$
Reset ( $\overline{\text{RESET}}$ ) output transition time	Rising	$t_{r^*}$	$C_L = 50 \text{ pF}$	—	—	500 ns
	Falling	$t_{f^*}$	$C_L = 50 \text{ pF}$	—	—	500 ns


\*: The voltage range is 10% to 90% at testing the reset output transition time.

## ■ TIMING DIAGRAM


## 1. Basic operation (Positive clock pulse)



## 2. Basic operation (Negative clock pulse)




### 3. Single-clock input monitoring (Positive clock pulse)




Note: The MB3793 can monitor only one clock.

The MB3793 checks the clock signal at every other input pulse. Therefore, set watchdog timer monitor time  $t_{WD}$  to the time that allows the MB3793 to monitor the period twice as long as the input clock pulse.

#### 4. Inhibition operation (Positive clock pulse)



**5. Clock pulse input (Positive clock pulse)**

Note: The MB3793 watchdog timer monitors Clock 1 (CK1) and Clock 2 (CK2) pulses alternately. When a CK2 pulse is detected after detecting a CK1 pulse, the monitoring time setting capacity ( $C_{TW}$ ) switches to charging from discharging. When two consecutive pulses occur on one side of this alternation before switching, the second pulse is ignored. In the above figure, pulses \*1 and \*2 are ignored.

**6. Inhibition input rising and falling time**

## ■ OPERATION SEQUENCE

The operation sequence is explained by using “■ TIMING DIAGRAM 1. Basic operation (Positive clock pulse)”. The following item numbers correspond to the numbers in “■ TIMING DIAGRAM 1. Basic operation (Positive clock pulse)”.

- (1) When the power voltage ( $V_{CC}$ ) reaches about 0.8 V ( $V_{CCL}$ ), a reset signal is output.
- (2) When  $V_{CC}$  exceeds the rising-edge detection voltage ( $V_{SH}$ ), charging of power-on reset hold time setting capacitance ( $C_{TP}$ ) is started.  $V_{SH}$  is about 4.3 V.
- (3) When the voltage at the CTP terminal setting the power-on reset hold time exceeds the threshold voltage ( $V_{th}$ ), resetting is canceled and the voltage at the RESET terminal changes to High level to start charging of the watchdog timer monitoring time setting capacitance ( $C_{TW}$ ).  $V_{th}$  is about 3.6 V.

The power-on reset hold time ( $t_{PR}$ ) can be calculated by the following equation.

$$t_{PR} (\text{ms}) \approx A \times C_{TP} (\mu\text{F})$$

Where, A is about 1300.

- (4) When the voltage at the CTW terminal setting the monitoring time reaches High level ( $V_H$ ),  $C_{TW}$  switches to discharging from charging.  $V_H$  is about 1.24 V (reference value).
- (5) When clock pulses are input to the CK2 terminal during  $C_{TW}$  discharging after clock pulses are input to the CK1 terminal—positive-edge trigger,  $C_{TW}$  switches to charging.
- (6) If clock pulse input does not occur at either the CK1 or CK2 clock terminals during the watchdog timer monitoring time ( $t_{WD}$ ), the CTW voltage falls below Low level ( $V_L$ ), a reset signal is output, and the voltage at the RESET terminal changes to Low level.  $V_L$  is about 0.24 V.

$t_{WD}$  can be calculated from the following equation.

$$t_{WD} (\text{ms}) \approx B \times C_{TW} (\mu\text{F}) + C \times C_{TP} (\mu\text{F})$$

Where, B is about 1500. C is about 3; it is much smaller than B.

Hence, when  $C_{TP} / C_{TW} \leq 10$ , the calculation can be simplified as follows:

$$t_{WD} (\text{ms}) \approx B \times C_{TW} (\mu\text{F})$$

- (7) When the voltage of the CTP terminal exceeds  $V_{th}$  again as a result of recharging  $C_{TP}$ , resetting is canceled and the watchdog timer restarts monitoring.

The watchdog timer reset time ( $t_{WR}$ ) can be calculated by the following equation.

$$t_{WR} (\text{ms}) \approx D \times C_{TP} (\mu\text{F})$$

Where, D is about 100.

- (8) When  $V_{CC}$  falls below the rising-edge detection voltage ( $V_{SL}$ ), the voltage of the CTP terminal falls and a reset signal is output, and the voltage at the RESET terminal changes to Low level.  $V_{SL}$  is about 4.2 V.

- (9) When  $V_{CC}$  exceeds  $V_{SH}$ ,  $C_{TP}$  begins charging.

- (10) When the voltage of the CTP terminal exceeds  $V_{th}$ , resetting is canceled and the watchdog timer restarts.

- (11) When an inhibition signal is input (INH terminal is High level), the watchdog timer is halted forcibly. In this case,  $V_{CC}$  monitoring is continued without the watchdog timer.

The watchdog timer does not function unless this inhibition input is canceled.

- (12) When the inhibition input is canceled (INH terminal is Low level), the watchdog timer restarts.

- (13) When the  $V_{CC}$  voltage falls below  $V_{SL}$  after power-off, a reset signal is output.


- (14) When the power voltage ( $V_{CC}$ ) falls below about 0.8 V ( $V_{CCL}$ ), a reset signal is released.

Similar operation is also performed for negative clock-pulse input (“■ TIMING DIAGRAM 2. Basic operation (Negative clock pulse)”).


Short-circuit the clock terminals CK1 and CK2 to monitor a single clock. The basic operation is the same but the clock pulses are monitored at every other pulse (■ TIMING Diagram 3. Single-clock input monitoring).

## ■ TYPICAL CHARACTERISTICS


## Power Current - Power Voltage




## Detection Voltage - Operating ambient Temperature











## Reset Output Voltage - Reset Output Current (P-MOS side)




## Reset Output Voltage - Reset Output Current (N-MOS side)



**Reset Output Voltage - Power Voltage**

**Reset-on Reset Time - Operating ambient temperature (when  $V_{CC}$  rising)**

**Watchdog Timer Monitoring Reset Time - Operating ambient temperature (when monitoring)**

**Watchdog Timer Monitoring Time - Operating ambient temperature**


**Power-on Reset Hold Time -  $C_{TP}$  Capacitance**

**Reset Time -  $C_{TP}$  Capacitance**

**Watchdog Timer Monitoring Time -  $C_{TW}$  Capacitance  
(under  $T_a$  condition)**

**Watchdog Timer Monitoring Time -  $C_{TW}$  Capacitance**


## ■ STANDARD CONNECTION



Equation of time-setting capacitances ( $C_{TP}$  and  $C_{TW}$ ) and set time

$$t_{PR} (\text{ms}) \approx A \times C_{TP} (\mu\text{F})$$

$$t_{WD} (\text{ms}) \approx B \times C_{TW} (\mu\text{F}) + C \times C_{TP} (\mu\text{F})$$

However, when  $C_{TP}/C_{TW} \leq 10$ ,

$$t_{WD} (\text{ms}) \approx B \times C_{TW} (\mu\text{F})$$

$$t_{WR} (\text{ms}) \approx D \times C_{TP} (\mu\text{F})$$

Value of A, B, C and D



A	B	C	D	Remark
1300	1500	3	100	

(Example) When  $C_{TP} = 0.1 \mu\text{F}$  and  $C_{TW} = 0.01 \mu\text{F}$ ,

$$t_{PR} \approx 130 \text{ [ms]}$$

$$t_{WD} \approx 15 \text{ [ms]}$$

$$t_{WR} \approx 10 \text{ [ms]}$$

**■ APPLICATION EXAMPLE****1. Monitoring Single Clock****2. Watchdog Timer Stopping**

## ■ NOTES ON USE

- Take account of common impedance when designing the earth line on a printed wiring board.
- Take measures against static electricity.
  - For semiconductors, use antistatic or conductive containers.
  - When storing or carrying a printed circuit board after chip mounting, put it in a conductive bag or container.
  - The work table, tools and measuring instruments must be grounded.
  - The worker must put on a grounding device containing 250 kΩ to 1 MΩ resistors in series.
- Do not apply a negative voltage
  - Applying a negative voltage of -0.3 V or less to an LSI may generate a parasitic transistor, resulting in malfunction.

## ■ ORDERING INFORMATION

Part number	Package	Remarks
MB3793-42PF-□□□	8-pin plastic SOP (FPT-8P-M01)	Conventional version
MB3793-42PNF-□□□	8-pin plastic SOP (FPT-8P-M02)	Conventional version
MB3793-42PF-□□□E1	8-pin plastic SOP (FPT-8P-M01)	Lead Free version
MB3793-42PNF-□□□E1	8-pin plastic SOP (FPT-8P-M02)	Lead Free version


## ■ RoHS Compliance Information of Lead (Pb) Free version

The LSI products of Spansion with "E1" are compliant with RoHS Directive , and has observed the standard of lead, cadmium, mercury, Hexavalent chromium, polybrominated biphenyls (PBB) , and polybrominated diphenyl ethers (PBDE) .


The product that conforms to this standard is added "E1" at the end of the part number.


**■ MARKING FORMAT (Lead Free version)**

Lead Free version

SOP-8  
(FPT-8P-M01)

Lead Free version

SOP-8  
(FPT-8P-M02)


**■ LABELING SAMPLE (Lead free version)**

■ MB3793-42PF-□□□E1, MB3793-42PNF-□□□E1  
**RECOMMENDED CONDITIONS OF MOISTURE SENSITIVITY LEVEL**

Item	Condition	
Mounting Method	IR (infrared reflow) , Manual soldering (partial heating method)	
Mounting times	2 times	
Storage period	Before opening	Please use it within two years after Manufacture.
	From opening to the 2nd reflow	Less than 8 days
	When the storage period after opening was exceeded	Please processes within 8 days after baking (125 °C, 24H)
Storage conditions	5 °C to 30 °C, 70%RH or less (the lowest possible humidity)	

[Temperature Profile for Spansion Standard IR Reflow]

(1) IR (infrared reflow)



(a) Temperature Increase gradient : Average 1 °C/s to 4 °C/s  
(b) Preliminary heating : Temperature 170 °C to 190 °C, 60s to 180s  
(c) Temperature Increase gradient : Average 1 °C/s to 4 °C/s  
(d) Actual heating : Temperature 260 °C Max; 255 °C or more, 10s or less  
(d') : Temperature 230 °C or more, 40s or less  
or  
Temperature 225 °C or more, 60s or less  
or  
Temperature 220 °C or more, 80s or less  
(e) Cooling : Natural cooling or forced cooling


Note : Temperature : the top of the package body



(2) Manual soldering (partial heating method)

Conditions : Temperature 400 °C Max



Times : 5 s max/pin

## ■ PACKAGE DIMENSIONS

 <b>8-pin plastic SOP</b> <b>(FPT-8P-M01)</b>	<table border="1"> <tr> <td>Lead pitch</td><td>1.27 mm</td></tr> <tr> <td>Package width × package length</td><td>5.3 × 6.35 mm</td></tr> <tr> <td>Lead shape</td><td>Gullwing</td></tr> <tr> <td>Sealing method</td><td>Plastic mold</td></tr> <tr> <td>Mounting height</td><td>2.25 mm MAX</td></tr> <tr> <td>Weight</td><td>0.10 g</td></tr> <tr> <td>Code (Reference)</td><td>P-SOP8-5.3×6.35-1.27</td></tr> </table>	Lead pitch	1.27 mm	Package width × package length	5.3 × 6.35 mm	Lead shape	Gullwing	Sealing method	Plastic mold	Mounting height	2.25 mm MAX	Weight	0.10 g	Code (Reference)	P-SOP8-5.3×6.35-1.27
Lead pitch	1.27 mm														
Package width × package length	5.3 × 6.35 mm														
Lead shape	Gullwing														
Sealing method	Plastic mold														
Mounting height	2.25 mm MAX														
Weight	0.10 g														
Code (Reference)	P-SOP8-5.3×6.35-1.27														

<b>8-pin plastic SOP</b> <b>(FPT-8P-M01)</b> 	<p>Note 1) *1 : These dimensions include resin protrusion.      Note 2) *2 : These dimensions do not include resin protrusion.      Note 3) Pins width and pins thickness include plating thickness.      Note 4) Pins width do not include tie bar cutting remainder.</p> 
--	--

Dimensions in mm (inches).  
 Note: The values in parentheses are reference values.



**■ MAJOR CHANGES**

Page	Section	Change Results
Revision 6.0		
-	-	Company name and layout design change
1	DESCRIPTION	Deleted "There is also a mask option that can detect voltages of 4.9 V to 2.4 V in 0.1-V steps."
Revision 6.1		
22	■ MB3793-42PF-□□□E1, MB3793-42PNF-□□□E1 RECOMMENDED CONDITIONS OF MOISTURE SENSITIVITY LEVEL	Changed the subtitle text of Figure

### ***Colophon***

The products described in this document are designed, developed and manufactured as contemplated for general use, including without limitation, ordinary industrial use, general office use, personal use, and household use, but are not designed, developed and manufactured as contemplated (1) for any use that includes fatal risks or dangers that, unless extremely high safety is secured, could have a serious effect to the public, and could lead directly to death, personal injury, severe physical damage or other loss (i.e., nuclear reaction control in nuclear facility, aircraft flight control, air traffic control, mass transport control, medical life support system, missile launch control in weapon system), or (2) for any use where chance of failure is intolerable (i.e., submersible repeater and artificial satellite). Please note that Spansion will not be liable to you and/or any third party for any claims or damages arising in connection with above-mentioned uses of the products. Any semiconductor devices have an inherent chance of failure. You must protect against injury, damage or loss from such failures by incorporating safety design measures into your facility and equipment such as redundancy, fire protection, and prevention of over-current levels and other abnormal operating conditions. If any products described in this document represent goods or technologies subject to certain restrictions on export under the Foreign Exchange and Foreign Trade Law of Japan, the US Export Administration Regulations or the applicable laws of any other country, the prior authorization by the respective government entity will be required for export of those products.

### ***Trademarks and Notice***

The contents of this document are subject to change without notice. This document may contain information on a Spansion product under development by Spansion. Spansion reserves the right to change or discontinue work on any product without notice. The information in this document is provided as is without warranty or guarantee of any kind as to its accuracy, completeness, operability, fitness for particular purpose, merchantability, non-infringement of third-party rights, or any other warranty, express, implied, or statutory. Spansion assumes no liability for any damages of any kind arising out of the use of the information in this document.

Copyright © 1996-2015 Spansion All rights reserved. Spansion®, the Spansion logo, MirrorBit®, MirrorBit® Eclipse™, ORNAND™ and combinations thereof, are trademarks and registered trademarks of Spansion LLC in the United States and other countries. Other names used are for informational purposes only and may be trademarks of their respective owners.