





(2,54 mm) .100"

MTLW-130-05-G-S-110 TLW-118-06-T-D **TLW, MTLW SERIES**

PROFILE .025" SQ POST HEADERS

Mates with:

BSW, CES, SLW, HLE, SMSD, SMSS

FEATURES

TLW

These headers provide the ultimate low profile (0,64 mm) .025" square post board stacking

system. The high quality Phosphor Bronze terminals

are available with a standard short post height

(TLW Series) for mating with low profile sockets, or the post height can be Modified (MTLW Series) to accommodate IDC assemblies and other applications.

CES =

TLW

NO. PINS **PER ROW**

LEAD STYLE

Specify LEAD STYLE

from chart

PLATING OPTION

Gold flash

on post,

Matte Tin

on tail

-G

= 10µ"

(0,25 µm)

Gold on post

Gold flash

on tail

= Matte Tin

PLATING

OPTION

ROW **OPTION**

OPTION

OTHER

-S = Single Row

– D = Double Row

–RA = Right Angle

> (-01 Lead Style only)


-"XX" = Polarized Position

Specify position for omitted pin.

POST


HEIGHT

01 thru 40 = Single Row



01 thru 36 = Double Row





.098

NO. PINS

PER ROW

(1,52) .060

-05 & -06

LEAD STYLE	Α	С
-01	N/A	(5,84) .230
-05	(4,32) .170	(2,67) .105
-06	(3,43) .135	(2,67) .105

-01

ALSO AVAILABLE (MOQ Required)

 Other platings Contact Samtec.

SPECIFICATIONS

For complete specifications see www.samtec.com?TLW or www.samtec.com?MTLW

Insulator Material: Black Liquid Crystal Polymer Terminal Material: Phosphor Bronze

Plating:
Au or Sn over
50µ" (1,27 µm) Ni
Current Rating (TLW/SLW): 5.2 A per per pin (1 pin powered per row) Operating Temp Range: -55°C to +105°C with Tin -55°C to +125°C with Gold RoHS Compliant:

Yes Lead-Free Solderable: Yes

For complete scope of


www.samtec.com/quality

recognitions see


RECOGNITIONS

01 thru 40 = Single Row

MTLW




01 thru 36 = Double Row



Specify LEAD STYLE from chart

LEAD

STYLE



.530 (18,54) .730 -09 (21,08) .830 -10(16,00)-22 .630 (11,30) .445 (12,19) -23 -24 .480

ROW OPTION



– D = Double Row

"XXX" = Post Height Dimension (In inches)



.F

= Gold flash

on post,

Matte Tin on tail

–G = 10µ" (0,25 µm) Gold on post, Gold flash on tail

= Matte Tin



Some lengths, styles and options are non-standard, non-returnable. MTLW Series is non-standard, non-returnable.