



(2,00 mm) .0787"

MTMM-114-05-F-Q-235

MTMM-108-07-F-D-350

MTMM-124-15-T-S-650

MTMM SERIES

MODIFIED THROUGH-HOLE HEADER

SPECIFICATIONS

For complete specifications see www.samtec.com?MTMM

Insulator Material:

Black Liquid Crystal Polymer

Terminal Material:

Phosphor Bronze

Plating:

Sn or Au over
50µ" (1,27 µm) Ni

Operating Temp Range:

-55°C to +105°C with Tin;
-55°C to +125°C with Gold

RoHS Compliant:

Yes

Lead-Free Solderable:

Yes


RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality



Mates with:
CLT, SQT, SQW, ESQT,
TLE, SMM, MMS, TCSD

Board Stacking



Choice of
single, double or
quad row

Specify
post height in
(0,13 mm) .005"
increments



(2,00 mm)
.0787" pitch

MTMM	1	NO. PINS PER ROW	LEAD STYLE	PLATING OPTION	ROW OPTION	POST HEIGHT	OPTION
		01 thru 50	Specify LEAD STYLE from chart.	-F = Gold flash on post, Matte Tin on tail -L = 10µ" (0,25 µm) Gold post, Matte Tin on tail -T = Matte Tin	-S = Single Row -D = Double Row -Q = Quad Row	-"XXX" = Post Height in inches (0,13 mm) .005" increments Example: -070 = (1,78 mm) .070"	-"XXX" = Polarized Position Specify position of omitted pin

No. of positions x (2,00) .0787

LEAD STYLE	OAL
-02	(6,48) .255
-03	(7,67) .302
-04	(8,20) .323
-05	(9,58) .377
-06	(10,08) .397
-07	(11,58) .456
-08	(12,09) .476
-09	(13,59) .535
-10	(14,10) .555
-11	(15,09) .594
-12	(15,60) .614
-13	(17,09) .673
-14	(19,08) .751
-15	(21,08) .830

Note: This Series is non-standard, non-returnable.