

## 40Gb Pass-Through Cassette - (x12) 12-Fiber MTP/MPO

MODEL NUMBER: **N484-12M12**



### Highlights

- High Density Fiber Cassette for use with Tripp Lite's [N484-00U](#) and [N484-01U](#) chassis'
- 40Gb Pass-through Cassette, with(x12) 12-Fiber MTP/MPO connections
- Factory terminated connectors reduce the time and labor required of field connector terminations
- Type B Adapters( Key up to Key up)

### Package Includes

- N484-12M12 40GbE Pass-Through Cassette - (x12) 12-Fiber MTP/MPO
- Quick Start Guide

### Description

Tripp Lite's N484-12M12 is a High Density 40Gb Pass-through Cassette, with(x12) 12-Fiber MTP/MPO connections. Designed specifically for use with Tripp Lite's [N484-00U](#) and [N484-01U](#) chassis'; up to 4 cassettes per [N484-01U](#), or 1 per [N484-00U](#). Each MTP/MPO connector is rated for up to 40GbE, with an extremely low insertion loss of 0.35db, well under the IEEE-802.3ae maximum channel loss spec of <25db. Installation is simple, with the cassette being easily installed or removed using screw tabs to lock or unlock it from the panel; no tools required. Furthermore, each cassette features factory terminated connectors that reduce the time and labor required of field connector terminations. Cassette housing made with heavy duty, 1.0mm Cold Rolled Steel.

### Features

- High Density Fiber Cassette for use with Tripp Lite's [N484-00U](#) and [N484-01U](#) chassis'
- 40Gb Pass-through Cassette, with(x12) 12-Fiber MTP/MPO connections
- Max insertion loss of 0.35dB falls well under the IEEE 802.3ae maximum channel loss spec of <25dB
- Type B adapters( Key up to Key up)
- Installation is simple, with the cassette being easily installed or removed using screw tabs to lock or unlock it from the panel; no tools required
- Factory terminated connectors reduce the time and labor required of field connector terminations
- Housing made of heavy duty, 1.0mm Cold Rolled Steel
- Includes dust caps for unused ports

## Specifications

PHYSICAL	
Unit Dimensions (hwd / in.)	1.4 x 4.4 x 0.8
Unit Weight (lbs.)	0.3
Color	Black



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

ENVIRONMENTAL	
Operating Temperature Range	-4 to 122 F (-20 to 50 C)
CONNECTIONS	
Connector A	(12) MTP PASS THROUGH
Connector B	(12) MTP PASS THROUGH
Ports	0
CERTIFICATIONS	
Approvals	RoHS, REACH
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2016 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:  
<http://www.tripplite.com/products/product-certification-agencies>