



[All Series](#) > [Series 45](#) > Part No. 45-1231.31N6.000.101

Part No. 45-1231.31N6.000.101, Illuminated pushbutton

[Request Information](#)

[Printable Page](#)

[Download PDF](#)

[Email This Page](#)



**3D CAD
DRAWING**




3D



Front View

45-1231.31N6.000.101



2D Right Side View



2D Top View

[Specifications](#) | [Bill of Materials](#)


Specifications

Actuator

[Illuminated pushbutton](#)

Lens Colour

White, transparent



2D Sales Drawing



Function	2 Positions, momentary (O<I)
Housing Material	Metal/Plastic
Shape of Handle or Frontring	raised/ level to bezel
Lock System	None
Key	None
Key Type	None
Switching Angle	None
Contacts	1NO
Terminal	Screw terminal
Voltage Illumination	24V AC/DC
Mounting Type	Front mounting
Mounting Style	Holder
Environmental Rating	IP66, IP67, IP69K
Industry Standards/Certifications	UL, CSA, VDE, CCC, CE, RoHS
Switching Function	On-Off
Illumination	White
Contact Material	Silver
Termination Style	Screw
Mechanical Life	Maintain 500'000 switching cycles Momentary 3'000'000 switching cycles
AC Voltage	500 V
DC Voltage	500 V
Switching Current	10 A

Bill of Materials

Actuator	45-2231.31N0.000
----------	------------------

Holder	45-2300.1000.000
Switch Element 1	45-311.1Z10
LED Module	45-320.1N16