


DUAL OPERATIONAL TRANSCONDUCTANCE AMPLIFIER


■ GENERAL DESCRIPTION

The NJM13600/13700 consist of two current controlled trans conductance amplifiers each with differential inputs and a push pull output. The two amplifiers share common supplies but otherwise operate independently. Linearizing diodes are provided at the inputs to reduce distortion and allow higher input levels. The result is a 10 dB signal-to-noise improvement referenced to 0.5 percent THD. Controlled impedance buffers are provided which are especially designed to complement the dynamic range of the amplifiers.

■ PACKAGE OUTLINE



NJM13600D
NJM13700D




NJM13600M
NJM13700M

■ FEATURES

- Package Outline DIP16,DMP16
- Bipolar Technology

■ PIN CONFIGURATION




NJM13600D,NJM13600M
NJM13700D,NJM13700M

PIN FUNCTION

- | | |
|---------------------|----------------------|
| 1. AMP BIAS INPUT A | 9. BUFFER OUTPUT B |
| 2. DIODE BIAS A | 10. BUFFER INPUT B |
| 3. +INPUT | 11. V^+ |
| 4. -INPUT | 12. OUTPUT B |
| 5. OUTPUT A | 13. -INPUT B |
| 6. V^- | 14. +INPUT B |
| 7. BUFFER INPUT A | 15. DIODE BIAS B |
| 8. BUFFER OUTPUT A | 16. AMP BIAS INPUT B |

■ EQUIVALENT CIRCUIT



NJM13600/13700

■ ABSOLUTE MAXIMUM RATINGS

(Ta=25°C)

PARAMETER	SYMBOL	RATINGS	UNIT
Supply Voltage	V^+V^-	36 or ± 18	V
Differential Input Voltage	V_{ID}	± 5	V
Diode Bias Current	I_D	2	mA
Amp Bias Current	I_{ABC}	2	mA
Buffer Output Current	I_O	20	mA
Power Dissipation	P_D	(DIP16) 570 (DMP16) 700 (note)	mW
DC Input Voltage	V_{IN}	$V^+ \sim V^-$	V
Operating Temperature Range	T_{opr}	-40~+85	°C
Storage Temperature Range	T_{stg}	-40~+125	°C

(note) At on a ceramic PCB (10x20x0.635 mm)

■ ELECTRICAL CHARACTERISTICS

($V^+V^- = \pm 15V, T_a = 25^\circ C, I_{ABC} = 500\mu A$)


PARAMETER	SYMBOL	TEST CONDITION	13600			13700			UNIT
			MIN.	TYP.	MAX.	MIN.	TYP.	MAX.	
Input Offset Voltage (V_{OS})	V_{IO}		-	0.4	5	-	0.4	4	mV
Input Offset Voltage		$I_{ABC} = 5\mu A$	-	0.3	5	-	0.3	4	mV
V_{OS} Including Diodes		Diode Bias Current, $I_D = 500\mu A$	-	0.5	5	-	0.5	5	mV
Input Offset Change		$5\mu A \leq I_{ABC} \leq 500\mu A$	-	0.1	-	-	0.1	3	mV
Input Bias Current	I_B		-	0.4	5	-	0.4	5	μA
Input Bias Current		(-20~+75°C)	-	1	8	-	1	8	μA
Forward Transconductance	gm		6700	9600	13000	6700	9600	13000	μS
		(-20~+75°C)	5400	-	-	5400	-	-	μS
gm Tracking		$R_L = 0, I_{ABC} = 5\mu A$	-	0.3	-	-	0.3	-	dB
Peak Output Current	I_{OP}	$R_L = 0, I_{ABC} = 5\mu A$	-	5	-	-	0	-	μA
Peak Output Current		$R_L = 0, I_{ABC} = 500\mu A$	350	500	650	350	500	650	μA
Peak Output Current		$R_L = 0$ (-20~+75°C)	300	-	-	300	-	-	μA
Peak Output Voltage Positive	V_{OP}	$R_L = \infty, 5\mu A \leq I_{ABC} \leq 500\mu A$	+12	+14.2	-	+12	+14.2	-	V
				2			2		
Peak Output Voltage Negative		$R_L = \infty, 5\mu A \leq I_{ABC} \leq 500\mu A$	-12	-14.4	-	-12	-14.4	-	V
Operating Current	I_{CC}	$I_{ABC} = 500\mu A$, two circuit	-	2.6	-	-	2.6	-	mA
V_{OS} Sensitivity Positive	SVR	$\Delta V_{OS} / \Delta V^+$	76.5	94	-	76.5	94	-	dB
V_{OS} Sensitivity Negative		$\Delta V_{OS} / \Delta V^-$	76.5	94	-	76.5	94	-	dB
Input Offset Current	I_{IO}		-	0.1	0.6	-	0.1	0.6	μA
CMRR	CMR		80	110	-	80	110	-	dB
Common Mode Range	V_{ICM}		± 12	± 13.5	-	± 12	± 13.5	-	V
Cross Talk	CT	20Hz<f<20kHz (note2)	-	-100	-	-	-100	-	dB
Differential Input Current	I_{ID}	$I_{ABC} = 0, Input = \pm 4V$	-	0.02	100	-	0.02	100	nA
Leakage Current	I_{LEAK}	$I_{ABC} = 0$ (Refer to Test Circuit)	-	0.2	100	-	0.2	100	nA
Input Resistance	R_{IN}		10	26	-	10	26	-	k Ω
Open Loop Bandwidth			-	2	-	-	2	-	MHz
Slew Rate	SR		-	50	-	-	50	-	V/ μs
Buffer Input Current		(note2)	-	0.4	5	-	0.4	5	μA
Peak Buffer Output Voltage		(note2)	10	-	-	10	-	-	V

(note1) Open unless otherwise specified. The inputs to the buffers are grounded and outputs are open.


(note2) $R_{OUT} = 5k\Omega$ connected from the buffer output to V^- and the input of buffer is connected to the transconductance amplifier output.

 $I_{ABC} = 500\mu A$

■ TEST CIRCUIT




Differential Input Current



Leakage Current

■ TYPICAL APPLICATIONS




NJM13600/13700

■ TYPICAL CHARACTERISTICS


Distortion vs. Differential Input Voltage

($V^+/V^- = \pm 15V$, $R_L = 10k\Omega$, $I_{ABC} = 1mA$, $T_a = 25^\circ C$)




Voltage vs. Amplifier Bias Current

($V^+/V^- = \pm 15V$, $R_L = 10k\Omega$, $T_a = 25^\circ C$)









Output Noise Current vs. Frequency

($T_a = 25^\circ C$)




■ TYPICAL CHARACTERISTICS



NJM13600/13700


■ TYPICAL CHARACTERISTICS

Input Leakage Current
($T_a = 25^\circ\text{C}$)




Transconductance

($V^+/V^- = \pm 15\text{V}$, Pin 2.15 Open, $T_a = 25^\circ\text{C}$)




Input Resistance

(Pin 2.15 Open, $T_a = 25^\circ\text{C}$)




Amplifier Bias Voltage vs. Amplifier Bias Current

($T_a = 25^\circ\text{C}$)




Input and Output Capacitance

($V^+/V^- = \pm 15\text{V}$, $T_a = 25^\circ\text{C}$)



Output Resistance

($T_a = 25^\circ\text{C}$)



[CAUTION]

The specifications on this databook are only given for information, without any guarantee as regards either mistakes or omissions. The application circuits in this databook are described only to show representative usages of the product and not intended for the guarantee or permission of any right including the industrial rights.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

NJR:

[NJM13700D](#) [NJM13700M](#) [NJM13600M](#) [NJM13600D](#) [NJM13700M-TE2](#)