

## Features

- Solid state, high reliability
- 316L stainless steel, ISO sensor design
- $\pm 0.5\%$  static accuracy
- Temperature compensated 32°F to 158°F (0°C to 70°C)
- 125 mV typical FSO on current version
- 75  $\pm 1$  mV FSO on voltage version
- Thermal errors less than 2% FSO
- Two standard ranges: 0 to 2.5 psig (0 to 1 bar), 0 to 5 psig (0 to 17.24 bar)
- Standard configurations include:
  - 0.74 in (19 mm) diameter x 0.28 in (7.1 mm) long cylinder with o-ring seals
- Custom configurations and other pressure ranges available. Please consult the factory.

## Applications

- Process control systems
- Hydraulic systems and valves
- Biomedical instruments
- Refrigeration and HVAC controls
- Appliances and consumer electronics
- Ship and marine systems
- Aircraft and avionic systems

NPI media isolated sensors are designed to operate in hostile environments and yet give the outstanding sensitivity, linearity, and hysteresis of a silicon sensor. The piezoresistive sensor chip is housed in a fluid-filled cylindrical cavity and isolated from measured media by a stainless steel diaphragm and body. The NPI Series employs SenStable® processing technology, providing excellent output stability. Available in either constant current or constant voltage version.


The modular design allows for a variety of pressure port modules, which are hermetically welded to the sensor header module. There are other standard port styles available. Please consult NovaSensor for more details.

---

# NPI-19 Series

## NovaSensor Low Pressure Sensors

NPI-19 Series is a NovaSensor product. NovaSensor has joined other GE high-technology sensing businesses under a new name—GE Industrial, Sensing.




# NPI-19 Series Specifications

## Operating

	Constant Current (1.5 mA)		Constant Voltage (10 V)	
	Value	Notes	Value	Notes
<b>General</b>				
<i>Pressure Ranges</i>				
2 PSI	0 to 2.5 psi (0 to 172 mbar)	17.2 kPa	0 to 2.5 psi (0 to 172 mbar)	17.2 kPa
5 PSI	0 to 5 psi (0 to 345 mbar)	34.5 KPa	0 to 5 psi (0 to 345 mbar)	34.5 KPa
Maximum Overpressure	3x pressure	rated	3x pressure	rated
<b>Electrical @ 77°F (25°C) unless otherwise stated</b>				
Input Excitation	1.5 mA maximum	2 mA maximum	10 VDC	12 VDC
Insulation Resistance	10 <sup>8</sup> Ω	@ 50 VDC	10 <sup>8</sup> Ω	@ 50 VDC
Input Impedance	4000 Ω	typical	10,000 Ω	typical
Output Impedance	5000 Ω	±20%	5000 Ω	±20%
Bridge Impedance	5000 Ω	±20%	5000 Ω	±20%
<b>Environmental</b>				
Compensated Temperature	32°F to 158°F	(0°C to 70°C)	32°F to 158°F	(0°C to 70°C)
Operating Temperature	14°F to 176°F	(-10°C to 80°C)	14°F to 176°F	(-10°C to 80°C)
Storage Temperature	-40°F to 257°F	(-40°C to 125°C)	-40°F to 257°F	(-40°C to 125°C)
<b>Mechanical</b>				
Weight	0.02 lb (10 g)	NPT-19A-XXX	0.02 lb (10 g)	NPT-19A-XXX
Media Compatibility	All corrosive media compatible with 316 L stainless steel		All corrosive media compatible with 316 L stainless steel	
Case and Diaphragm Material	316L stainless steel		316L stainless steel	
Recommended O-Ring	NPI-19A; 0.66 in x 0.039 in (16.76 mm x 1 mm)		NPI-19A; 0.66 in x 0.039 in (16.76 mm x 1 mm)	

Compensated Performance (1.5 mA)					(10 VDC)				
Parameter	Units	Minimum	Type	Maximum	Units	Minimum	Type	Maximum	
<b>Notes</b>									
Offset	mV	-2	±1	2	mV	-2	±1	2	
<b>Full Scale Output</b>									
2 PSI	mV	50	125	200	mV	72	75	78	
5 PSI	mV	50	125	200	mV	74	75	76	
Static Accuracy	%FSO	-0.5	0.1	0.5	%FSO	-0.5	0.1	0.5	2
<b>Thermal Accuracy of Offset</b>									
2 PSI	%FSO	-2	±0.5	2	%FSO	-2	±0.5	2	3
5 PSI	%FSO	-1.5	±0.5	1.5	%FSO	-1.5	±0.5	1.5	3
<b>Thermal Accuracy of FSO</b>									
2 PSI	%FSO	-2	±0.5	2	%FSO	-2	±0.5	2	3
5 PSI	%FSO	-1.0	±0.5	1.0	%FSO	-1.0	±0.5	1.0	3
<b>Thermal Repeatability</b>									
2 PSI	%FSO	-0.3	0.1	0.3	%FSO	-0.2	0.1	0.2	3
5 PSI	%FSO	-0.2	0.1	0.2	%FSO	-0.2	0.1	0.2	3

1. Performance with offset, thermal accuracy of offset, and thermal accuracy of FSO compensation resistors. All values measured at 77°F (25°C) and at 1.5 mA constant current or 10 VDC, unless otherwise noted.
2. Includes Linearity (BFSL), pressure hysteresis and repeatability errors.
3. 32°F to 158°F (0°C to 70°C) with reference to 77°F (25°C).
4. Consult factory for vacuum applications.




# NPI-19 Series Specifications

## Ordering Information


The code number to be ordered may be specified as follows:

NPI-19 NovaSensor Pressure Type (ISO Sensor)			
Code	Pressure Port Type		
A	No port, o-ring seal		
Code	Pressure Range		
021	2.5 psi (172 mbar), 1.5 mA		
002	2.5 psi (172 mbar), 10 V		
031	5 psi (345 mbar), 1.5 mA		
005	5 psi (345 mbar), 10 V		
Code	Description		
G	Gauge		
Code	Tolerance		
H	Constant Current Supply (1.5 mA)		
V	Constant Voltage Supply (10 VDC)		

NPI-19 - - - - - Typical model number



Constant current schematic diagram



Constant voltage schematic diagram



©2006 GE. All rights reserved.  
920-298A

All specifications are subject to change for product improvement without notice.  
GE® is a registered trademark of General Electric Co. Other company or product names mentioned in this document may be trademarks or registered trademarks of their respective companies, which are not affiliated with GE.

[www.gesensing.com](http://www.gesensing.com)