


THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

PANDUIT P/N	PANEL THICKNESS	RECOM'D MTG HOLE DIA.	COLOR	WEIGHT
NR2WH-L	.170-.190(4.3- 4.8)	.320(8.1)	NATURAL (WHITE)	.07 LB/50 PCS (32g/50 PCS)
NR4BL-L	.220-.240(5.6-6.1)	.320(8.1)	BLACK	.07 LB/50 PCS (33g/50 PCS)
NR2WH-12	.170-.190(4.3- 4.8)	.320(8.1)	NATURAL (WHITE)	.02 LB/12 PCS (11g/12 PCS)
NR4BL-12	.220-.240(5.6-6.1)	.320(8.1)	BLACK	.02 LB/12 PCS (11g/12 PCS)

NOTES:

1. NR2WH IS TO BE USED WITH PANDUIT 2X2 FIBEROPTIC DUCT AND FITTINGS. NR4BL IS TO BE USED WITH PANDUIT 4X4 FIBEROPTIC DUCT AND FITTINGS.
2. DIMENSIONS IN PARENTHESES ARE IN METRIC.



CAD FILENAME/LAYERS				D36086BD_DC_NR2WH_NR4BL_02			
PANDUIT							
CORP. TINLEY PARK, ILLINOIS							
SNAP RIVET KIT							
(NR2WH-L, NR4BL-L, NR2WH-12, NR4BL-12)							
CUSTOMER DRAWING							
UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: (.X) ± (.XXX) ± (.XX) ± ANGLES ±				UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE GIVEN IN INCHES, THIRD ANGLE PROJECTION.			
DRAWN BY				DW		SCALE	
DATE				7/25/97		NONE	
CHECKED BY				HIW		DRAWING NO.	
REV				DATE		36086-04	
BY				CHK		SIZE	
DESCRIPTION				ECN		A	

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

NR4BL-L