


Wirewound Resistors, Commercial High Power, Quick Connect Terminals



FEATURES

- Can be purchased with or without brackets installed ("BKT" SPECIAL)
- Quick connect terminals
- High power ratings
- Special inorganic potting compound and ceramic case provide high thermal conductivity in a fireproof package
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912



RoHS
COMPLIANT
HALOGEN
FREE
GREEN
(5-2008)

STANDARD ELECTRICAL SPECIFICATIONS

GLOBAL MODEL	POWER RATING $P_{40^{\circ}\text{C}}$ W	RESISTANCE RANGE Ω	TOLERANCE $\pm \%$	WEIGHT (typical) g
PC-30	30	1 to 2K	5, 10	45
PC-40	40	1 to 2K	5, 10	75
PC-50	50	1 to 2K	5, 10	75

TECHNICAL SPECIFICATIONS

PARAMETER	UNIT	PC QUICK CONNECT CHARACTERISTICS
Temperature Coefficient	ppm/ $^{\circ}\text{C}$	± 300
Short Time Overload	-	10 x rated power for 5 s
Operating Temperature Range	$^{\circ}\text{C}$	-55 to +275
Dielectric Withstanding Voltage	V_{AC}	1000
Maximum Continuous Working Voltage	V	$(P \times R)^{1/2}$

GLOBAL PART NUMBER INFORMATION


Global Part Numbering example: **PC-3022R00KE66** (Visit www.vishay.net SAP Parts Manual for all options)

P	C	-	3	0	2	2	R	0	0	K	E	6	6			
GLOBAL MODEL (5 digits)			VALUE (5 digits)			TOLERANCE (1 digit)			PACKAGING CODE (3 digits)			SPECIAL (up to 3 digits)				
PC-30 PC-40 PC-50			R = decimal K = thousand 15R00 = 15 Ω 1K500 = 1.5 k Ω			J = $\pm 5 \%$ K = $\pm 10 \%$			E66 = lead (Pb) free bulk pack			(dash number) from 1 to 999 as applicable BKT = brackets				

Historical Part Number example: **PC-30-22-10 %**

PC-30	22 Ω	10 %
HISTORICAL MODEL	RESISTANCE VALUE	TOLERANCE

DIMENSIONS in inches [millimeters]



GLOBAL MODEL	DIMENSIONS in inches [millimeters]					
	W ± 0.039 [1.00]	H ± 0.039 [1.00]	L ± 0.059 [1.50]	H_1 ± 0.039 [1.00]	P ± 0.079 [2.00]	D ± 0.02 [0.50]
PC-30	0.75 [19.00]	0.75 [19.00]	2.95 [75.00]	1.22 [31.00]	2.17 [55.00]	0.30 [7.50]
PC-40	0.75 [19.00]	0.75 [19.00]	3.54 [90.00]	1.22 [31.00]	2.64 [67.00]	0.30 [7.50]
PC-50	0.75 [19.00]	0.75 [19.00]	3.54 [90.00]	1.22 [31.00]	2.64 [67.00]	0.30 [7.50]

MATERIAL SPECIFICATIONS

Element: copper-nickel alloy or nickel-chrome alloy, depending on resistance value


Core: high purity grade alumina ceramic rod

Body: steatite ceramic case with inorganic potting compound

Terminals: 100 % tin

Part Marking: HEI, model, wattage, value, tolerance, date code

DERATING



PERFORMANCE		
TEST	CONDITIONS OF TEST	TEST LIMITS
Short Time Overload	10 x rated power for 5 s	$\pm 2\% \Delta R$
Load Life	1000 h at rated power, +70 °C, 1.5 h "ON", 0.5 h "OFF"	$\pm 5\% \Delta R$
Temperature Cycle	-30 °C; ~85 °C for 5 cycles	$\pm 1\% \Delta R$



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.