

## 3.2-3.8kW Single-Phase Metered PDU, 200-240V (8 C13 & 2 C19), C20 / L6-20P Adapter, 12ft Cord, 1U Rack-Mount

MODEL NUMBER: **PDUMH20HV**



### Description

Tripp Lite Metered PDU / Power Distribution Units offer real-time local reporting of load level in amps via built-in digital meter. Enables visual current monitoring of PDU output current to prevent circuit overloads as additional equipment is added. Offers reliable rackmount multi-outlet power distribution from any protected UPS, generator or mains input power source. High quality design includes rugged all-metal housing and secure rackmount installation with included mounting accessories.

### Features

- 16/20A single phase 200-240V Metered Power Distribution Unit / PDU(Agency de-rated to 16A continuous)
- Built-in 2 digit visual meter continuously reports PDU load level in amps
- C20 inlet with C20 input cable and L6-20P adapter; 12 ft. / 3.7m line cord
- 1U horizontal rackmount format installs in one rack space
- 10 total outlets(8 C13 / 2 C19)
- Mounting flanges support installation in 2 and 4 post racks, with additional support for wall-mount and under-counter installation formats
- Mounting ears are reversible for front or rear facing rackmount installation
- Optional [PDUSIDEBRKT](#) enables 0U vertical rackmount in compatible racks
- Back panel grounding lug
- TAA Compliant Version Available - Order Tripp Lite [PDUMH20HVTAA](#)

### Specifications

OVERVIEW	
PDU Type	Metered
OUTPUT	

### Highlights

- Metered single phase 16/20A 200-240V PDU
- 1U horizontal rackmount; Digital current meter
- C20 input with L6-20P plug adapter; 12 ft. / 3.7m line cord
- 10 total outlets (8 C13, 2 C19)
- Reversible housing; 6.5 in. / 16.5 cm depth

### Applications

- Ideal for network configurations requiring a metered PDU

### Package Includes

- Rackmount PDU
- C19 to L6-20P plug adapter
- Rack mounting brackets

Output Capacity Details	3.33kW (208V), 3.52kW (220V), 3.68kW (230V), 3.84kW (240V), 3.2kW (200V); 20A maximum (Agency de-rated to 16A continuous)
Frequency Compatibility	50 / 60 Hz
Output Receptacles	(8) C13; (2) C19
Output Nominal Voltage	200-240V nominal, single phase
Overload Protection	n/a
Outlet Type	IEC-C13, IEC-C19
Individual Outlet Switching	No
<b>INPUT</b>	
PDU Input Voltage	200; 208; 220; 230; 240
Recommended Electrical Service	20A 208/240V; 16A 230V
Maximum Input Amps	20
Maximum Input Amps Details	Agency de-rated to 16A continuous
PDU Plug Type	NEMA L6-20P; IEC-320 C20
Input Cord Length (ft.)	12
Input Cord Length (m)	3.7
Input Cord Details	Includes 12 ft. / 3.6m C19 to C20 power cable and L6-20P plug adapter
Input Phase	Single-Phase
<b>USER INTERFACE, ALERTS &amp; CONTROLS</b>	
Front Panel LCD Display	Digital display reports total PDU output current in amps
Switches	n/a
<b>PHYSICAL</b>	
Shipping Dimensions (hwd / in.)	2.25 x 20.5 x 10.5
Shipping Dimensions (hwd / cm)	5.7 x 52.1 x 26.7
Shipping Weight (lbs.)	7.2
Shipping Weight (kg)	3.3
Unit Dimensions (hwd / in.)	1.75 x 17.5 x 6.5
Unit Dimensions (hwd / cm)	2.87 x 44.4 x 16.5
Unit Weight (lbs.)	6.8
Unit Weight (kg)	3.1
Material of Construction	Metal
Form Factors Supported	1U rackmount. Includes mounting accessories for 2-4 post racks
PDU Form Factor	Horizontal (1U, 2U, etc)



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

#### ENVIRONMENTAL

Storage Temperature Range	5-122F (-15 to 50C)
Relative Humidity	5-95% non-condensing
Operating Elevation (ft.)	0-10,000
Operating Elevation (m)	0-3000

#### SPECIAL FEATURES

TVSS Grounding	Rear grounding lug
----------------	--------------------

#### CERTIFICATIONS

TAA Compliant Option	TAA Compliant Version Available - Order Tripp Lite PDUMH20HVTAA
Certifications	Tested to UL 60950-1 (USA, Canada), Class A (Emissions), NOM (Mexico), CE (IEC 60950), (RoHS compliant)

#### WARRANTY

Product Warranty Period (Worldwide)	2-year limited warranty
-------------------------------------	-------------------------

© 2015 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<http://www.tripplite.com/products/product-certification-agencies>