



SOLUTIONS

PRODUCTS AND SERVICES

SUPPORT

ABOUT US

Search Panduit.com

GO



Search within category

GO

BUY NOW

DESIGN / INSTALL



PLT2I-M

Pan-Ty® locking tie, intermediate cross section, 8.0" (203mm) length, nylon 6.6, natural, bulk package.

Specs

Packaging Details

Tools

Documents

★ Add to Favorites

🛒 Add to BOM

Material	Nylon 6.6
Color	Natural
Cross Section	Intermediate
Locking Style	Locking
Min. Loop Tensile Strength Lbs. (N)	40 (178)
Plenum-Rated	Yes, AH-2
Tool	GTS-E, GS2B, PTS, PPTS, STS2
Length In (mm)	8.0 (203)
Thickness In (mm)	0.045 (1.1)
Bundle Diameter Range In. (mm)	0.06 (1.5) - 2.00 (51)
CE Compliant	Yes
CSA Certified	Yes
Mil. Std. Part Number	—
UL 62275 Compliant (Type 1, 11)	No
UL 62275 Compliant (Type 2, 21)	Yes
UL Listed (File #E56854)	Yes
UL Recognized (File #E56854)	Yes
Application	General
Continuous Use Temperature Range	-76°F (-60°C) - 185°F (85°C)
Environment	Plenum
Installation Temperature	-4°F (-20°C) - 32°F (0°C)
Min. Loop Tensile Strength (N)	178
Operating Temperature	-76°F (-60°C) - 185°F (85°C)
Part Features	One-piece locking wedge for cable and high loop tensile strength
UV Resistant	false
Width In (mm)	0.142 (3.6)

Request a Quote
Are you looking for a free quote on Panduit
Products and Solutions?

Yes, I need a quote! ▶

RoHS Compliancy Status Compliant

Min. Order Qty.	1,000.0000
-----------------	------------

[LEGAL INFORMATION](#) | [PRIVACY POLICY](#) | [CONTACT US](#) | [SITE MAP](#) | [WHERE TO BUY](#) | [JOBS](#) | [UNSUBSCRIBE](#)

Request a Quote

Are you looking for a free quote on Panduit Products and Solutions?

Yes, I need a quote!