

Waber-by-TrippLite SurgeSuppressor

Heavy-duty metal housing



Model#: DG115 -SI

- ▶ 6 outlets/6ft. cord
- ▶ 600 joule rating
- ▶ Visual surge indication

DESCRIPTION

The Waber -by-Tripp Lite DG115 -SI Power Strip offers a convenient method of power distribution and surge suppression in workbench, wallmount or floor mount applications. Includes 6 NEMA 5 -15R output receptacles, 6 foot AC line cord and keyhole mounting tabs for installation in a wide variety of applications. Protects connected equipment from transient surges and line noise with built-in surge suppression rated at 600 joules. Corded, multi -outlet strip reduces cabling clutter and enables the connection of multiple electrical devices to a single AC wall socket. Features metal housing, lighted power switch with integrated 15 amp resettable circuit breaker and attractive gray color scheme. Lifetime warranty.

PLUG/OUTLETS -Input: NEMA 5 -15P/Output: 6 NEMA 5 -15R

ELECTRICAL -120VAC, 50/60Hz, 15A (Requires standard NEMA 5 -15R wall receptacle)

FORMAT -Corded power distribution strip with remote power switch on a 6ft. cord

SUPPRESSION -600 joules AC suppression

KEY BUYING POINTS

- Multi-outlet power strip offers convenient power distribution in workbench, wallmount or floor mount applications
- Includes 6 NEMA 5 -15R output receptacles
- Lighted combination power switch with integrated circuit breaker
- Keyhole mounting tab support permanent installation on a wide variety of surfaces
- UL 1449 (USA/400V rating), UL 1363 (USA), cUL (Canada)
- 15 amp power handling capacity
- 6 foot AC line cord
- Lifetime warranty

TYPICAL APPLICATIONS

- Offers multiple outlet power distribution and surge suppression in workbench, wallmount or floor mount applications. Ideal protection for home appliances, entertainment centers, industrial equipment and other electronic loads.

PACKAGE INCLUDES

- DG115-SI Power Strip
- Warranty information
- Instruction manual

COMPLETE SPECIFICATIONS

SYSTEM OVERVIEW	
Voltage compatibility:	120VAC
Frequency compatibility:	50/60Hz
OUTPUT	
Output voltage capacity (amps):	15
Output watt capacity (watts):	1800
Outlet quantity/type:	6 NEMA 5 -15R output receptacles
Overload protection:	15A resettable circuit breaker
INPUT	
Input connection type:	NEMA 5 -15P input plug
Input cord length (ft.):	6
Input cord length (m):	1.8
Input cord gauge, type:	14 gauge, SJT
Recommended electrical service:	120V 15A
LEDS ALARMS & SWITCHES	
Diagnostic LEDs:	Protection present (green)
Switches:	Lighted two position power switch controls power to all outlets
Locking switch cover:	Transparent locking switch cover prevents accidental shutoff
AC SURGE/NOISE SUPPRESSION	
Protection modes:	Includes full normal mode (H -N) and common mode (N -G/H -G) line surge suppression
AC suppression joule rating:	600 joules
AC suppression response time:	<1ns
UL 1499 let through rating:	400V -UL Verified
EMI/RFI filtering:	Up to 20dB
Immunity:	Conform to IEE 587/ANSI C62.41
PHYSICAL	
Unit Dimensions (HWD/in):	12.5x2.5x1.5
Unit Dimensions (HWD/cm):	31.75x6.35x3.8
Material of construction:	Metal
Integrated keyhole mounting tabs:	Keyhole mounting tabs enable wall mounting
Housing color:	Gray
Receptacle color:	Gray
AC line cord color:	Gray
CERTIFICATIONS	
UL 1449 1998 Rev. (AC Suppression):	UL 1449
UL 1363 (Power Tap):	UL 1363
cUL/CSA (Canada):	cUL
WARRANTY	
Product warranty:	Lifetime

*The policy of Tripp Lite is one of continuous improvement.
Specifications are subject to change without notice.
Therefore, your product may vary slightly from what is currently listed.
Please make note that this information was posted on 08/04/2003.*



Tripp Lite World Headquarters
1111 W. 35th Street
Chicago, IL 60609 USA

Customer Support
(773) 869 - 1234

© 2003 Tripp Lite. All Rights Reserved.