

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

NOT for Patient-Care Rooms - UL1363 Medical-Grade Power Strip with 4 Hospital-Grade Outlets, 15-ft. Cord

MODEL NUMBER: PS-415-HG



Highlights

- Versatile power distribution strip
- 4 hospital-grade receptacles and hospital-grade plug
- 15-ft. cord
- 15A resettable circuit breaker

Applications

- AC power distribution with hospital-grade receptacles and plug where durability and reliability are required.
- Not for use where NEC requires hospital-grade receptacles.

Package Includes

- PS-415-HG Power Strip
- Owner's manual and warranty information

Description

Tripp Lite's PS-415-HG Power Strip offers 15A AC power distribution in a rugged all-metal outlet strip for 120V applications. Features 4 output receptacles, 15-ft. AC power cord and a built-in resettable circuit breaker that controls power to all outlets and protects against overloads. Switchless design prevents accidental shutoff. Optional-use keyhole mounting tabs and flanges.

PLUG/OUTLETS: NEMA 5-15P-HG hospital-grade plug and 4 NEMA5-15R-HG hospital-grade receptacles

ELECTRICAL: 120V AC, 50/60Hz, 15A

FORMAT: All-metal corded multi-outlet strip

Features

- Rugged all-metal housing withstands years of use without breakage
- 4 x NEMA 5-15R-HG hospital-grade output receptacles
- 15-ft. AC cord with integrated, molded NEMA5-15P-HG hospital-grade plug
- Optional-use keyhole mounting tabs and flanges
- Switchless design prevents accidental shutoff
- 15A electrical capacity with built-in resettable circuit breaker
- 120V, 50/60Hz
- Certified by UL (USA) and cUL (Canada)

Specifications

OVERVIEW		
Style	Strip	



WARRANTY			
cUL / CSA (Canada)	cUL (Series Number: AGIB12015SL)		
UL1363 (Power Tap)	UL1363 (Series Number: AGIB12015SL)		
CERTIFICATIONS			
Keyhole Slot Mounting Measurement (Center to Center)	Distance between keyhole tabs = 127mm; Distance between end tabs = 207.45mm		
Outlets Measurement (Center to Center)	Inner outlets = 32.5mm		
Color (AC Line Cord)	White		
Receptacle Color	White		
Integrated Keyhole Mounting Tabs	Keyhole mounting tabs and flanges enable mounting to a variety of surfaces		
Material of Construction	Metal		
Unit Dimensions (hwd / cm)	3.8 x 21.9 x 6.4		
Unit Dimensions (hwd / in.)	1.5 x 8.65 x 2.5		
PHYSICAL			
Audible Alarm	No power switch		
LEDS ALARMS & SWITCHES			
Voltage Compatibility (VAC)	120		
Input Cord Length (m)	4.572		
Input Cord Length (ft.)	15		
Input Connection Type	NEMA 5-15P-HG		
Recommended Electrical Service	15A 120V		
Nominal Input Voltage(s) Supported	120V AC		
INPUT			
Outlet Orientation	Single row of 4		
Overload Protection	15A circuit breaker		
Circuit Breaker (amps)	15		
Output Receptacles	(4) 5-15R-HG		
Frequency Compatibility	50 / 60 Hz		
OUTPUT			
Model Type	NOT For Patient Areas		



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Product Warranty Period (Worldwide)	Lifetime limited warranty
-------------------------------------	---------------------------

© 2015 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.