


PANDUIT PART NUMBER	STUD SIZE	DIMENSIONS in.				
PREFIX		A	W	C	M	H
PV18-6FX	#6	.88 (22.35)	.30 (7.62)	.21 (5.33)	.69 (17.53)	.15 (3.81)
PV18-8FX	#8	.95 (24.13)	.32 (8.13)	.25 (6.35)	.73 (18.54)	.17 (4.32)
PV18-10FX	#10	.97 (24.64)	.35 (8.89)	.25 (6.35)	.75 (19.05)	.20 (5.08)

NOTES :

- UL LISTED AND CSA CERTIFIED FOR:
A. 600 V MAX. VOLTAGE RATING
B. 221°F (105°C) MAX. TEMP. RATING
C. #22-18 AWG SOLID OR STRANDED, COPPER WIRE
- SEE www.panduit.com
FOR PART NUMBER SUFFIX DESIGNATION FOR PACKAGE SIZE
- MATERIAL:
A. STAMPING - .032 (.81) THK COPPER, TIN PLATED
B. HOUSING - RED VINYL
- WIRE STRIP LENGTH: $5/16 \begin{smallmatrix} +1/32 \\ -00 \end{smallmatrix}$ (7.94 $\begin{smallmatrix} +.80 \\ -.00 \end{smallmatrix}$)
- DIMENSIONS IN BRACKETS ARE IN MILLIMETERS
- INSTALLATION TOOLS:
A. UL AND CSA APPROVED: CT-100,
B. UL AND CSA APPROVED FOR EXPANDED WIRE RANGE # 22-16AWG:
CT-100A, CT-500, CT-500CH, CT-550, CT-550CH, CT-600-A,
CT-1550, CT-1551, CT-2500, CT2550CH
C. PANDUIT APPROVED: CT-160, CT-260



LISTED
587H
E52164



CERTIFIED
LR31212

07	8/11	SHOR	NUMERICALLY ARRANGED INSTALLATION TOOLS	PANDUIT CORP. TINLEY PARK, ILLINOIS			
06	4/11	SRB	Removed PK column and changed Packaging note #2 referring package qty to Panduit website. Also added expanded wire range tools: CT-100A, CT-600A, CT-500CH, CT-550CH, CT-1550, CT-1551, CT-2500, CT-2550				
REV	DATE	BY	DESCRIPTION	DRAWN BY DRL	CHK'D	SCALE NONE	DRAWING NO. A41459

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

[PV18-6FX-MY](#) [PV18-8FX-MY](#) [PV18-10FX-CY](#) [PV18-8FX-CY](#) [PV18-6FX-CY](#) [PV18-10FX-MY](#)