



Technical Specifications:					
Model (does not include kits)	Model (includes kits)	Cable Length	Cable Diameter	Shaft Type	Procedure
PV-100	PVM-100	18"/457.2mm	.4"/10.5mm	Obedient	Search Bags, auto a/c, view around corners
PV-618	PVM-618	18"/457.2mm	.23"/5.8mm	Non-Obedient	Search Bags, behind auto doors, Auto a/c
PV-300	PVM-300	36"/914.4mm	.4"/10.5mm	Obedient	Search Bags, Gas/fuel tanks, behind walls, View around corners between door panels
PV-636	PVM-636	36"/914.4mm	.23"/5.8mm	Non-Obedient	Search Gas/Fuel Tanks, behind walls, between door panels
PV-480	PVM-480	48"/1219.2mm	.4"/10.5mm	Obedient	Inspect cargo, Gas/FuelTanks, behind walls, Inside packages and crates
PV-720	PVM-720	72"/1828.8mm	.4"/10.5mm	Obedient	Inspect cargo, Gas/FuelTanks, behind walls, Inside packages and crates
PV-960	PVM-960	96"/2438.4mm	.4"/10.5mm	Obedient	Inspect cargo, Gas/FuelTanks, behind walls, Inside packages and crates
Field of View: 40°			Lamp: 2.7v		
Optimal Viewing Distance:			Power Source: 2 AA Batteries (not included)		
Min.: .8" / 20mm Max.: Dependent upon ambient lighting conditions.			Operating Pressure: 2.9 avg. p/psi / 3.2 max. p/psi		