

3140 Refrigerator Door Switches *Splashproof*



5A 250Vac 25T85 5E4 (50,000 Operations)



UL CSA 5A 250Vac

UL 85°C, file E45221, CSA file LR10990

In house test

24V 110Vac Lampload (500,000 operations)



RoHS compliant

3141, μ contact gap.

3145 and 3146, 3mm contact gap.

Technical data on pages 4 & 5.

Sealed terminals option available. Call factory for details.

- ▶ Door switches
- ▶ Ratings up to 5A, 250V ac
- ▶ Splashproof
- ▶ Momentary action
- ▶ Choice of actuators
- ▶ 2 circuit switch



HK3141AA








H3145AA

ORDER FORMAT

HK 3141 A A

TERMINALS CODE FUNCTION CODE ACTUATOR CODE BODY CODE

▶ TERMINAL	▶ FUNCTION	▶ ACTUATOR	▶ BODY	▶ OPTIONS
H  4.8 x 0.8 Standard format is H terminals in positions 1 & 2 and K terminals in positions 3 & 4 For sealed terminals call the factory	 3141  3145  3146	A  B  C  D 	A  Panel cut-out Panel thickness 1.0 - 2.5mm	Finish Gloss finish only Color White is standard Call factory for custom colors A full range is available for large orders

Dimensions (mm) ("A" actuator shown)

3141 uses terminals 1,2,3,4

3145 uses terminals 3,4

3146 uses terminals 1,2

For details of actuator travel and switching angles call the factory.

