



A

Pushbutton

ELUM™ Series Right Angle Illuminated Latching Pushbutton

**LEAD FREE
COMPATIBLE OPTION**

Features/Benefits

- **SPDT (N.O. & N.C.)**
- **Low height above PCB**
- **Reliable self-cleaning contact**
- **Surface-mount or thru-hole PCB**
- **Standard or custom actuator**
- **Central LED illumination**
- **Latching or Momentary**
- **Long travel. Smooth feel**
- **RoHS compliant and compatible**

Typical Applications

- **Telecom network equipment**
- **Automotive electronics**
- **Consumer electronics**
- **Computer, server, modem, data storage**
- **Professional instrumentation, medical**

Patent Numbers
6,974,924 B2 US
EP1583118B1 Europe



Materials

FIXED CONTACTS: Stainless steel, silver plated with gold flash
TERMINALS: Stainless steel, silver plated
MOVABLE CONTACTS: Copper alloy, silver plated with gold flash
BASE: Glass filled LCP (UL94V-0)
ACTUATOR: Glass filled nylon 4/6 (UL94V-0)
COVER: Stainless steel

Electrical

MAXIMUM POWER: 3.5 VA
MIN./MAX. VOLTAGE: 20 mV – 50 VDC
MIN./MAX. CURRENT: 0.01 mA – 250 mA
DIELECTRIC STRENGTH: ≥ 250 Vrms
CONTACT RESISTANCE: ≤ 50 m Ω
INSULATION RESISTANCE: $\geq 10^9$ Ω
BOUNCE TIME: ≤ 1 ms
LED SPECIFICATIONS: See page A-5

Mechanical

OPERATING FORCE: 2.5 N at Full Travel
SWITCHING TRAVEL: .067" (1.7 mm)
LATCH TRAVEL: .131" (3.6 mm)
FULL TRAVEL: .200" (5.1 mm)

Operating Environment

OPERATING TEMPERATURE: -40°C TO 80°C.
STORAGE TEMPERATURE: -40°C TO 80°C.
RELATIVE HUMIDITY: 90% R.H. @ 80°C.
OPERATING LIFE: 30,000 Cycles.
VIBRATION: Per EIA 186-E Method
MECHANICAL SHOCK: Per EIA 186-E Method 12.
OVERLOAD: Withstands 40 N for 1 minute without damage

Process Environment

SOLDERABILITY: According to Mil STD 202F Method 208D or EIA RS-186E Method 9.
LEAD FREE PROCESS COMPATIBLE: 260°C peak, 10 seconds Max. above 250° C.
WASHING PROCESS: No clean process compatible (SMT)
Bottom wash compatible (Thru-hole)
SHEAR TEST (SWITCH/PCB): > 40 N

Packaging

"SA" Terminal Style SMT: Tape and reel per EIA 481-2 (450/reel)
"TH" Terminal Style PC: Tray (60/tray)

NOTE: Any models supplied with Q, contact material are RoHS compliant.


NOTE: Specifications and materials listed above are for switches with standard options. For information on specific and custom switches, please contact Customer Service.

Build-A-Switch

To order, simply select desired option from each category and place in the appropriate box.

Designation _____ ELUM ELUM Series Switch Function _____ OA Momentary OC*** Momentary short travel EE Latching (push-push) Terminal Style _____ TH Right Angle, PC thru-hole SA Right Angle, surface mount Contact Material* _____ Q Silver with gold flash Illumination _____ (NONE) Models without illumination 1 LED White 2 LED Bi-color – Red (Green) 3 LED Red 5 LED Amber 6 LED Green 7 LED Blue 8 LED Bi-Color – Amber (Green)	E L U M Q	Actuator Style** C02 Black without window C12 Black with window C22 Black with window and snap feature for custom actuators
--	---	---

* Other plating options available, please contact Customer Service.
** Custom actuators available, please contact Customer Service.
*** Short travel available in momentary only.



Dimensions are shown: Inches (mm)
Specifications and dimensions subject to change




Pushbutton

ELUMOATHQ6C12



PC THRU-HOLE



Technical drawing of the 100 Series Locking Bolt Assembly. The drawing includes two views: a front view (top) and a side view (bottom). Dimensions are provided in inches and millimeters.

Front View Dimensions:

- Overall width: .200 (5,08)
- Overall height: .450 (11,43)

Side View Dimensions:

- Overall length: .810 (20,58)
- Overall height: .237 (6,01)
- Distance from front face to start of bolt: .160 (4,06)
- Distance from front face to end of bolt: .824 (20,94)
- Distance from front face to end of housing: .854 (21,7)

ACTUATOR SHOWN EXTENDED POSITION

ELUM — — — —



SWITCH FUNCTION



For SPST N.O. function, only terminals 3 & 2 are used.
For SPST N.C. function, only terminals 3 & 4 are used.
Circuit: Make before break

LED pins 1 & 5 are independent of switch function.

For bi-color LED's the polarity must be reversed to alternate the color



Dimensions are shown: Inches (mm)
Specifications and dimensions subject to change

www.ck-components.com


**A****Pushbutton**

ELUM™ Series Right Angle Illuminated Latching Pushbutton


TERMINAL STYLE



SA RIGHT ANGLE, SURFACE MOUNT



TH RIGHT ANGLE, PC THRU-HOLE



CONTACT MATERIAL



OPTION CODE	CONTACT MATERIAL	TERMINAL PLATING	RATINGS
Q	SILVER WITH GOLD FLASH	SILVER	250 mA

* Note: See Technical Data section of this catalog for RoHS compliant and compatible definitions and specifications.

FIXED CONTACTS AND TERMINALS: Stainless steel, silver plated with gold flash

MOVABLE CONTACTS: Copper alloy, silver plated with gold flash

NOTE: Any models supplied with Q, contact material are RoHS compliant.

ILLUMINATION




OPTION CODE	ILLUMINATION TYPE	TYPICAL INTENSITY* MIN	TYPICAL INTENSITY* MAX	PEAK WAVELENGTH	Vf Forward Voltage
		(mcd)		(nm)	
0	Model without illumination	N/A	N/A	N/A	
1	LED Super White	4,000	5,000	N/A	3.5
2	LED Bi-Color – Red (Green)	10	20	635/565	2.0
3	LED Red	4	8	700	2.0
5	LED Amber	35	50	610	2.0
6	LED Green	35	50	565	2.0
7	LED Super Blue	800	1,500	470	3.8
8	LED Bi-Color – Amber (Green)	10	10	585/565	2.0

*LED FORWARD CURRENT: 20 mA

LED FORWARD VOLTAGE: see chart above

LED REVERSE VOLTAGE: 5.0 V MAX

* For information on specific and custom LED, please contact Customer Service.



Third Angle
Projection



Dimensions are shown: Inches (mm)
Specifications and dimensions subject to change

www.ck-components.com

ELUM™ Series Right Angle Illuminated Latching Pushbutton




A

Pushbutton


ACTUATOR STYLE*




C02 BLACK WITHOUT WINDOW



C12 BLACK WITH WINDOW




C22 BLACK WITH WINDOW AND SNAP FEATURE TO ACCEPT CUSTOM CAP





* Custom actuators available, please contact Customer Service.

FORCE TRAVEL DIAGRAM



OA, EE ACTUATOR POSITION			
A	SWITCH POINT	.067 ± .020	1,7 ± 0.5mm
B	LATCH	.131 ± .020	3,3 ± 0.5mm
C	FULL ACTUATION	.200 ± .020	5,1 ± 0.5mm
OC ACTUATOR POSITION			
A	SWITCH POINT	.067 ± .020	1,7 ± 0.5mm
C	FULL ACTUATION	.098 ± .020	2,5 ± 0.5mm

TAPE & REEL



Dimensions are shown: Inches (mm)
Specifications and dimensions subject to change

www.ck-components.com



A
Pushbutton

ELUM™ Series Right Angle Illuminated Latching Pushbutton

AVAILABLE HARDWARE

Cap



PART NO.

957C00000 High temperature black cap with universal standby symbol

956C02000 High temperature black cap with no symbol

Material: 4/6 Nylon SMT compatible

Cap



PART NO.

181D01000 Paint and Laser Etched with black paint and universal standby symbol

Material: Clear polycarbonate


Cap



PART NO.



181D00000 Paint and laser etched with white paint underlay and black paint with universal standby symbol.

Material: Clear polycarbonate



NOTE: Caps are for use with the C22 actuator style. Other colors and symbols available, consult Customer Service Center.

CAP INSTALLATION



Third Angle
Projection



Dimensions are shown: Inches (mm)
Specifications and dimensions subject to change

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

C&K Components:

<u>ELUMOASAQ3C12</u>	<u>ELUMOASAQ6C12</u>	<u>ELUMOASAQ7C12</u>	<u>ELUMOASAQ9C12</u>	<u>ELUMEESAQ3C12</u>
<u>ELUMEESAQ6C12</u>	<u>ELUMEESAQ9C12</u>	<u>ELUMEESAQ7C12</u>	<u>ELUMEESAQ2C22</u>	<u>ELUMOASAQ8C22</u>
<u>ELUMEETHQ8C22</u>	<u>ELUMEETHQ2C22</u>	<u>ELUMOATHQ2C22</u>	<u>ELUMEESAQ2C12</u>	<u>ELUMEESAQ1C12</u>
<u>ELUMEESAQ1C22</u>	<u>ELUMEESAQ3C22</u>	<u>ELUMEESAQ5C12</u>	<u>ELUMEESAQ6C22</u>	<u>ELUMEESAQ7C22</u>
<u>ELUMEESAQ8C12</u>	<u>ELUMEESAQ8C22</u>	<u>ELUMEETHQ1C12</u>	<u>ELUMEETHQ3C12</u>	<u>ELUMEETHQ5C12</u>
<u>ELUMEETHQ6C12</u>	<u>ELUMEETHQ7C12</u>	<u>ELUMEETHQ7C22</u>	<u>ELUMEETHQ8C12</u>	<u>ELUMOASAQ1C12</u>
<u>ELUMOASAQ1C22</u>	<u>ELUMOASAQ5C12</u>	<u>ELUMOASAQ6C22</u>	<u>ELUMOASAQ7C22</u>	<u>ELUMOASAQ8C12</u>
<u>ELUMOATHQ3C12</u>	<u>ELUMOATHQ6C12</u>	<u>ELUMOATHQ7C12</u>	<u>ELUMEETHQ6C22</u>	<u>ELUMEETHQ2C12</u>
<u>ELUMOATHQ7C22</u>	<u>ELUMOATHQ2C12</u>	<u>ELUMOASAQ2C12</u>	<u>ELUMOATHQ6C22</u>	<u>ELUMOASAQ2C22</u>
<u>ELUMOATHQ8C12</u>	<u>ELUMOATHQ8C22</u>	<u>ELUMOATHQ5C12</u>	<u>ELUMOATHQ1C12</u>	<u>ELUMEETHQ1C22</u>
<u>ELUMOATHQ1C22</u>	<u>ELUMEETHQ3C22</u>			