



TECHNICAL SPECIFICATIONS

Contacts:

Supplied on disposable plastic carrier strips

Current Rating:

5 amperes

Contact Resistance:

0.006 Ohm, maximum

Contact Material and Plating:

Phosphor Bronze

†Gold, 10 microinches minimum, over nickel, 50 to 100 microinches

Insertion/Withdrawal Force:

2 to 16 ounces per contact

†ELCO Standard Plating shown. Other plating may be supplied on request.

ORDERING CODE – BASE CARD CONTACTS

- Guide Pin – 62 5204 41 12 00 062
- Guide Socket – 62 5204 40 12 00 062
- Contacts

02

000

000

3

000

000

Number of Contacts on Strip
1 to 123

Contact Style

Pattern

3 – for In-Line Pattern
9 – for Offset Pattern

Spacing Code

100 – for In-Line Pattern
200 – for Offset Pattern

Variation

000 – for In-Line Pattern
009 – for Offset Pattern
010 – for Offset Pattern

For loose contacts, order by individual part numbers tabulated on page 53.

323		1/16" card
327		3/32" card

ORDERING CODE – MODULE CARD CONTACTS

Upper-tier and Lower-Tier Contacts on Separate Strips

02

000

000

5

000

000

Number of Contacts on Strip
1 – 120 for In-Line Pattern
1 – 60 for Offset Pattern

Contact Style

In-Line:		
332		1/16" card
Offset:		
332		1/16" card, Lower Tier
372		1/16" card Upper Tier

For loose contacts, order by individual part numbers tabulated on page 53.

Spacing Code

100 – for In-Line Pattern
200 – for Offset Pattern

Lower and upper tier contacts of the offset pattern assembly are ordered separately. Order one extra lower tier contact when pattern is to start and end with a lower tier contact (example – 9 lower tier and 8 upper tier).