



NOVACAP RF1111 SERIES CAPACITORS



NOVACAP manufactures a new improved ESR performance RF1111 series capacitors. This series has been designed for rugged environments in high power broadband coupling and switching power supplies. The Class II ceramic dielectric affords high volumetric efficiency with negligible piezoelectric effects. Please contact the factory for higher WVDC, capacitance values not listed, tolerance, or leading options.

CAPACITANCE & VOLTAGE SELECTION

CAP CODE	CAP (pF)	TOL.	RATED WVDC	CAP CODE	CAP (pF)	TOL.	RATED WVDC	CAP CODE	CAP (pF)	TOL.	RATED WVDC
472	4700	K,M	50	153	15,000	K,M	50	473	47,000	K,M	50
562	5600	K,M	50	183	18,000	K,M	50	503	50,000	K,M	50
682	6800	K,M	50	223	22,000	K,M	50	563	56,000	K,M	50
822	8200	K,M	50	273	27,000	K,M	50	683	68,000	K,M	50
103	10,000	K,M	50	333	33,000	K,M	50	823	82,000	K,M	50
123	12,000	K,M	50	393	39,000	K,M	50	104	100,000	K,M	50



DIMENSIONS INCHES (MM)

SIZE	NOMINAL	TOLERANCE
LENGTH L	.110 (2.79)	+0.025-.010 (+0.64-0.25)
WIDTH W	.110 (2.79)	±.015 (0.38)
T MAX	.102 (2.59)	Maximum
MB	.020 (.508)	±.010 (0.25)

RECOMMENDED MOUNTING PADS

SIZE	A Min.	B Min.	C Min.	D Min.
VERT	.120"	.050"	.075"	.175"
HORIZ	.130"	.050"	.075"	.175"

VERT =Vertical Mount,HORIZ =Horizontal Mount




DIELECTRIC CHARACTERISTICS

Operating Temp Range	-55°C to 125°C
Temp Voltage Coefficient	+15/-25% Delta C Max
Dissipation Factor	.025 (2.5%) Max
Insulation Resistance @ 25°C	>1000ΩF
Insulation Resistance @ 125°C	>100ΩF
Dielectric Withstanding Voltage	2.5X WVDC, 5 Seconds
Test Parameters	1KHz, 1.0VRMS, 25°C



NOVACAP RF1111 SERIES CAPACITORS



Note 1: Current rating based a device thermal resistance of 20°C/W and a 65°C mounting surface.
3 Watts of power dissipation will result in a 125°C case temperature.

HOW TO ORDER

RF	1111	X	473	K	500	X102	K	T
SERIES	SIZE	DIELECTRIC	CAPACITANCE	TOLERANCE	VOLTAGE	THICKNESS	TERMINATION	PACKING
	See Chart	X = BX Class II	Value in Picofarads Two significant figures, followed by number of zeros: 473 = 47,000pF	K = +/- 10 % M = +/- 20 %	VDCW Two significant figures, followed by number of zeros: 500 = 50V	.102" (2.59) max thickness	K = Solderable Palladium/Silver (Non-Magnetic) N = Nickel barrier 100% Tin (RoHS) Y = Nickel barrier 90%Tin/10%Lead	OPTION T=Reeled W=Waffle None= Bulk