COLOR DRIVER RFCC SYSTEM

Lumidrives

Dialight



OPERATING CONDITIONS

- ▲ Operating Ambient Temperature -10°C to +55°C
- ▲ Maximum case temperature 85°C
- ▲ Input voltage 110-240 VAC / 50-60 Hz
- Power consumption, 0-27W
- ▲ Power factor =0.95
- ▲ Output current = 350mA at 100%
- Maximum # LEDs = 6 per channel / 18 per driver (master or slave)
- ▲ Dimming control of master by handheld remote
- ▲ Link up to 99 slave drivers per master
- V_{out}: 3-24 VDC

MECHANICAL DIMENSIONS

Master & slave drivers:

179.2mm x 53.3mm x 32.3mm (7.06" x 2.10" x 1.27") 2 Mounting slots for M3 screws

Handheld remote:

96mm x 47mm x 24mm (3.78" x 1.85" x 0.94")

Wall plate:

86mm x 86mm x 24mm (3.39" x 3.39" x 0.94") (Once installed, wall plate depth 12mm above grade)

Dialight reserves the right to make changes at any time in order to supply the best product possible.

FEATURES / BENEFITS

- User friendly handheld remote or control by push button wallplate
- ▲ Add up to 99 slave drivers per master driver
- System allows for control of up to 1800 LEDs with a single remote or wall pack
- ▲ 3 Fully addressable output channels to separately control & drive red, blue & green LED circuits, making infinite combinations of colors possible
- ▲ Digital dimming level from 0-100%
- Short & open circuit protected
- Remote mountable up to 30 meters (95')
- ▲ DMX controllable
- Available Color Kinetics pass through license, contact factory for details.

APPLICATION

- Dynamic RGB color mixing
- Decorative lighting
- Entertainment lighting
- Theme lighting
- Bars & restaraunts
- Appropriate driver for Dialight-Lumidrives Colorengine Circular or HL16 RGB modules

MATERIALS/FINISH

- LED output via MOLEX micro fit 3.0 system (female)
- RJ45 cable to link master to first slave and from first slave to second (and so on)

Dialight Corporation

1501 Route 34 South • Farmingdale, NJ 07727 USA Tel: (1) 732-919-3119 • Fax: (1) 732-751-5778 • www.dialight.com





COLORDRIVER RFCC SYSTEM

PART NUMBERS

Reference Part Number	Dialight Part Number	Description
CDURF-3-35	RFCCMASTER	18 LED Colordriver RF Master
CDUSL-3-35	RFCCSLAVE	18 LED Colordriver RF Slave
CDURF-TX	RFCCREMOTE	Colordriver RF Remote

WIRING INFORMATION



Dialight reserves the right to make changes at any time in order to supply the best product possible.

Dialight Corporation

1501 Route 34 South • Farmingdale, NJ 07727 USA Tel: (1) 732-919-3119 • Fax: (1) 732-751-5778 • www.dialight.com

