


Commercial 12mm Diameter Carbon Composition Rotary Potentiometer

Features

- Miniature 12mm size
- Low cost
- Snap-in bracket for PC board mounting
- Detent available
- Insulated shaft available
- RoHS compliant



Electrical and Mechanical Specifications

Resistance Range

500 ohms through 1 Megohms

Resistance Tolerance

±30%, ±20%, ±10%

Power Rating

0.15 watts @ 50°C

Dielectric Strength

500 VDC for 1 minute

Maximum Operating Voltage

350 VDC

Insulation Resistance

100 Megohms minimum @ 250 VDC

Rotational Angle

Mechanical angle: 300°
Effective angle: 280°

Rotational Torque

20 – 216 gf-cm

Stop Strength

5.76 kg-cm minimum (VR without detent)
3 kg-cm minimum (VR with detent)

Mounting Information

P.C. board mounting
Type "X": Shaft parallel to P.C. board
Type "U": Shaft vertical to P.C. board
Type "H": Same as "X" except hook terminals

Detent

Detent @ 50% rotation

Push-Pull strength on shaft

8 kg for 10 seconds

Rotational life

10K cycles


Operating temperature

-10°C ~ 80°C


Solder Heat Resistance

260°C for 5 seconds

XM 296RE/ HM 296RE Molded Shaft, Shaft Parallel to P.C. Board



UM 296RE Molded Shaft, Shaft Perpendicular to P.C. Board



Ordering Information

296

X

B

TERMINAL STYLE

X – PC
U – PC FORMED TO REAR
H – HOOK

SHAFTS AVAILABLE
(ALL SHAFTS .236" Dia. (6.0mm) except "E" - Diameter is .240" (6.1mm))

COVER	TRIM
A – .640" (16.3mm)	FLATTED .472"X.177" (12X4.5mm)
B – .840" (21.3mm)	FLATTED .472"X.177" (12X4.5mm)
C – 1.031" (26.2mm)	FLATTED .472"X.177" (12X4.5mm)
D – .540" (13.7mm)	KNURLED .287"X.18T (7.3mmX18T)
E – .265" (6.7mm)	FLATTED .218"X.204" (5.5X5.2mm)
F – .640" (16.3mm)	FLATTED .276"X.177" (7X4.5mm)
G – .717" (18.2mm)	FLATTED .276"X.177" (7X4.5mm)
H – 1.035" (26.3mm)	FLATTED .276"X.177" (7X4.5mm)

252

B

2

N

RESISTANCE CODE EXAMPLES

CODE	RESISTANCE
501	500 OHMS
102	1K
252	2.5K
502	5K
103	10K
253	25K
503	50K
104	100K

RESIST TOL
A – $\pm 10\%$
B – $\pm 20\%$
C – $\pm 30\%$

DETENT
N – NO DETENT
C – CENTER DETENT

TAPER
1 – LINEAR
2 – 10% AUD
3 – 10% CCW AUD

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

CTS:

[296UD102B1N](#) [296UD103B1N](#) [296UD104B1N](#) [296UD105B1N](#) [296UD252B1N](#) [296UD253B1N](#) [296UD254B1N](#)
[296UD501B1N](#) [296UD502B1N](#) [296UD503B1N](#) [296UD504B1N](#) [296XD102B1N](#) [296XD103B1N](#) [296XD104B1N](#)
[296XD105B1N](#) [296XD252B1N](#) [296XD253B1N](#) [296XD254B1N](#) [296XD501B1N](#) [296XD502B1N](#) [296XD503B1N](#)
[296XD504B1N](#)