

## Datasheet

RS Stock No. 1242596

**RS Pro Compact Internal Fitting Vertical Float Switch**

The RSF150 series are compact vertically mounted devices with a single switch point. Mounting is either from the top or bottom of a tank from the inside, so requires access to the inside of the tank.

These have M12 circular connectors for electrical connection.  
Cables are available for use with M12 connectors.

Typical applications include vending machines, printing systems and chemical dosing equipment.

These can be manufactured in a variety of plastics, with a choice of gasket materials, to suit most commonly used liquids.

The switch action may be reversed by removing the float, inverting it, then refitting to the stem.

**MPN:** RSF157YGP

**Material:** Polyvinylidene Flouride (PVDF)

**Max Power:** 25 VA

**Connection:** M12 Circular

**Gasket:** Viton

**Approvals:** UL (Pending)

**Technical Specification**

**Material:** Polyvinylidene Flouride (PVDF)

**Colour:** Green

**Temp Range °C:** -10 to +105

**Min Fluid SG:** 0.85

**Must Close Level (SG=1):** 9.5 mm

**Must Open Level (SG=1):** 20.5 mm

**Electrical Specification**

**Contact Form:** N/O (N/C)

**Switching Power Max:** 25 VA

**Switching Voltage AC Max:** 240 V

**Switching Voltage DC Max:** 120 V

**Switching Current Max:** 0.6 A

**Note: All ratings are for RESISTIVE LOADS ONLY**

### ***Mechanical Dimensions***

All dimensions are in millimeters (inches)

