HellermannTyton

Article Number: 115-00038

Description: Releasable Cable Tie, 32.3" Long, 175 lb Tensile Strength,

PA66, Black, 25/pkg

Base Data Local Order Number RT150LEP0X2 RT150LEP Type Color Black (BK) Features and Benefits · Special design offers a release feature for quick and easy access to wire bundles. · Head design provides high tensile strength with very low insertion force even after repeated use. Quantity Per bag **Product Description** HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force . For high volume applications, tensioning tools are available to ensure consistent and safe installation. Short Description Releasable Cable Tie, 32.3" Long, 175 lb Tensile Strength, PA66, Black, 25/pkg Product Dimensions Minimum Tensile Strength (Imperial) 175.0lbs 780.0N Minimum Tensile Strength (Metric) 32.3" Length L (Imperial) Length L (Metric) 820.0mm **Fixation Method** None Identification Plate Position none **Releasable Closure** Yes Tie Closure plastic pawl Variant Inside Serrated Width W (Imperial) 0.35" Width W (Metric) 8.8mm Cable Tie Width Max. (Imperial) 0.346" Cable Tie Width Max. (Metric) 8.8mm Bundle Diameter Min. (Imperial) 0.32"

115-00038

HellermannTyton

| Product Dimensions | Bundle Diameter Min. (Metric) | 8.0mm |
|-----------------------------|---------------------------------|----------------------|
| | Bundle Diameter Max. (Imperial) | 9.6" |
| | Bundle Diameter Max. (Metric) | 245.0mm |
| Material and Specifications | | |
| | Material | Polyamide 6.6 (PA66) |
| | Material Shortcut | PA66 |
| | Flammability | UL 94 V2 |
| | Minimum Application Temperature | - |
| | ROHS Compliant | Yes |
| Logistic and Packaging | | |
| | Package Quantity (Metric) | 25 |
| | Customs Number(Schedule B) | 3926909987 |
| | | |