

115-41503

HellermannTyton



Article Number: 115-41503

Description: Releasable Cable Tie, Release Tab, 34.7" Long, 250lb Tensile Strength, PA66UV, Black, 25/pkg

| | | |
|--------------------|-------------------------------------|---|
| Base Data | | |
| | Local Order Number | RT250L0UVX2 |
| | Type | RT250L |
| | Color | Black (BK) |
| | Features and benefits | <ul style="list-style-type: none"> • UV stabilized heavy duty cable ties contain an inhibitor which prolongs the life of the tie in UV exposures. • Special design offers a release feature for quick and easy access to wire bundles. • Head design provides high tensile strength with very low insertion force even after repeated use. • Buckle feature on head allows excess strap to be tucked away after installation. |
| | Quantity Per | bag |
| | Brand Family | RT250-Series |
| | Product Description | HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation. |
| | GLOBAL PART NAME | RT250L-PA66UV-BK |
| | Short Description | Releasable Cable Tie, Release Tab, 34.7" Long, 250lb Tensile Strength, PA66UV, Black, 25/pkg |
| Product Dimensions | | |
| | Minimum Tensile Strength (Imperial) | 250.0lbs |
| | Minimum Tensile Strength (Metric) | 1115.0N |
| | Length L (Imperial) | 34.7" |
| | Length L (Metric) | 881.38mm |
| | Fixation Method | None |
| | Identification Plate Position | none |
| | Releasable Closure | Yes |
| | Tie Closure | plastic pawl |
| | Variant | Inside Serrated |
| | Width W (Imperial) | 0.49" |

115-41503



| | | |
|-----------------------------|----------------------------------|-------------------------------------|
| Product Dimensions | Width W (Metric) | 12.5mm |
| | Bundle Diameter Min. (Imperial) | 0.47" |
| | Bundle Diameter Min. (Metric) | 12.0mm |
| | Bundle Diameter Max. (Imperial) | 10.0" |
| | Bundle Diameter Max. (Metric) | 254.0mm |
| | Thickness T (Imperial) | 0.0837" |
| | Cable Tie Head Length (Imperial) | 0.88" |
| | Cable Tie Head Width (Imperial) | 0.79" |
| | Thickness T (Metric) | 2.2mm |
| Material and Specifications | | |
| | Material | Polyamide 6.6 UV-resistant (PA66UV) |
| | Material Shortcut | PA66UV |
| | Flammability | UL 94 HB |
| | Operating Temperature | -40°F to +185°F (-40°C to +85°C) |
| | ROHS Compliant | Yes |
| Logistic and Packaging | | |
| | Package Quantity (Imperial) | 25 |
| | Package Quantity (Metric) | 25Pieces |
| | Customs Number(Schedule B) | 3926909987 |