

115-41303

# HellermannTyton



Article Number: 115-41303

Description: Releasable Cable Tie, Release Tab, 20.3" Long, 250lb Tensile Strength, PA66UV, Black, 25/pkg

Base Data		
	Local Order Number	RT250R0UVX2
	Type	RT250R
	Color	Black (BK)
	Features and benefits	<ul style="list-style-type: none"> <li>• UV stabilized heavy duty cable ties contain an inhibitor which prolongs the life of the tie in UV exposures.</li> <li>• Special design offers a release feature for quick and easy access to wire bundles.</li> <li>• Head design provides high tensile strength with very low insertion force even after repeated use.</li> <li>• Buckle feature on head allows excess strap to be tucked away after installation.</li> </ul>
	Quantity Per	bag
	Brand Family	RT250-Series
	Product Description	HellermannTyton releasable cable ties offer a release feature in the head allowing for easy access to wire bundles when changes are necessary. The head design guarantees high tensile strength even after repeated use, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
	GLOBAL PART NAME	RT250R-PA66UV-BK
	Short Description	Releasable Cable Tie, Release Tab, 20.3" Long, 250lb Tensile Strength, PA66UV, Black, 25/pkg
Product Dimensions		
	Minimum Tensile Strength (Imperial)	250.0lbs
	Minimum Tensile Strength (Metric)	1115.0N
	Length L (Imperial)	20.3"
	Length L (Metric)	515.0mm
	Fixation Method	None
	Identification Plate Position	none
	Releasable Closure	Yes
	Tie Closure	plastic pawl
	Variant	Inside Serrated
	Width W (Imperial)	0.49"

115-41303

# HellermannTyton

Product Dimensions	Width W (Metric)	12.5mm
	Bundle Diameter Min. (Imperial)	0.47"
	Bundle Diameter Min. (Metric)	12.0mm
	Bundle Diameter Max. (Imperial)	4.9"
	Bundle Diameter Max. (Metric)	125.0mm
	Thickness T (Imperial)	0.075"
	Cable Tie Head Length (Imperial)	0.88"
	Cable Tie Head Width (Imperial)	0.79"
	Thickness T (Metric)	1.9mm
Material and Specifications		
	Material	Polyamide 6.6 UV-resistant (PA66UV)
	Material Shortcut	PA66UV
	Flammability	UL 94 V2
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	25
	Package Quantity (Metric)	25
	Customs Number(Schedule B)	3926909987
	Weight (Metric)	12.2kg