

WPC A11 Wireless Charging Module



FEATURES Rohs

- Designed to meet WPC Qi Standard, power transmitter design A11 compliant
- Operating temperature -40° C to $+125^{\circ}$ C
- Assembled with ferrite plate which is built with WPC listed ferrite material, high Q for maximum power transmission

APPLICATIONS

- Wireless charger for general electronic device or aftermarket accessories
- Wireless charger for office, residential or public area application
- Wireless charger for power tools or any other devices that need contactless power
- Wireless charging embedded solution for automobile central console, arm rest...etc

ELECTRICAL SPECIFICATIONS

| PART NUMBER | INDUCTANCE (μH ± 10%) | | | DCR Max | Q @ 100 KHz/1V |
|------------------|--------------------------|------|------|---------|-------------------|
| | MIN | NOM | MAX | (msz) | (MIN) |
| RWC5050AK060-500 | 5.85 | 6.50 | 7.15 | 50 | 70 |

Inductance tested at 100KHz,1V 1. Operating temperature range: -40°C ~ +125°C (Including self-heating)

2. Storage temperature range (packaging conditions): -10°C ~ +40°C and RH 70%(MAX) З.

SHAPES AND DIMENSIONS

| Unit:mm | | |
|---------------------|---------------------|---------------------|
| А | В | С |
| 50.00 <u>+</u> 0.50 | 44.00 <u>+</u> 1.50 | 20.50 <u>+</u> 0.50 |
| | | |
| D | E | F |
| 17.00 Min. | 10.00 Ref. | 5.00±2.00 |
| | | |
| G | Н | J |
| 1.00 <u>+</u> 0.10 | 3.00 Max. | 1.20 Ref. |



PART NUMBER SYSTEM EXAMPLE

| <u>RWC</u> | <u>5050</u> | AK | <u>060</u> - | <u>500</u> |
|------------|----------------|-------------|-----------------|-------------------------------|
| Coil Type | Part Size Code | Height Code | Inductance Code | Catalog or Custom Information |

USA: +1.423.308.1690 Europe: +42.0.4885.7511.1 Asia: +86.757.2563.8860

MCP-DS-WPC A11 REV1.0 1213

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user. Laird Technologies makes no warranties as to the fitness, merchantability, suitability or non- infringement of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies' Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2013 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trademarks or registered trademarks of Laird Technologies, the campany thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights. Version A01

www.lairdtech.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Laird Technologies: RWC5050AK060-500