




# CM Series Single Pole Power Rocker Switches

## SWITCH FUNCTION




NO. POLES	MODEL NO.	SWITCH FUNCTION			CONNECTED TERMINALS			SCHEMATIC	
		Pos. 1	Pos. 2	Pos. 3	Pos. 1	Pos. 2	Pos. 3		
		C&K marking on opposite side			C&K marking on opposite side				
SP	<b>CM101</b>	ON	NONE	ON	2-1	N/A	2-1		
	<b>CM102</b>	ON	NONE	OFF			OPEN		OR 
	<b>CM103</b>	ON	OFF	ON			OPEN	2-3	
	<b>CM107</b>	ON	OFF	MOM.					
	<b>CM12 *</b>	ON	NONE	OFF					N/A

\* CM12 - for switches with both marking and illumination




Shown in Pos. 1

## ACTUATOR




**J1** ROCKER

**J3** ILLUMINATED ROCKER



NOTE: J3 actuator available with CM102 & CM12 switch function only.



Third Angle  
Projection

Dimensions are shown: Inches (mm)  
Specifications and dimensions subject to change

**C&K**



# CM Series Single Pole Power Rocker Switches

## ACTUATOR COLOR



OPTION CODE	ACTUATOR COLOR
2	BLACK
1	WHITE
3	RED
R	RED, ILLUMINATED
A	AMBER, ILLUMINATED
G	GREEN, ILLUMINATED

## MOUNTING STYLE/COLOR




**S2** SNAP-IN, BLACK



**S1** SNAP-IN, WHITE

**S4** SNAP-IN, BLACK (SHORT FRAME)


**S3** SNAP-IN, WHITE




Shown in Pos. 1



Shown in Pos. 1




### PANEL MOUNTING



PANEL THICKNESS	"X"	"Y"
0.030-0.049 (0,75-1,25)	1.189-.004 (30,2-0,1)	0.441+.004 (11,2+0,1)
0.049-0.079 (1,25-2,0)	1.197-.004 (30,4-0,1)	0.441+.004 (11,2+0,1)
0.079-0.118 (2,0-3,0)	1.212-.004 (30,8-0,1)	0.441+.004 (11,2+0,1)


## TERMINATION





**05** .250 QUICK CONNECT

**07** SOLDER LUG


Rocker



Shown in Pos. 1



NOTE: Available with CM101 & CM102 switch functions only.



Third Angle Projection

Dimensions are shown: Inches (mm)  
Specifications and dimensions subject to change


[www.ck-components.com](http://www.ck-components.com)

# CM Series Single Pole Power Rocker Switches


## ACTUATOR MARKING




**NONE** NO MARKING





**D** ON-OFF



**H** 0 I



**P** 0 -



**NOTE:** Orientation of actuator marking and terminals.

Shown in Pos. 1

## CONTACT MATERIAL



OPTION CODE	CONTACT AND TERMINAL MATERIAL	RATINGS	
<b>QA</b>	SILVER	POWER	16 AMPS @ 125 VAC; 1/8 HP 10 AMPS @ 250 VAC, 1/3 HP (UL/CSA).

\* Note: See Technical Data section of this catalog for RoHS compliant and compatible definitions and specifications.

## LAMP RATING




**(NONE)** NO LAMP

**7** 125 VAC 33kΩ NEON

**8** 250 VAC 150kΩ NEON

**NOTE:** Lamp rating for J3 & J8 actuator option.



Third Angle  
Projection

Dimensions are shown: Inches (mm)  
Specifications and dimensions subject to change

[www.ck-components.com](http://www.ck-components.com)

