

GENERAL SPECIFICATIONS

Electrical Capacity

Resistive Load: 15A & ½ HP @ 125 or 250V AC for high capacity models
Lamp Load: 5A @ 125V AC

Other Ratings

Contact Resistance: 15 milliohms maximum
Insulation Resistance: 100 megohms minimum @ 500V DC
Dielectric Strength: 1,000V AC minimum between contacts for 1 minute minimum;
1,500V AC minimum between contacts & case for 1 minute minimum
Mechanical Life: 1,000,000 operations minimum
Electrical Life: 50,000 operations minimum
Travel: Pretravel .047" (1.19mm); Overtravel .040" (1.01mm); Differential .011" (0.27mm)
Operating Temp Range: -40°C through +85°C (-40°F through +185°F)

Materials & Finishes

Caps & Shrouds: Polycarbonate with glossy finish or PBT
Plunger: Polyacetal or brass with nickel plating
Bushing: Steel with zinc plating or glass fiber reinforced polyamide
Case: Polyester
Movable & Stationary Contacts: Silver alloy
Terminals: Brass with silver plating

Standards & Certifications

UL: Internal snap switch is UL recognized.
CSA: Internal snap switch is CSA certified.

TYPICAL SWITCH ORDERING EXAMPLE

SCB

2

5

P

15

A

—

4

CA

Poles

1	SPDT
2	DPDT

Circuits

5	ON	(ON)
6	ON	ON

() = Momentary

Bushings

P	Plastic (with momentary only)
S	Steel

Rating

15	15A
----	-----

Terminals

A	.187" (4.75mm) Quick Connect
* B	.250" (6.35mm) Quick Connect

Note: Contact factory for availability of screw lug and solder lug models.

* Available in Americas only

Caps & Shrouds

For Momentary

3	.520" (13.2mm) Diameter Cap
---	-----------------------------

For Momentary & Alternate Action

4	Round Cap & Shroud (AT454 & AT455)
5	Rectangular Cap & Shroud (AT452 & AT453)

Colors

Caps		Shrouds
A	Black	A
B	White	B
C	Red	—
F	Green	—
G	Blue	—
H	Gray	H

DESCRIPTION FOR TYPICAL ORDERING EXAMPLE

SCB25P15A-4CA

DPDT ON-(ON) Circuit

15A Rating

Round Red Cap with Black Shroud


Plastic Bushing

.187" (4.75mm) Quick Connect Terminals

Note: Standard hardware is provided with caps. See Bushing detail for more information.


Toggles
Rockers
Pushbuttons
Illuminated PB
Programmable
Keylocks
Rotaries
Slides
Tactiles
Tilt
Touch
Indicators
Accessories
Supplement

POLES & CIRCUITS


		Plunger Position () = Momentary		Connected Terminals		Throw & Schematics
Pole	Model	Normal 	Down 	Normal 	Down 	Note: Terminal numbers are actually on the switch.
SP	SCB15 SCB16	ON ON	(ON) ON	1-2	1-3	SPDT 
DP	SCB25 SCB26	ON ON	(ON) ON	1-2 1-2	1-3 1-3	SP with 2 switches 

BUSHINGS


P Plastic
(for Momentary only)




S Steel



"A" =
11.2mm
Momentary
15.5mm
Alternate Action



Maximum Effective Panel Thickness:
.165" (4.2mm) without Shroud
.157" (4.0mm) with Shroud



Maximum Effective Panel Thickness:
Momentary: .177" (4.5mm) without Shroud
.157" (4.0mm) with Shroud
Alternate Action: .354" (9.0mm)


Standard Hardware Provided with Caps

Cap Option 3: AT504M Knurled Face Nut, AT508 Lockwasher, AT527M Hex Mounting Nut


Cap Options 4 & 5: AT508 Lockwasher & AT527M Hex Mounting Nut

TERMINALS

A .187" (4.75mm)
Quick Connect




B .250" (6.35mm)
Quick Connect




TYPICAL SWITCH DIMENSIONS

.520" (13.2mm) Dia. Cap • .187" (4.75mm) Quick Connect




SCB15S15A-3C

Round Cap & Shroud • .187" (4.75mm) Quick Connect



SCB25P15A-4CA

Rectangular Cap & Shroud • .250" (6.35mm) Quick Connect



SCB26S15B-5CA

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

NKK Switches:

[SCB15P15B-3G](#) [SCB15P15B-3H](#) [SCB15P15B-3F](#) [SCB15P15B-3C](#) [SCB15P15B-2H](#) [SCB15P15B-2F](#) [SCB15P15B-2G](#) [SCB15P15B-2B](#) [SCB15P15B-2A](#) [SCB25P15A-1C](#) [SCB25P15A-1H](#) [SCB25P15A-1F](#) [SCB25P15A-3F](#) [SCB25P15A-3G](#) [SCB25P15A-1G](#) [SCB25P15A-1B](#) [SCB25P15A-3B](#) [SCB25P15A-3H](#) [SCB25P15A-1A](#) [SCB25P15A-2A](#) [SCB25P15A-3C](#) [SCB15P15A-2F](#) [SCB15P15A-2H](#) [SCB15P15A-2B](#) [SCB15P15A-2G](#) [SCB15P15A-2C](#) [SCB25P15A-2F](#) [SCB25P15A-2H](#) [SCB25P15A-2B](#) [SCB25P15A-2C](#) [SCB25P15A-2G](#) [SCB25P15B-1F](#) [SCB25P15B-1G](#) [SCB25P15B-1A](#) [SCB25P15B-1H](#) [SCB25P15B-1C](#) [SCB25P15B-1B](#) [SCB25S15B-5AH](#) [SCB25P15B-3F](#) [SCB25P15B-2B](#) [SCB25P15B-3G](#) [SCB25P15B-2H](#) [SCB25P15B-3H](#) [SCB25P15B-2G](#) [SCB25P15B-2F](#) [SCB25P15B-3A](#) [SCB25P15B-2A](#) [SCB25P15B-3B](#) [SCB15P15B-1G](#) [SCB15P15B-1F](#) [SCB15P15B-1C](#) [SCB15P15B-1B](#) [SCB15P15B-1H](#) [SCB15P15B-1A](#) [SCB15P15A-3H](#) [SCB15P15A-3F](#) [SCB15P15A-1H](#) [SCB15P15A-1B](#) [SCB15P15A-3G](#) [SCB15P15A-1C](#) [SCB15P15A-1G](#) [SCB15P15A-1F](#) [SCB15P15A-3B](#) [SCB26S15A-4AA](#) [SCB15P10A-1C](#) [SCB15P10B-3A](#) [SCB15S10A-2A](#) [SCB15S15A-4AA](#) [SCB15S15A-4CA](#) [SCB15S15D-4CA](#) [SCB25P15A-4CA](#) [SCB25S15B-1A](#) [SCB26S15B-4AA](#) [SCB16S15B-5BH](#) [SCB26S15B-4GA](#) [SCB15P15A-4CA](#) [SCB15P15B-5CA](#) [SCB15S15B-1A](#) [SCB15S15B-4AA-RO](#) [SCB15P15A-5CA](#) [SCB15S15B-2A](#) [SCB25S15B-4CA](#) [SCB25S15C-3A](#) [SCB15P15B-4GA](#) [SCB15S15A-2B](#) [SCB15S15B-3G](#) [SCB16S15B-4FH](#) [SCB25P15A-4FA](#) [SCB25S15A-4CA](#) [SCB25S15B-2H](#) [SCB26S15A-4CA](#) [SCB26S15A-4FA](#) [SCB25P10B](#) [SCB15S15A-4FA](#) [SCB16S15B-5GA](#) [SCB15P15A-4FH](#) [SCB26S15C-4AA](#) [SCB15P10D-3A](#) [SCB15P10A-4BB](#) [SCB25S10C-4AA](#)