




## Code Conductor, Long Barrel, Butt Splice

For Use with Stranded Copper Conductors

### Type SCL

- Long barrel maximizes the number of crimps and provides premium wire pull-out strength and electrical performance
- Color-coded barrels marked with Panduit and specified competitor die index numbers for proper crimp die selection
- Internal wire stops to prevent over-insertion of conductor
- Tin-plated to inhibit corrosion

- UL Listed and CSA Certified to 35 KV\*\* and temperature rated to 90°C when crimped with Panduit and specified competitor crimping tools and dies
- UL Listed and CSA Certified for wide wire range-taking capability when crimped with Panduit® Uni-Die™ Dieless Crimping Tools‡
- Tested by Telcordia – meets NEBS Level 3



| Part Number | Copper Conductor Size       | Figure Dimensions (In.) |      | Panduit Color Code | Panduit Die Index No.‡ | Burndy Die Index No.‡ | T&B Die Index No.‡ | Wire Strip Length (In.) | Std. Pkg. Qty. |
|-------------|-----------------------------|-------------------------|------|--------------------|------------------------|-----------------------|--------------------|-------------------------|----------------|
|             |                             | Barrel O.D.             | L    |                    |                        |                       |                    |                         |                |
| SCL8-L      | #8 AWG                      | 0.27                    | 2.25 | Red                | P21                    | 49                    | 21                 | 1 1/16                  | 50             |
| SCL6-L      | #6 AWG                      | 0.31                    | 2.38 | Blue               | P24                    | 7                     | 24                 | 1 1/8                   | 50             |
| SCL4-L      | #4 – #3 AWG STR, #2 AWG SOL | 0.38                    | 2.38 | Gray               | P29                    | 8                     | 29                 | 1 1/8                   | 50             |
| SCL2-Q      | #2 AWG                      | 0.42                    | 2.62 | Brown              | P33                    | 10                    | 33                 | 1 1/4                   | 25             |
| SCL1-E      | #1 AWG                      | 0.47                    | 2.87 | Green              | P37                    | 11                    | 37                 | 1 3/8                   | 20             |
| SCL1/0-X    | 1/0 AWG                     | 0.52                    | 2.87 | Pink               | P42                    | 12                    | 42                 | 1 3/8                   | 10             |
| SCL2/0-X    | 2/0 AWG                     | 0.58                    | 3.13 | Black              | P45                    | 13                    | 45                 | 1 1/2                   | 10             |
| SCL3/0-X    | 3/0 AWG                     | 0.64                    | 3.12 | Orange             | P50                    | 14                    | 54                 | 1 1/2                   | 10             |
| SCL4/0-X    | 4/0 AWG                     | 0.71                    | 3.37 | Purple             | P54                    | 15                    | 54                 | 1 5/8                   | 10             |
| SCL250-X    | 250 kcmil                   | 0.77                    | 3.38 | Yellow             | P62                    | 16                    | 62                 | 1 5/8                   | 10             |
| SCL300-X    | 300 kcmil                   | 0.81                    | 4.12 | White              | P66                    | 17                    | 66                 | 2                       | 10             |
| SCL350-X    | 350 kcmil                   | 0.88                    | 4.12 | Red                | P71                    | 18                    | 71                 | 2                       | 10             |
| SCL400-6    | 400 kcmil                   | 0.95                    | 4.37 | Blue               | P76                    | 19                    | 76                 | 2 1/8                   | 6              |
| SCL500-6    | 500 kcmil                   | 1.06                    | 4.62 | Brown              | P87                    | 20                    | 87                 | 2 1/4                   | 6              |
| SCL600-6    | 600 kcmil                   | 1.19                    | 5.50 | Green              | P94                    | 22                    | 94                 | 2 11/16                 | 6              |
| SCL750-6    | 750 kcmil                   | 1.30                    | 5.87 | Black              | P106                   | 24                    | 106                | 2 7/8                   | 6              |
| SCL1000-3   | 1000 kcmil                  | 1.50                    | 6.12 | White              | P125                   | 27                    | 125                | 3                       | 3              |

‡See pages D3.62 – D3.65 for tool and die information.

\*\*Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 V.

A.  
System  
Overview

B1.  
Cable Ties

B2.  
Cable  
Accessories

B3.  
Stainless  
Steel Ties

C1.  
Wiring  
Duct

C2.  
Surface  
Raceway

C3.  
Abrasion  
Protection

C4.  
Cable  
Management

D1.  
Terminals

D2.  
Power  
Connectors

D3.  
Grounding  
Connectors

E1.  
Labeling  
Systems

E2.  
Labels

E3.  
Pre-Printed  
& Write-On  
Markers

E4.  
Permanent  
Identification

E5.  
Lockout/  
Tagout  
& Safety  
Solutions

F.  
Index

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

[SCL1/0-X](#) [SCL2-Q](#) [SCL3/0-X](#) [SCL4-L](#) [SCL4/0-X](#) [SCL400-6](#) [SCL6-L](#) [SCL250-X](#)