

(0.80 mm) .0315"

SEM, SEMS, SEML SERIES

MICRO TIGER EYE™ SOCKET

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?SEM, www.samtec.com?SEMS or www.samtec.com?SEML

Insulator Material: Black Liquid Crystal Polymer
Contact Material: BeCu
Plating: Au or Sn over 50 μm (1.27 μm) Ni
Operating Temp Range: -55 °C to +125 °C
Current Rating (SEM/TEM): 2.6 A per pin (1 pin powered per row)
RoHS Compliant: Yes

PROCESSING

Lead-Free Solderable: Yes
SMT Lead Coplanarity: (0.10 mm) .004" max

RECOGNITIONS


For complete scope of recognitions see www.samtec.com/quality



OTHER SOLUTIONS

- Board Stacking: See SFM, TFM Series
 - Cable Assemblies: See SFSD, TFSD Series
- Contact Samtec.

MATED HEIGHT



TEM LEAD STYLE	MATED HEIGHT*
-03.0	6 mm
-04.0	7 mm
-07.0	10 mm

*Processing conditions will affect mated height.

Note: Some sizes, styles and options are non-standard, non-returnable.

SEM, SEML Mates with: TEM

SEMS Mates with: TEMS



ALSO AVAILABLE (MOQ Required)

- Other sizes
 - Other platings
- Contact Samtec.

High-reliability Tiger Eye™ contacts

Choice of mated heights

Weld tab

RUGGEDIZED BY SAMTEC

- Passes 10 year MFG
- Locking clip option
- Weld tab option

TYPE STRIP	1	NO. PINS PER ROW	02	STACK HEIGHT	PLATING OPTION	D	OPTION	OTHER OPTION
------------	---	------------------	----	--------------	----------------	---	--------	--------------

<p>SEM = Tiger Eye™ Strip</p> <p>SEMS = Tiger Eye™ Slim Strip</p> <p>SEML = Tiger Eye™ Friction Lock</p>	<p>05, 10, 15, 20, 25</p> <p>30, 35, 40, 45, 50 (SEM/SEML only) (Standard sizes)</p>	<p>-03.0 = 6 mm, 7 mm or 10 mm Stack Height when mated with TEM/TEMS Series (SEML only available with 6 mm Stack Height)</p>	<p>-FG = Gold Flash</p> <p>-G = 10 μm (0.25 μm) Gold on contact, Gold Flash on tail</p> <p>-H = 30 μm (0.76 μm) Gold on contact, Gold Flash on tail</p>	<p>Leave blank for SEMS</p> <p>-A = Alignment Pin (Not available with -LC or -WT)</p> <p>-LC = Locking Clip (Not available with -A or -WT) (Manual placement required)</p> <p>-WT = Weld Tab (Not available with -A or -LC) (Required callout for SEML)</p>	<p>-K = (3.50 mm) .138" DIA Polyimide film Pick & Place Pad (Required for SEMS)</p> <p>-TR = Tape & Reel (Required for SEMS)</p>
---	--	--	---	---	--

