
ROHS COMPLIANT

PRODUCT DATA DRAWING

REVISION HISTORY			
REV	DESCRIPTION	DATE	APPROVED
В	DCN 41836	11/15	STW



(.826[20.98])

SHRINK TUBING

MATERIAL:

BODY &

COUPLING NUT: STAINLESS STEEL PER AMS-5640,

ALLOY UNS S30300, TYPE 1

CONTACT: BRASS PER ASTM B16, ALLOY UNS No. C36000

CRIMP RING: COPPER OR BRASS

LOCK RING: BERYLLIUM COPPER PER ASTM B196,

ALLOY No. UNS C17300, TD04

INSULATOR: PTFE PER ASTM D1710, TYPE I, GRADE 1, CLASS B

GASKET: SILICONE RUBBER PER A-A-59588,

CLASS 2B, GRADE 50/60

SHRINK TUBING: SCL POLYOLEFIN PER MIL-I-23053/4,

CLASS 1

FINISH:

BODY &

COUPLING NUT: PASSIVATED PER AMS-2700, TYPE 2

CRIMP RING: NICKEL PER QQ-N-290, CLASS 2

CONTACT: GOLD PER ASTM B488, TYPE II,

CODE C, CLASS .76, OVER NICKEL

PER AMS-QQ-N-290, CLASS 1, .00005" MIN.

PERFORMANCE:

IMPEDANCE: 50 OHMS

FREQ. RANGE: DC TO 12.4 GHz

MATERIAL: SEE NOTES

FINISH: SEE NOTES

SURFACE AREA: N/A

PROPRIETARY

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SV MICROWAVE, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SV MICROWAVE, INC IS PROHIBITED.

DIMENSIONS ARE IN INCHES TOLERANCES:

FRACTIONAL: ±1/64 ANGULAR: X° ±10°0'
X°X' ±15'

DECIMAL: X ±.030
.XX ±.010
.XXX ±.010
.XXX ±.005

INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M - 1994

THIRD ANGLE PROJECTION

UNLESS OTHERWISE SPECIFIED

1) ALL DIMENSIONS ARE IN INCHES [MILLIMETERS]
2) ALL DIMENSIONS ARE AFTER PLATING.
3) BREAK CORNERS & EDGES. 005 R. MAX.
4) CHAM. 1ST & LAST THREADS.
5) SURFACE ROUGHNES 63* MIL-STD-10.
6) DIA'S ON COMMON CENTERS TO BE CONCENTRIC WITHIN 005 T.I.R.
7) REMOVE ALL BURRS

APPROVED:

DRAWN: BRT 04/08/97

CHECKED: RG 55, 17

DGG 04/03/78

Amphenol MICROWAVE 2400 Centrepark West Drive, Suite 100 West Palm Beach, FL 33409

SMA CRIMP PLUG FOR RG 55, 142, 223, 400/U CABLES

SIZE CAGE CODE DWG. NO. SF2900-6001

SCALE: 6:1 SHEET 1 0

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol: SF2900-6001