

date 12/15/2011

page 1 of 3

SERIES: SJ1-4251 **DESCRIPTION:** 2.5 MM AUDIO JACKS


FEATURES

- low profile design
- switch options include:
- no switch
- tip switch
- ring switch
- tip and ring switch





PART NUMBER KEY



SPECIFICATIONS

| OI EOII IOAI IOIIO | | | | | |
|---------------------------|---|-----|-------|----------|-----------|
| parameter | conditions/description | min | typ | max | units |
| rated input voltage | | | 12 | | Vdc |
| rated input current | | | | 1 | А |
| contact resistance | between terminal and mating plug between terminal in a closed circuit* | | | 50 30 | $m\Omega$ |
| insulation resistance | at 500 Vdc | 100 | | | ΜΩ |
| voltage withstand | at 50/60Hz for 1 minute | | | 500 | Vac |
| insertion/withdrawl force | | 0.3 | | 3 | kg |
| terminal strength | any direction for 10 seconds | | | 500 | g |
| operating temperature | | -25 | | 85 | °C |
| life | | | 5,000 | | cycles |

SOLDERABILITY

*When measured at a current of less than 100 mA / 1 kHz


Notes:

| parameter | conditions/description | min | typ | max | units |
|----------------|---|-----|-----|-----|-------|
| wave soldering | dipped in solder pot for 5±0.5 seconds at | 255 | 260 | 265 | °C |


MECHANICAL DRAWING





TOLERANCE: $X.X \pm 0.2mm$ $X.XX \pm 0.1mm$ $X.XXX \pm 0.05mm$





| | MATERIAL | PLATING |
|------------|--------------|------------|
| terminal 1 | copper alloy | gold flash |
| terminal 2 | copper alloy | gold flash |
| terminal 3 | copper alloy | gold flash |
| terminal 4 | copper alloy | gold flash |
| terminal 5 | brass | gold flash |
| terminal 6 | brass | gold flash |
| plastic | PA66 | |
| | | |











| Model No. | SJ1-42514 | SJ1-42515TS | SJ1-42515RS | SJ1-42516 |
|-----------|----------------|---------------------------------|----------------------|----------------------------------|
| Schematic | 01 04 03 | 0 1 0 4 0 3 0 5 0 5 | 01 04 03 06 | 01 04 03 06 05 05 |
| PIN | | | | |
| 1 | sleeve | sleeve | sleeve | sleeve |
| 2 | tip | tip | tip | tip |
| 3 | ring 1 | ring 1 | ring 1 | ring 1 |
| 4 | ring 2 | ring 2 | ring 2 | ring 2 |
| 5 | NP | tip switch | NP | tip switch |
| 6 | NP | NP | ring switch | ring switch |

CUI Inc | SERIES: SJ1-4251 | DESCRIPTION: 2.5 MM AUDIO JACKS | date 12/15/2011 | page 3 of 3

REVISION HISTORY

| rev. | description | date |
|------|----------------------|------------|
| 1.0 | initial release | 10/27/2005 |
| 1.01 | new template applied | 12/15/2011 |

The revision history provided is for informational purposes only and is believed to be accurate.



Headquarters 20050 SW 112th Ave. Tualatin, OR 97062 800.275.4899

Fax 503.612.2383 cui.com techsupport@cui.com

CUI offers a one (1) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

CUI Inc.:

SJ1-42514 SJ1-42515TS