


## Twin Thermostats **SKTD Series**



## **Features**

- Designed to provide air temperature control and monitoring in cabinets
- Twin thermostats integrates two independently switchable thermostats, unlike thermostats with changeover contacts, connected devices can be switched in different temperature ranges.
- Available with N.C/N.O., N.C/N.C., N.O/N.O.





	Part Number					
Scale: ( Fahrenheit)						
Scale: (Celsius)	SKTD541C	SKTD542C	SKTD543C			
Type of contact:	N.C. / N.O. with spring contact	N.C. / N.C. with spring contact	N.O. / N.O. with spring contact			
Suitable for the operation of	Fan and Heater	Heaters and Alarms	Fans and Alarms			
Switching tolerance:	+ - 4K					
Switching Capacity:	N.C. 240 VAC /10A N.O. 120 VAC / 15 A DC max 30watts					
Adjustment Range:	32-140° F / 0-60° C					
Connection:	Screw terminal for AWG 14 / (2.5mm2)					
Mounting:	Clip mounting on 35 mm DIN rails					
Dimension	Height 3.17" (80.5mm) Width 2.32" (59mm) Depth 1.5" (38mm)					
Housing:	Flame retardant plastic UL94VO					
Color:	Light Gray RAL7035					
Protection:	IP20					
Approval:	UL Recognized Component, cUL Recognized Component, CE					

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Hammond:

SKTD543 SKTD541 SKTD542C SKTD541C SKTD543C SKTD542