

5W DC-DC Regulated Single Output Converter

SLW05 series



Features :


- 2:1 wide input range
- 4:1 wide input range (optional)
- 1000VDC I/O isolation
- 3000VDC I/O isolation (option)
- Input Pi network filter
- Protections: Short circuit/ Over load
- Free air convection
- Six-sided shield metal case
- High reliability / Low cost
- 100% burn-in test
- 1 year warranty

SPECIFICATION

ORDER NO.		SLW05A-05	SLW05B-05	SLW05C-05	SLW05A-09	SLW05B-09	SLW05C-09	SLW05A-12	SLW05B-12	SLW05C-12	SLW05A-15	SLW05B-15	SLW05C-15	
OUTPUT	DC VOLTAGE	5V			9V			12V			15V			
	CURRENT RANGE	100 ~ 1000mA			55.6 ~ 556mA			41.7 ~ 417mA			33.3 ~ 333mA			
	RATED POWER	5W												
	VOLTAGE ACCURACY	±2.0%												
	RIPPLE & NOISE (max.) Note.2	50mVp-p			60mVp-p			60mVp-p			60mVp-p			
	LINE REGULATION Note.3	±0.2%												
	LOAD REGULATION Note.4	±0.5%												
SWITCHING FREQUENCY		50KHz min.												
INPUT	VOLTAGE RANGE	A: 9 ~ 18VDC B: 18~36VDC C: 36~72VDC												
	EFFICIENCY (Typ.)	75%	77%	77%	80%	80%	83%	80%	80%	83%	81%	81%	85%	
	DC CURRENT	Full load	A: 556mA B: 270mA C: 135mA											
		No load	A: 33mA B: 16mA C: 10mA											
FILTER		Pi network												
PROTECTION (Note. 5)	OVER CURRENT	160~250% rated output power												
		Protection type : Hiccup mode, recovers automatically after fault condition is removed												
	SHORT CIRCUIT	All output equipped with short circuit												
Protection type : Hiccup mode, recovers automatically after fault condition is removed														
ENVIRONMENT	WORKING TEMP.	-25~+71℃ (Refer to output load derating curve)												
	WORKING HUMIDITY	20%~90% RH non-condensing												
	STORAGE TEMP., HUMIDITY	-25~+105℃ 10~95% RH												
	TEMP. COEFFICIENT	±0.03% / ℃ (0~50℃)												
	VIBRATION	10~500Hz, 2G 10min./1cycle, period for 60min. each along X, Y, Z axes												
SAFETY & EMC	WITHSTAND VOLTAGE	I/P-O/P: 1KVDC												
	ISOLATION RESISTANCE	I/P-O/P: 100M Ohms / 500VDC												
OTHERS	MTBF	800khrs min. MIL-HDBK-217F(25℃)												
	DIMENSION	50.8*25.4*11.27mm or 2"*1"*0.44" inch (L*W*H)												
	WEIGHT	31g												

Mechanical Specification


Unit:mm(inch)



Pin Configuration

Pin no.	Output Single
1	+Vin
2	-Vin
3	+Vout
4	No Pin
5	-Vout

Derating Curve



NOTE

- 1.All parameters are specified at normal input, rated load, 25°C 70% RH. Ambient.
- 2.Ripple & noise are measured at 20MHz by using a 12" twisted pair terminated with a 0.1uf & 47uf capacitor.
- 3.Line regulation is measured from low line to high line at rated load.
- 4.Load regulation is measured from 10% to 100% rated load.
- 5.Please prevent the converter from operating in overload or short circuit condition for more than 30 seconds.