

SmartPro 5kVA Line Interactive Sine Wave UPS, SNMPWEBCARD option, 3U Rack/Tower, USB, Serial, EPO, 208V

MODEL NUMBER: **SMART5000TEL3U**



Description

Tripp Lite's SMART5000TEL3U intelligent, line interactive UPS protects server, networking and telecommunications equipment from blackouts, voltage fluctuations and surges in a compact rackmount housing. Completely self-contained UPS system occupies only 3 rack spaces (3U) in a standard 19 inch rack, making this model one of the smallest 5kVA UPS systems available. Included accessories support mounting 4 post rack enclosures. Large capacity 5000 VA/3750 watt UPS system accepts raw AC input, adjusting output to regulated 208V levels. One pair of 120V outlets support up to 600VA monitors and other low voltage accessories. Includes slot for internal SNMP/web card, plus 2 DB9 and 2 USB enhanced monitoring ports for unattended shutdown, remote control and monitoring of UPS system and power data. Five outlets (two L6-20R, one L6-30R and two 5-15R) allow the connection of high current 20 and 30 amp 208V connectors and up to two 120V devices (max 600VA at 120V).

Features

- Large 5000VA/3750-watt output capacity accommodates solitary large loads or multiple low-power loads
- High power density 5kVA power module occupies only 3 rack spaces (3U)
- 16 minutes half-load runtime (with a continuous load 2500VA; much longer runtime available at smaller loads)
- Line-interactive voltage regulation corrects severe brownouts and overvoltages without using battery power
- High voltage output supports 208V server, internetworking and telecom applications
- Pair of 120V outlets supports up to 600VA for standard 120V monitors, voicemail and other low-power networking devices
- Five total outlets (two L6-20R, one L6-30R and two 5-15R)
- Diagnostic LEDs provide visual indication of 17 separate performance conditions
- Included PowerAlert Software provides e-mail or pager notification of power problems and simultaneous automatic unattended shutdown of multiple servers
- 4 built-in communications ports (2 USB/2 DB9) for remote monitoring and unattended shutdown
- Slot for SNMP/web card (part#: SNMPWEBCARD) and environmental sensor (part#: ENVIROSENSE) for remote communications in large IP environments
- Emergency Power Off (EPO) interface for emergency shutoff in large facilities
- Hot-swappable/user-replaceable batteries allow on-site battery replacement through the front panel without powering off connected equipment or

Highlights

- 5kVA / 5000VA line interactive 3U rack/tower UPS; Sine wave output
- 208V nominal output during inputs of 174-282V; Supports 600VA 120V output
- USB, Serial, EPO & optional SNMP/Web card monitoring options
- 97% line-mode efficiency; Hot-swappable internal batteries
- NEMA L6-30P input; 2 NEMA 5-15R, 2 L6-20R & 1 L6-30R outlets

Package Includes

- SMART5000TEL3U UPS System
- PowerAlert Software and cabling
- Mounting hardware
- Instruction manual



removing the UPS from the rack

- UPS ships fully assembled and ready for installation; no time-consuming user battery connections required

Specifications

OUTPUT	
Output Volt Amp Capacity (VA)	5000
Output kVA capacity (kVA)	5
Output Watt Capacity (watts)	3750
Output kW capacity	3.8
Output power factor	0.8
Nominal Output Voltage(s) Supported	120V; 208V
Nominal Voltage details	120V output is limited to 600VA / 450 watts (maximum)
Frequency compatibility	60 Hz
Output voltage regulation (line mode)	208 & 120V (-6%, +20%)
Output voltage regulation (Battery mode)	+/- 5%
Built-in UPS output receptacles	2 5-15R outlet(s); 2 L6-20R outlet(s); 1 L6-30R outlet(s)
Output receptacle details	120V 5-15R outlets are limited to 600VA / 450 watts (maximum)
Output circuit breaker	20A double pole breaker supports L6-20R outlets, 5A breaker supports 5-15R outlets, L6-30R outlet is unbreakered
Output AC waveform (AC mode)	Sine wave
Output AC waveform (battery mode)	Pure Sine wave
INPUT	
Rated input current (at maximum load)	24A
Nominal Input Voltage(s) Supported	208V AC
UPS input connection type	L6-30P
UPS Input cord length (ft.)	10
UPS Input cord length (m)	3
Recommended Electrical Service	30A 208V
Phase	Single-Phase
BATTERY	
Full load runtime (minutes)	8.5 min. (3750w)
Half load runtime (minutes)	20 min. (1875w)



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

DC system voltage (VDC)	48
Battery recharge rate (included batteries)	Less than 4 hours from 10% to 90%
Replacement battery cartridge (internal UPS battery replacement)	RBC94-3U (quantity 3)
Battery Access	Front panel battery access door
Battery replacement description	Hot-swappable, user replaceable batteries
VOLTAGE REGULATION	
Voltage regulation description	Automatic voltage regulation (AVR) maintains line power operation with an input voltage range of 167 to 260
Overvoltage correction	Input voltages between 228V and 260V are reduced by 12%
Undervoltage correction	Input voltages between 167V and 194V are boosted by 12%
LEDS ALARMS & SWITCHES	
LED Indicators	5 LEDs indicate line power, battery power, overload, voltage regulation and battery low/replace status
Alarms	Audible alarm indicates power-failure, overload and low-battery conditions
Alarm cancel operation	Power-fail alarm can be silenced using alarm-cancel switch; once silenced, alarm will re-sound to indicate low-battery status
Switches	2 Switches control off/on power status and alarm-cancel/self-test operation
SURGE / NOISE SUPPRESSION	
UPS AC suppression joule rating	1020
UPS AC suppression response time	Instantaneous
EMI / RFI AC noise suppression	Yes
PHYSICAL	
Installation form factors supported with included accessories	4 post 19 inch rackmount
Installation form factors supported with optional accessories	2 post rackmount (2POSTRMKITWM); Tower (2-9USTAND)
Primary form factor	Rackmount
UPS / Power Module dimensions in primary form factor (height x width x depth / inches)	5.25 x 17.5 x 25
UPS / Power Module dimensions in primary form factor (height x width x depth / cm)	13.3 x 44.4 x 63.5
Rack Height	3U
Secondary form factor	Tower (requires 2-9USTAND)
UPS / Power Module weight (lbs)	143.3
UPS / Power Module weight (kg)	65.1



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

UPS Shipping dimensions (height x width x depth / inches)	11.2 x 23 x 31.5
UPS Shipping dimensions (height x width x depth / cm)	28.6 x 58.4 x 80
Shipping weight (lbs)	181.9
Shipping weight (kg)	82.6
Cooling method	Fan
UPS housing material	Steel
ENVIRONMENTAL	
Operating Temperature Range	+32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius
Storage Temperature Range	+5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius
Relative Humidity	0 to 95%, non-condensing
AC mode BTU / hr. (full load)	366
AC mode efficiency rating (100% load)	97%
COMMUNICATIONS	
Communications interface	USB; DB9 Serial; EPO (emergency power off); Slot for SNMP/Web interface
Network monitoring port description	Supports detailed monitoring of UPS and site power conditions
PowerAlert software	Included
Communications cable	USB and DB9 cabling included
WatchDog compatibility	Supports Watchdog application, OS and hard-reboot restart options for remote applications
LINE / BATTERY TRANSFER	
Transfer time	7 milliseconds (AC to Battery), 1 millisecond (Battery to AC)
Low voltage transfer to battery power (setpoint)	167
High voltage transfer to battery power (setpoint)	260
SPECIAL FEATURES	
Grounding lug	Back panel grounding lug
Cold Start (startup in battery mode during a power failure)	Cold-start operation supported
High availability UPS features	Hot swappable batteries
Green & high efficiency features	Greater than 95% efficiency - GREEN UPS
CERTIFICATIONS	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

UPS Certifications	Tested to UL1778 (USA); Tested to CSA (Canada); Meets FCC Part 15 Category A (EMI)
WARRANTY	
Product Warranty Period (Worldwide)	2-year warranty, 3 year with registration. Note: Registration is required for 3-year warranty.
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$250,000 Ultimate Lifetime Insurance

Related Items

Optional Products

Model Number	Description	Qty.
SNMPWEBCARD	For remote monitoring and control via SNMP, Web, or Telnet.	1
ENVIROSENSE	Monitors temperature, humidity and contact-closure inputs. (Requires SNMPWEBCARD or switched PDU.)	1
U022-010	10-ft. USB2.0 A/B Gold Device Cable (A Male to B Male)	1
DTEL2	Network Surge Suppressor - Essential protection for data and communication lines	1
DCATV	Network Surge Suppressor - Essential protection for TV/VCR coaxial lines	1
DNET1	Network Surge Suppressor - Essential protection for data and communication lines	1
WEXT5-5000TEL	5-Year Extended Warranty - For SMART5000TEL3U only	1
2-9USTAND	Enables Tower Placement of Rackmount UPS Systems	1
MODBUSCARD	For remote monitoring and control via MODBUS protocol	1
2POSTRMKITHD	Enables 2-Post Rackmount Installation of 3U and Larger UPS, Transformer and Battery Pack Components	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at:

<http://www.tripplite.com/sku/SMART5000TEL3U>.

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Tripp Lite:](#)

[SMART5000TEL3U](#)