42U SmartRack Value Series Standard-Depth Rack Enclosure Cabinet, 2000-lb. Capacity with doors, side, roof & bottom panels

MODEL NUMBER: **SR2000**

Highlights

- 42U SmartRack Economy Rack Enclosure Cabinet with doors, side, roof and bottom panels
- 4 interior vertical posts with unthreaded square hole openings
- 2000 lb stationary / 1100 lb rolling load capacity
- Standard 24" (600mm) width and 40" (1016 mm depth) for optimizing floor space
- Includes 40 pieces of M6 cage nuts and 40 pieces of M6 screws (equipment mounting hardware)

Package Includes

- (1) SR2000 SmartRack Economy Rack Enclosure Cabinet
- (1) Key sets for front / rear doors, and side panels
- (40) M6 Cage Nuts
- (40) M6 Screws
- (40) M6 Nylon Washers
- (2) Stabilizer brackets
- Owner's Manual

Description

Tripp Lite's SR2000 Economy SmartRack Enclosure Cabinets are designed for secure, high density server and networking applications in IT environments. Designed with provisions to integrate cooling, power distribution and cable management, SmartRack enclosures make ideal homes for mission-critical equipment. Toolless mounting accessory slots allow quick installation of PDUs and vertical cable managers. Lightweight modular doors and side panels provide safe, convenient service access. SmartRack enclosures support cooling, cable management, power distribution and monitoring features that keep critical servers and network equipment operating nonstop.

Features

- Ships fully assembled
- Ships with flat, front and rear doors, full length side panels, and roof and bottom panels
- 2000 lb stationary / 1100 lb rolling load capacity
- Rear sets of equipment mounting rails adjust in 3/8" increments.
- Toolless accessory mounting slots for quick installation of compatible PDUs and vertical cable managers. Mounting slots are arranged in an industry-standard pattern compatible with a wide variety of accessories. Each slot can accommodate two vertical PDUs or cable managers side-by-side (four items per enclosure).
- Rack Enclosure includes mounting hardware of 40 pieces of M6 cage nuts and 40 pieces of M6 screws
- Textured powder coat finish for tough resistance to environmental concerns such as deployment in warehouses.
- Maximum usable internal depth of 29.75 inches/756 mm (front to rear rail).
- Compatibility with airflow optimization accessories as well as cable management accessories.

Specifications

PHYSICAL

Installed Whole System Maximum Rack Depth (in.)	29.8
Installed Whole System Maximum Rack Depth (cm)	75.56
Installed Whole System Minimum Rack Depth (in.)	22.62
Installed Whole System Minimum Rack Depth (cm)	57.45
Rack Height (U Spaces)	42
Shipping Dimensions (hwd / in.)	82.86 x 25.75 x 45.5
Shipping Dimensions (hwd / cm)	210.46 x 65.40 x 115.57
Shipping Weight (lbs.)	219.4
Shipping Weight (kg)	98.73
Unit Dimensions (hwd / in.)	77.67 x 23.62 x 39.37
Unit Dimensions (hwd / cm)	197.28 x 59.99 x 100
Unit Weight (lbs.)	169.4
Unit Weight (kg)	76.23
Unit Dimensions (cm)	197.28 x 60 x 100
Color	Black
Weight Capacity - Stationary (lbs.)	2000
Weight Capacity - Rolling (lbs.)	1100
Weight Capacity - Stationary (kg)	900
Weight Capacity - Rolling (kg)	495
Hinged (Swings Away from Wall Bracket)	No

SPECIAL FEATURES

Seismic Rack	No

CERTIFICATIONS

Certifications	EIA/ECA-310-E; IP20
NOM (Mexico)	Tested to NOM (Mexico)
Approvals	RoHS

WARRANTY

Product Warranty Period (Worldwide)	5-year limited warranty