

C 091 A Characteristics

General Characteristics	Standard	Characteristics										
Number of contacts		2 ¹⁾ + 3	4	5	5 Stereo	6	7	7	8	12	14	
View on termination side of male contact insert												
Contact arrangement	DIN EN 61076-2-106	03-a ✓	04-a ✓	05-a ✓	05-b ✓	06-a ✓	07-a ✓	07-b ✓	08-a ✓	12-a ✓	14-a ✓	
Contact arrangement	IEC 60130-9 ²⁾	✓	✓		✓	✓		✓	✓			
Electrical Characteristics												
Rated voltage ³⁾	IEC 60664-1	300 V ≈ (100 V ≈)		300 V ≈ (63 V ≈)		100 V ≈ (32 V ≈)		300 V ≈ (63 V ≈)		100 V ≈ (32 V ≈)		150 V ≈ (32 V ≈)
Rated voltage	UL 1977	250 V										60 V
Rated impulse withstand voltage ³⁾	IEC 60664-1	1500 V (840 V)			1200 V (500 V)		1500 V (840 V)		1200 V (500 V)			
Pollution degree ³⁾	IEC 60664-1	1 (2)										
Installation category	IEC 60664-1	I										
Insulation group	IEC 60664-1	II, 400 ≤ CTI < 600										
Current rating	IEC 60512-5-2 UL 1977	5 A / + 40 °C / + 104 °F please refer also to current derating curves page 59									3 A / + 40 °C / + 104 °F	
Insulation resistance	IEC 60512-3-1	> 10 ¹⁰ Ω ⁴⁾										
Contact resistance	IEC 60512-2-1	< 5 m Ω										
Climatic Characteristics												
Climatic category	IEC 60068-1	40 / 100 / 56										
Temperature range	IEC 60068-1	- 40 °C ... + 100 °C / - 40 °F ... + 212 °F										
Mechanical Characteristics												
IP-degree	IEC 60529	IP 40										
Insertion and withdrawal forces	IEC 60512-13-2	25 N 90.oz	30 N 110.oz	35 N 125.oz		50 N 180.oz		55 N 200.oz		60 N 220.oz	50 N 180.oz	
Mechanical operation	IEC 60512-9-1	Silver ≥ 500 mating cycles Gold ≥ 1000 mating cycles										
Materials												
Housing material		coupling ring brass, strain relief, die cast, nickel plated										
Dielectric material		thermoplastic										
Contact plating		silver plated / gold plated ⁵⁾										
Further Characteristics												
Termination technique		solder, crimp										
Wire gauge		solder: ≤ 0,5 mm ² / 20 AWG crimp: 2 - 6 pol (excluding 5S): 0,09 - 1,00 mm ² / 28 - 18 AWG crimp: 5S, 7, 7S and 8-pol.: 0,09 - 0,75 mm ² / 28 - 20 AWG									solder: ≤ 0,25 mm ² / 24 AWG crimp: 0,09-0,25 mm ² / 28 - 24 AWG	
Flammability		UL 94 V0										
Locking system	IEC 60130-9 DIN EN 61076-2-106	metal screw coupling; tightening torque 0,7 Nm										

Caution: Do not connect or disconnect under load. Metal housing parts shall be securely incorporated to protected ground.

¹⁾ 2 contact version: contact loading 1+3

²⁾ Edition 2000-05

³⁾ values in brackets are according to DIN EN 61076-2-106

⁴⁾ under operating conditions >10⁸ Ω

⁵⁾ Remark for gold plated contacts: In order to avoid brittle inter-metallic connections, gold-plated terminals have to be tin-plated in the solder area.

IEC 60 664 ≙ DIN VDE 0110; IEC 60 512-x ≙ DIN EN 60 512-x; IEC 60 130-9 ≙ DIN EN 60 130-9; IEC 61076-2-106 ≙ DIN EN 61076-2-106

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol:

[C091 00V000 130 2](#) [TA 0000 502](#) [TA 0002 091 0001](#) [T 3200 001](#) [T 3200 005](#) [T 3200 018](#) [T 3201 001](#) [T 3201 018](#)
[T 3202 018](#) [T 3203 000](#) [T 3203 018](#) [T 3260 001](#) [T 3260 002](#) [T 3260 005](#) [T 3260 018](#) [T 3261 001](#) [T 3262 000](#) [T](#)
[3263 000](#) [T 3263 018](#) [T 3263 100](#) [T 3263 400](#) [T 3300 001](#) [T 3300 002](#) [T 3300 005](#) [T 3300 018](#) [T 3301 001](#) [T 3302](#)
[000](#) [T 3303 000](#) [T 3303 018](#) [T 3303 100](#) [T 3303 400](#) [T 3356 005](#) [T 3359 018](#) [T 3359 100](#) [T 3360 001](#) [T 3360 002](#)
[T 3360 005](#) [T 3360 010](#) [T 3360 018](#) [T 3360 551](#) [T 3361 001](#) [T 3361 010](#) [T 3362 000](#) [T 3362 010](#) [T 3362 400](#) [T](#)
[3363 000](#) [T 3363 010](#) [T 3363 018](#) [T 3363 100](#) [T 3363 400](#) [T 3400 001](#) [T 3400 002](#) [T 3400 005](#) [T 3400 018](#) [T 3401](#)
[001](#) [T 3402 000](#) [T 3403 000](#) [T 3403 018](#) [T 3403 100](#) [T 3403 400](#) [T 3475 001](#) [T 3475 002](#) [T 3475 005](#) [T 3475 018](#)
[T 3476 001](#) [T 3476 552](#) [T 3477 000](#) [T 3477 400](#) [T 3478 000](#) [T 3478 100](#) [T 3478 400](#) [T 3484 001](#) [T 3484 005](#) [T](#)
[3485 001](#) [T 3487 000](#) [T 3487 100](#) [T 3504 001](#) [T 3504 002](#) [T 3504 005](#) [T 3504 018](#) [T 3505 001](#) [T 3506 000](#) [T 3507](#)
[000](#) [T 3507 009](#) [T 3507 018](#) [T 3507 100](#) [T 3507 400](#) [T 3635 000](#) [T 3635 001](#) [T 3635 002](#) [T 3635 005](#) [T 3636 001](#)
[T 3636 002](#) [T 3638 000](#) [T 3638 004](#) [T 3638 100](#) [T 3650 000](#) [T 3650 001](#) [T 3650 005](#) [T 3651 001](#)