



VANESSA 12 LED BOARD PERFORMANCE at 25°C (2x6 Parallel Configuration)

ADURA Module P/N	Typical Wattage (W)	OPERATING CURRENT		INPUT VOLTAGE (Vdc)	CCT (Kelvin)	CRI	TYPICAL LUMEN (lm)	Typical Lumens Per Watt (LPW)
		Nominal Current (mA)	Max Current (mA)					
Lin-150036D-0123535-277-2x6	12	700	3000	17.0	2700K	70	1699	143
	17	1000		17.4			2343	135
	25	1400		17.9			3134	125
	37	2000		18.3			4213	115
	45	2400		18.6			4886	109
LIN-150036D-0123535-307-2x6	12	700	3000	17.0	3000K	70	1746	147
	17	1000		17.4			2407	138
	25	1400		17.9			3220	129
	37	2000		18.3			4329	118
	45	2400		18.6			5021	112
LIN-150036D-0123535-357-2x6	12	700	3000	17.0	3500K	70	1799	151
	17	1000		17.4			2481	143
	25	1400		17.9			3318	133
	37	2000		18.3			4461	122
	45	2400		18.6			5174	116
LIN-150036D-0123535-407-2x6	12	700	3000	17.0	4000K	70	1912	161
	17	1000		17.4			2637	152
	25	1400		17.9			3527	141
	37	2000		18.3			4742	129
	45	2400		18.6			5500	123
LIN-150036D-0123535-457-2x6	12	700	3000	17.0	4500K	70	1972	166
	17	1000		17.4			2721	156
	25	1400		17.9			3646	146
	37	2000		18.3			4922	134
	45	2400		18.6			5653	127
LIN-150036D-0123535-507-2x6	12	700	3000	17.0	5000K	70	1985	167
	17	1000		17.4			2743	158
	25	1400		17.9			3676	147
	37	2000		18.3			4949	135
	45	2400		18.6			5747	129
LIN-150036D-0123535-577-2x6	12	700	3000	17.0	5700K	70	1964	165
	17	1000		17.4			2715	156
	25	1400		17.9			3638	146
	37	2000		18.3			4898	133
	45	2400		18.6			5687	127
LIN-150036D-0123535-657-2x6	12	700	3000	17.0	6500K	70	1937	163
	17	1000		17.4			2677	154
	25	1400		17.9			3587	143
	37	2000		18.3			4829	132
	45	2400		18.6			5608	126

ADURA Module P/N	Typical Wattage (W)	OPERATING CURRENT		INPUT VOLTAGE (Vdc)	CCT (Kelvin)	CRI	TYPICAL LUMEN (lm)	Typical Lumens Per Watt (LPW)
		Nominal Current (mA)	Max Current (mA)					
LIN-150036D-0123535-278-2x6	12	700	3000	17.0	2700K	80	1619	136
	17	1000		17.4			2233	128
	25	1400		17.9			2987	119
	37	2000		18.3			4016	109
	45	2400		18.6			4658	104
LIN-150036D-0123535-308-2x6	12	700	3000	17.0	3000K	80	1716	144
	17	1000		17.4			2366	136
	25	1400		17.9			3165	127
	37	2000		18.3			4255	116
	45	2400		18.6			4935	110
LIN-150036D-0123535-358-2x6	12	700	3000	17.0	3500K	80	1792	151
	17	1000		17.4			2471	142
	25	1400		17.9			3305	132
	37	2000		18.3			4443	121
	45	2400		18.6			5153	115
LIN-150036D-0123535-408-2x6	12	700	3000	17.0	4000K	80	1806	152
	17	1000		17.4			2490	143
	25	1400		17.9			3331	133
	37	2000		18.3			4477	122
	45	2400		18.6			5193	116
LIN-150036D-0123535-458-2x6	12	700	3000	17.0	4500K	80	1826	154
	17	1000		17.4			2518	145
	25	1400		17.9			3369	135
	37	2000		18.3			4529	123
	45	2400		18.6			5253	118
LIN-150036D-0123535-508-2x6	12	700	3000	17.0	5000K	80	1765	148
	17	1000		17.4			2439	140
	25	1400		17.9			3269	131
	37	2000		18.3			4401	120
	45	2400		18.6			5111	114
LIN-150036D-0123535-279-2x6	12	700	3000	17.0	2700K	90	1205	101
	17	1000		17.4			1673	96
	25	1400		17.9			2247	90
	37	2000		18.3			3024	82
	45	2400		18.6			3512	79
LIN-150036D-0123535-309-2x6	12	700	3000	17.0	3000K	90	1300	109
	17	1000		17.4			1806	104
	25	1400		17.9			2425	97
	37	2000		18.3			3263	89
	45	2400		18.6			3790	85

ADURA Module P/N	Typical Wattage (W)	OPERATING CURRENT		INPUT VOLTAGE (Vdc)	CCT (Kelvin)	CRI	TYPICAL LUMEN (lm)	Typical Lumens Per Watt (LPW)
		Nominal Current (mA)	Max Current (mA)					
LIN-150036D-0123535-359-2x6	12	700	3000	17.0	3500K	90	1304	110
	17	1000		17.4			1811	104
	25	1400		17.9			2431	97
	37	2000		18.3			3272	89
	45	2400		18.6			3800	85
LIN-150036D-0123535-407-2x6	12	700	3000	17.0	4000K	90	1355	114
	17	1000		17.4			1882	108
	25	1400		17.9			2527	101
	37	2000		18.3			3401	93
	45	2400		18.6			3950	88