

Capacitor, tantalum, 33 uF, 6032, +/-10% Tol, 16V@85C



Cutout at KEMET's option (either end); see note about P and R dimensions and cutout.

Dimensions (mm)

Specifications

ID	Dimension	Tolerance	Manufacturer:	KEMET
L	6	+/-0.3	Capacitance:	33 uF
w	3.2	+/-0.3	Voltage DC @ 85C:	16V
н	2.5	+/-0.3	Voltage DC @ 105C:	13V
к	1.4	+/-0.2	Voltage DC @ 125C:	10V
F	2.2	+/-0.1	Tolerance:	+/-10%
S	1.3	+/-0.3	Application:	General Purpose
В	0.5	+/-0.15	Body Type:	Molded Chip
х	0.1	ref	Temperature Range:	-55/+125C
Р	0.9	ref	Footprint:	6032
R	1	ref	Termination:	Tin
т	0.13	ref	Leakage Current:	5.3 uA
Α	2.5	ref	Dissipation Factor:	6%
G	2.8	ref	Impedance @ 100kHz:	1.4 Ohm
E	2.4	ref	Package Kind:	T&R
			Package Quantity:	3000

Notes: -C



© 2006-2012 IntelliData.net

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.