

Solid Tantalum Surface Mount Capacitors TANTAMOUNT[®], Molded Case, Hi-Rel COTS, Low ESR, Built-In-Fuse


FEATURES

- Terminations: 100 % matte tin, standard, tin/lead available
- Molded case available in three case sizes
- Compatible with "High Volume" automatic pick and place equipment
- High ripple current carrying capability
- Meets EIA 535BAAC case sizes
- Weibull grading and surge current test options per MIL-PRF-55365
- Standard and low ESR options
- Compliant to RoHS Directive 2002/95/EC


RoHS*
COMPLIANT

PERFORMANCE/ELECTRICAL CHARACTERISTICS

Operating Temperature: - 55 °C to + 125 °C
(Above 85 °C voltage derating is required)

Capacitance Range: 0.47 μF to 470 μF

Capacitance Tolerance: ± 10 %, ± 20 %

Voltage Rating: 4 V_{DC} to 50 V_{DC}

ORDERING INFORMATION								
T86	D	107	K	010	E	A	A	S
TYPE	CASE CODE	CAPACITANCE	CAPACITANCE TOLERANCE	DC VOLTAGE RATING AT + 85 °C	TERMINATION/PACKAGING	RELIABILITY LEVEL	SURGE CURRENT	ESR
	See Ratings and Case Codes Table	This is expressed in picofarads. The first two digits are the significant figures. The third is the number of zeros to follow	K = ± 10 % M = ± 20 %	This is expressed in V. To complete the three-digit block, zeros precede the voltage rating. A decimal point is indicated by an "R" (6R3 = 6.3 V)	C = Matte tin/ 7" (178 mm) reel H = Matte tin/ 7" (178 mm), 1/2 reel E = Tin/lead/ 7" (178 mm) reel L = Tin/lead/ 7" (178 mm), 1/2 reel	A = 1.0 % B = 0.1 % S = Hi-Rel standard Z = Non-ER	A = 10 cycles at + 25 °C B = 10 cycles at - 55 °C/+ 85 °C S = 3 cycles at + 25 °C	S = Std. L = Low

DIMENSIONS in inches [millimeters]							
CASE CODE	EIA SIZE	L	W	H	P	Tw	Th (MIN.)
C	6032-28	0.236 ± 0.012 [6.0 ± 0.30]	0.126 ± 0.012 [3.2 ± 0.30]	0.098 ± 0.012 [2.5 ± 0.30]	0.051 ± 0.012 [1.3 ± 0.30]	0.087 ± 0.004 [2.2 ± 0.10]	0.039 [1.0]
D	7343-31	0.287 ± 0.012 [7.3 ± 0.30]	0.170 ± 0.012 [4.3 ± 0.30]	0.110 ± 0.012 [2.8 ± 0.30]	0.051 ± 0.012 [1.3 ± 0.30]	0.095 ± 0.004 [2.4 ± 0.10]	0.039 [1.0]
E	7343-43	0.287 ± 0.012 [7.3 ± 0.30]	0.170 ± 0.012 [4.3 ± 0.30]	0.158 ± 0.012 [4.0 ± 0.30]	0.051 ± 0.012 [1.3 ± 0.30]	0.095 ± 0.004 [2.4 ± 0.10]	0.039 [1.0]

* Pb containing terminations are not RoHS compliant, exemptions may apply

RATINGS AND CASE CODES								
μF	4 V	6.3 V	10 V	16 V	20 V	25 V	35 V	50 V
0.47								C
0.68								C
1.0								C
1.5							C	C
2.2						C	C	C/D
3.3						C	C	C/D
4.7					C	C	C/D	D
6.8				C	C	C	D	D/E
10			C	C	C	C/D	D/E	
15		C	C	C	C/D	D	D/E	
22		C	C	C/D	D	D/E	E	
33		C	C/D	C/D	D/E	E		
47		C/D	C/D	D/E	E			
68	C	C/D	D/E	D	E			
100	C	D/E	D	E				
150	D	D	D/E	E				
220	D	D/E	E					
330	D/E	E						
470	E							

CONSTRUCTION AND MARKING

C, D, E, Cases

Marking:
Capacitor marking includes an anode (+) polarity band, capacitance in microfarads and the voltage rating. The Vishay Sprague[®] trademark is included if space permits. Capacitors rated at 6.3 V are marked 6 V. A manufacturing date code is marked on all capacitors. Capital letter “E” stands for lead (Pb)-free terminations small cap letter “e” stands for SnPb



Solid Tantalum Surface Mount Capacitors TANTAMOUNT®,
Molded Case, Hi-Rel COTS, Low ESR, Built-In-Fuse

Vishay Sprague

STANDARD RATINGS						
CAPACITANCE (μF)	CASE CODE	PART NUMBER	MAX. DC LEAKAGE at + 25 °C (μA)	MAX. DF at + 25 °C 120 Hz (%)	STANDARD (S) MAX. ESR at + 25 °C 100 kHz (Ω)	LOW (L) MAX. ESR at + 25 °C 100 kHz (Ω)
4 V_{DC} AT + 85 °C, 2.7 V_{DC} AT + 125 °C						
68	C	T86C686(1)004(2)(3)(4)(5)	2.7	8	1.40	0.40
100	C	T86C107(1)004(2)(3)(4)(5)	4.0	8	0.80	0.40
150	D	T86D157(1)004(2)(3)(4)(5)	6.0	8	0.60	0.30
220	D	T86D227(1)004(2)(3)(4)(5)	8.8	8	0.60	0.40
330	D	T86D337(1)004(2)(3)(4)(5)	13.2	15	0.60	0.30
330	E	T86E337(1)004(2)(3)(4)(5)	13.2	8	0.50	0.30
470	E	T86E477(1)004(2)(3)(4)(5)	18.8	16	0.50	0.25
6.3 V_{DC} AT + 85 °C, 4 V_{DC} AT + 125 °C						
15	C	T86C156(1)6R3(2)(3)(4)(5)	0.9	6	1.80	0.60
22	C	T86C226(1)6R3(2)(3)(4)(5)	1.1	6	1.80	0.60
33	C	T86C336(1)6R3(2)(3)(4)(5)	1.6	6	1.40	0.60
47	C	T86C476(1)6R3(2)(3)(4)(5)	2.3	6	1.30	0.60
47	D	T86D476(1)6R3(2)(3)(4)(5)	2.3	6	0.90	0.45
68	C	T86C686(1)6R3(2)(3)(4)S	3.3	6	0.80	N/A
68	D	T86D686(1)6R3(2)(3)(4)(5)	3.3	6	0.70	0.35
100	D	T86D107(1)6R3(2)(3)(4)(5)	6.0	8	0.70	0.35
100	E	T86E107(1)6R3(2)(3)(4)(5)	6.0	8	0.70	0.30
150	D	T86D157(1)6R3(2)(3)(4)(5)	9.0	8	0.60	0.30
220	D	T86D227(1)6R3(2)(3)(4)(5)	13.2	8	0.60	0.30
220	E	T86E227(1)6R3(2)(3)(4)(5)	13.2	8	0.50	0.30
330	E	T86E337(1)6R3(2)(3)(4)(5)	19.8	8	0.50	0.30
10 V_{DC} AT + 85 °C, 7 V_{DC} AT + 125 °C						
10	C	T86C106(1)010(2)(3)(4)S	1.0	6	1.80	N/A
15	C	T86C156(1)010(2)(3)(4)(5)	1.5	6	1.80	0.60
22	C	T86C226(1)010(2)(3)(4)(5)	2.2	6	1.40	0.50
33	C	T86C336(1)010(2)(3)(4)(5)	3.3	6	1.30	0.40
33	D	T86D336(1)010(2)(3)(4)(5)	3.3	6	0.90	0.40
47	C	T86C476(1)010(2)(3)(4)S	4.7	6	1.00	N/A
47	D	T86D476(1)010(2)(3)(4)(5)	4.7	6	0.70	0.40
68	D	T86D686(1)010(2)(3)(4)(5)	6.8	6	0.70	0.35
68	E	T86E686(1)010(2)(3)(4)(5)	6.8	6	0.70	0.35
100	D	T86D107(1)010(2)(3)(4)(5)	10.0	8	0.60	0.30
150	D	T86D157(1)010(2)(3)(4)(5)	15.0	8	0.60	0.30
150	E	T86E157(1)010(2)(3)(4)(5)	15.0	8	0.50	0.40
220	E	T86E227(1)010(2)(3)(4)(5)	22.0	8	0.50	0.30
16 V_{DC} AT + 85 °C, 10 V_{DC} AT + 125 °C						
6.8	C	T86C685(1)016(2)(3)(4)(5)	1.1	6	2.00	0.60
10	C	T86C106(1)016(2)(3)(4)(5)	1.6	6	1.80	0.70
15	C	T86C156(1)016(2)(3)(4)S	2.4	6	1.40	N/A
22	C	T86C226(1)016(2)(3)(4)(5)	3.5	6	1.30	0.70
22	D	T86D226(1)016(2)(3)(4)(5)	3.5	6	0.90	0.45
33	C	T86C336(1)016(2)(3)(4)(5)	5.3	6	1.00	0.50
33	D	T86D336(1)016(2)(3)(4)(5)	5.3	6	0.70	0.35
47	D	T86D476(1)016(2)(3)(4)(5)	7.5	6	0.70	0.35
47	E	T86E476(1)016(2)(3)(4)(5)	7.5	6	0.70	0.35
68	D	T86D686(1)016(2)(3)(4)(5)	10.9	6	0.60	0.30
100	E	T86E107(1)016(2)(3)(4)(5)	16.0	8	0.60	0.30
150	E	T86E157(1)016(2)(3)(4)S	24.0	10	0.40	N/A



STANDARD RATINGS						
CAPACITANCE (μ F)	CASE CODE	PART NUMBER	MAX. DC LEAKAGE at + 25 °C (μ A)	MAX. DF at + 25 °C 120 Hz (%)	STANDARD (S) MAX. ESR at + 25 °C 100 kHz (Ω)	LOW (L) MAX. ESR at + 25 °C 100 kHz (Ω)
20 V_{DC} AT + 85 °C, 13 V_{DC} AT + 125 °C						
4.7	C	T86C475(1)020(2)(3)(4)(5)	0.9	6	2.00	1.00
6.8	C	T86C685(1)020(2)(3)(4)(5)	1.4	6	1.90	0.60
10	C	T86C106(1)020(2)(3)(4)(5)	2.0	6	1.60	0.80
15	C	T86C156(1)020(2)(3)(4)S	3.0	6	1.40	N/A
15	D	T86D156(1)020(2)(3)(4)(5)	3.0	6	0.90	0.45
22	D	T86D226(1)020(2)(3)(4)(5)	4.4	6	0.70	0.35
33	D	T86D336(1)020(2)(3)(4)(5)	6.6	6	0.70	0.40
33	E	T86E336(1)020(2)(3)(4)(5)	6.6	6	0.70	0.40
47	E	T86E476(1)020(2)(3)(4)(5)	9.4	6	0.60	0.30
68	E	T86E686(1)020(2)(3)(4)(5)	13.6	6	0.60	0.30
25 V_{DC} AT + 85 °C, 17 V_{DC} AT + 125 °C						
2.2	C	T86C225(1)025(2)(3)(4)S	0.6	6	2.80	N/A
3.3	C	T86C335(1)025(2)(3)(4)(5)	0.8	6	2.30	2.10
4.7	C	T86C475(1)025(2)(3)(4)(5)	1.2	6	1.90	1.00
6.8	C	T86C685(1)025(2)(3)(4)(5)	1.7	6	1.60	0.60
10	C	T86C106(1)025(2)(3)(4)(5)	2.5	6	1.40	0.60
10	D	T86D106(1)025(2)(3)(4)(5)	2.5	6	1.00	0.50
15	D	T86D156(1)025(2)(3)(4)(5)	3.8	6	0.80	0.40
22	D	T86D226(1)025(2)(3)(4)(5)	5.5	6	0.70	0.35
22	E	T86E226(1)025(2)(3)(4)(5)	5.5	6	0.70	0.35
33	E	T86E336(1)025(2)(3)(4)(5)	8.3	6	0.60	0.30
35 V_{DC} AT + 85 °C, 23 V_{DC} AT + 125 °C						
1.5	C	T86C155(1)035(2)(3)(4)(5)	0.5	6	3.80	2.60
2.2	C	T86C225(1)035(2)(3)(4)S	0.8	6	2.90	N/A
3.3	C	T86C335(1)035(2)(3)(4)S	1.2	6	2.00	N/A
4.7	C	T86C475(1)035(2)(3)(4)S	1.6	6	1.80	N/A
4.7	D	T86D475(1)035(2)(3)(4)(5)	1.6	6	1.20	0.60
6.8	D	T86D685(1)035(2)(3)(4)(5)	2.4	6	1.00	0.50
10	D	T86D106(1)035(2)(3)(4)(5)	3.5	6	0.80	0.50
10	E	T86E106(1)035(2)(3)(4)(5)	3.5	6	0.80	0.50
15	D	T86D156(1)035(2)(3)(4)(5)	5.3	6	0.70	0.50
15	E	T86E156(1)035(2)(3)(4)(5)	5.3	6	0.70	0.50
22	E	T86E226(1)035(2)(3)(4)S	7.7	6	0.60	N/A
50 V_{DC} AT + 85 °C, 33 V_{DC} AT + 125 °C						
0.47	C	T86C474(1)050(2)(3)(4)S	0.5	4	6.70	N/A
0.68	C	T86C684(1)050(2)(3)(4)S	0.5	4	5.90	N/A
1.0	C	T86C105(1)050(2)(3)(4)(5)	0.5	4	4.40	2.70
1.5	C	T86C155(1)050(2)(3)(4)(5)	0.8	6	5.00	3.20
2.2	C	T86C225(1)050(2)(3)(4)S	1.1	6	2.80	N/A
2.2	D	T86D225(1)050(2)(3)(4)(5)	1.1	6	2.10	0.90
3.3	C	T86C335(1)050(2)(3)(4)(5)	1.7	6	2.40	1.60
3.3	D	T86D335(1)050(2)(3)(4)S	1.7	6	2.00	N/A
4.7	D	T86D475(1)050(2)(3)(4)S	2.4	6	1.10	N/A
6.8	D	T86D685(1)050(2)(3)(4)S	3.4	6	0.90	N/A
6.8	E	T86E685(1)050(2)(3)(4)S	3.4	6	0.90	N/A

Notes


- (1) Capacitance tolerance codes: K, M
- (2) Terminations and packaging codes: C, H, E, L
- (3) Reliability level: A, B, S, Z
- (4) Surge current: A, B, S
- (5) ESR: L, S



Solid Tantalum Surface Mount Capacitors TANTAMOUNT[®],
Molded Case, Hi-Rel COTS, Low ESR, Built-In-Fuse

Vishay Sprague

TYPICAL CURVES AT + 25 °C, IMPEDANCE AND ESR VS. FREQUENCY





Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.